



2. CIRCUIT DIAGRAM(接线图)



A端	线材	B端
1	1	1
2	2	2
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
8	8	8
9	9	9
10	10	10
11	11	11
12	12	12
13	13	13
14	14	14
15	15	15
16	16	16
17	17	17
18	18	18
19	19	19
20	20	20
21	21	21
22	22	22
23	23	23
24	24	24
25	25	25
26	26	26
27	27	27
28	28	28
29	29	29
30	30	30
31	31	31
32	32	32
33	33	33
34	34	34
35	35	35
36	36	36
37	37	37
38	38	38
39	39	39
40	40	40
41	41	41
42	42	42
43	43	43
44	44	44
45	45	45
46	46	46
47	47	47
48	48	48
49	49	49
50	50	50
51	51	51
52	52	52
53	53	53
54	54	54
55	55	55
56	56	56
57	57	57
58	58	58
59	59	59
60	60	60
61	61	61
62	62	62
63	63	63
64	64	64
65	65	65
66	66	66
67	67	67
68	68	68
69	69	69
70	70	70
71	71	71
72	72	72
73	73	73
74	74	74
75	75	75
76	76	76
77	77	77
78	78	78
79	79	79
80	80	80
81	81	81
82	82	82
83	83	83
84	84	84
85	85	85
86	86	86
87	87	87
88	88	88
89	89	89
90	90	90
91	91	91
92	92	92
93	93	93
94	94	94
95	95	95
96	96	96
97	97	97
98	98	98
99	99	99
100	100	100

1	红色	Red	9
2	黑色	Black	8
3	黄色	Yellow	7
4	绿色	Green	6
5	蓝色	Blue	5
6	白色	White	4
7	橙色	Orange	3
8	紫色	Purple	2
9	棕色	Brown	1



A端点位图

3. Final examination(成品检查)

- 1) 100%外形尺寸:所有尺寸与图示一致.
- 2) 外观:a)电线圆实平滑,颜色均匀,外被表面无破损、划伤、脏污、变形等缺陷;
- 3) 结构:线材和各插头五金以及各接触件应牢固无松动,标志清晰,正确无误;
- 4) 导通性能:100%测试,DC300V,绝缘 $\geq 20M\Omega$,导通电阻 $< 1\Omega$,无断路或触不良现象,测试时应加摇摆测试.

序列号	名称	规格				数量	备注	
1	胶壳	X9396H-09-N0				2PCS		
2	端子	X9396T-PSN-BSN				18PCS		
3	线缆	UL1007/20AWG				9PCS	裁线长度：310MM	
					DRAWING NO.			RVE.
					X9396胶壳定制线			A0
					UNIT			
RVE.	DESCRIPTION				DATE	SCALE		Free
DESIGNED		DATE			PAGE	1 OF 1		
CHECKED		DATE		X9396T-PSN-09-A20RBYGLW (YR) PN-X9396T-L300-F				
APPROVED		DATE						