


CAN transceiver for 42 V systems


The HT2551A is the interface between the CAN protocol controller and the physical bus.. The device provides differential transmit capability to the bus and differential receive capability to the CAN controller. The IC is in-tended for automotive electronic applications


Main features

- Fully compatible with the “ISO 11898-24 V” standard
- Thermally protected
- Short-circuit proof
- Three mode operation
- High speed of data transfer (up to 1 Mbit/s)
- High immunity against electromagnetic interference.
- Permissible value of electrostatic potential is 2000V.



Pin layout





VD1, VD2 – diodes;
VT1, VT2 - transistors

Fig. 3 – Block diagram

Table 2 – Absolute maximum ratings

Symbol	Parameter	Target		Unit
		Min	Max	
V_{CC}	Supply voltage	-0,3	7,0	V
V_n	01, 04, 05, 08 pin voltage	-0,3	$V_{CC} + 0,3$	V
V_{tr}	06, 07 pin transient voltage	-200	200	V
T_{stg}	Storage temperature	-60	150	°C
T_j	Junction temperature	-	150	°C

Table 3 – Recommended operating condition

Symbol	Parameter	Target		Unit
		Min	Max	
V_{CC}	Supply voltage	4,5	5,5	V
V_{CAN}	Input/output high and low level voltage of CAN - signal	-42	42	V

Table 4 – Electric parameters at $-40 \leq T_{amb} \leq +125$ °C

Symbol	Parameter	Measurement mode	Target		Unit
			Min	Max	
Supply					
I ₃	Supply current	Dominant; V ₁ = 1,0 V, V _{CC} < 5,1 V	-	78	mA
		Dominant; V ₁ = 1,0 V, V _{CC} < 5,25 V	-	80	
		Dominant; V ₁ = 1,0 V, V _{CC} < 5,5 V	-	85	
		Recessive; V ₁ = 4,0 V, R ₈ = 47 kΩ	-	10	
		Standby mode ¹⁾	-	0,315	
		Standby mode ²⁾	-	0,275	
Transmitter					
V _{IH}	High-level input voltage	Output recessive	0,7 V _{CC}	V _{CC} +0,3	V
V _{IL}	Low-level input voltage	Output dominant	-0,3	0,3 V _{CC}	V
I _{IH}	High-level input current	4,5 V < V _{CC} < 5,5 V V ₁ = 4,0 V	-200	30	μA
I _{IL}	Low-level input current	4,5 V < V _{CC} < 5,5 V V ₁ = 1,0 V	-200	-100	μA
V _{6,7}	Recessive bus voltage	4,5 V < V _{CC} < 5,5 V V ₁ = 4,0 V, no load	2,0	3,0	V
I _{LO}	Off-state output leakage current	4, 5 V < V _{CC} < 5,5 V -2, 0 V < (V ₆ , V ₇) < 7,0 V	-2,0	2,0	mA
		4, 5 V < V _{CC} < 5,5 V -5, 0 V < (V ₆ , V ₇) < 36 V	-10	10	
V ₇	CANH output voltage	4,75 V < V _{CC} < 5,5 V V ₁ = 1,0 V	3,0	4,5	V
		V ₁ = 1,0 V 4,5 V < V _{CC} < 4,75 V	2,75	4,5	
V ₆	CANL output voltage	4,5 V < V _{CC} < 5,5 V V ₁ = 1,0 V	0,5	2,0	V

Table 4 continued

Symbol	Parameter	Measurement mode	Target		Unit
			Min	Max	
$\Delta V_{6,7}$	difference between output voltage at pins 6 and 7	$4,5\text{ V} < V_{CC} < 5,5\text{ V}$ $V_1 = 1,0\text{ V}$	1,5	3,0	V
		$V_1 = 1,0\text{ V}, R_L = 45\ \Omega$	1,5	-	
		$V_1 = 4,0\text{ V}, \text{no load}$	-0,5	0,05	
I_{SC7}	CANH short-circuit current	$4,5\text{ V} < V_{CC} < 5,5\text{ V}$ $V_7 = -5,0\text{ V}$	-	-200	mA
I_{SC6}	CANL signal short-circuit current	$4,5\text{ V} < V_{CC} < 5,5\text{ V}$ $V_6 = 36\text{ V}$	-	200	mA
Receiver (pins 06, 07 are externally controlled, $V_4 = 4,0\text{ V}$, $-2,0\text{ V} < (V_6, V_7) < 7,0\text{ V}$, unless otherwise specified)					
$V_{DIFF(R)}$	Differential input voltage (recessive mode)	³⁾	-1,0	0,5	V
		$4,5\text{ V} < V_{CC} < 5,5\text{ V}$ $-7,0\text{ V} < (V_6, V_7) < 12\text{ V}$ ₃₎	-1,0	0,4	
$V_{DIFF(D)}$	Differential input voltage (dominant mode)	-	0,9	5,0	V
		$4,5\text{ V} < V_{CC} < 5,5\text{ V}$ $-7,0\text{ V} < (V_6, V_7) < 12\text{ V}$ ₄₎	1,0	5,0	
		₄₎	0,97	5,0	
		$4,5\text{ V} < V_{CC} < 5,1\text{ V}$ ₄₎	0,91	5,0	
V_{OH}	High-level output voltage (pin 4)	$4,5\text{ V} < V_{CC} < 5,5\text{ V}$ $I_4 = -100\ \mu\text{A}$	$0,8 V_{CC}$	V_{CC}	V
V_{OL}	Low-level output voltage (pin 4)	$4,5\text{ V} < V_{CC} < 5,5\text{ V}$ $I_4 = 1,0\text{ mA}$	0	$0,2 V_{CC}$	V
		$4,5\text{ V} < V_{CC} < 5,5\text{ V}$ $I_4 = 10\text{ mA}$	0	1,5	
R_I	CANL and CANH input resistance I	$4,5\text{ V} < V_{CC} < 5,5\text{ V}$	5,0	25	k Ω
R_{DIFF}	Differential input resistance	$4,5\text{ V} < V_{CC} < 5,5\text{ V}$	20	100	k Ω
Reference voltage					
V_{REF}	Reference voltage	$4,5\text{ V} < V_{CC} < 5,5\text{ V}$ $V_8 = 1,0\text{ V}, I_5 < 50\text{ mA}$	$0,45 V_{CC}$	$0,55 V_{CC}$	V
		$4,5\text{ V} < V_{CC} < 5,5\text{ V}$ $V_8 = 4,0\text{ V}, I_5 < 5,0\ \mu\text{A}$	$0,4 V_{CC}$	$0,6 V_{CC}$	

Table 4 continued

Symbol	Parameter	Measurement mode	Target		Unit
			Min	Max	
Timing parameters ($R_L = 60 \Omega$, $C_L = 100 \text{ pF}$, unless otherwise specified)					
t_{bit}	One bit transmitting minimum time	$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$ $R_8 = 0 \Omega$	-	1,0	μs
t_{onTXD}	Input data transfer to active bus delay	$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$ $R_8 = 0 \Omega$	-	50	ns
t_{offTXD}	Input data transfer to inactive bus delay	$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$ $R_8 = 0 \Omega$	-	80	ns
t_{onRXD}	Input data transfer to active receiver delay	$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$ $R_8 = 0 \Omega$	-	120	ns
		$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$ $R_8 = 47 \text{ k}\Omega$	-	550	
t_{offRXD}	Input data transfer to inactive receiver delay	$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$ $R_8 = 0 \Omega$	-	190	ns
		$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$ $R_8 = 47 \text{ k}\Omega$	-	400	
t_{WAKE}	Wake-up time from standby mode (via 08 pin)	$4, 5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$	-	20	μs
t_{dRXDL}	Bus input data transfer delay to low on output of received data	$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$ $V_8 = 4,0 \text{ V}$	-	3,0	μs
Standby mode and low RFI mode					
V_{stb}	Input voltage for standby mode	$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$	$0,75 V_{\text{CC}}$	-	V
I_{slope}	Input current for low RFI mode	$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$	- 200	- 10	μA
V_{slope}	Input voltage for low RFI mode	$4,5 \text{ V} < V_{\text{CC}} < 5,5 \text{ V}$	$0,4 V_{\text{CC}}$	$0,6 V_{\text{CC}}$	V
1) $I_1 = I_4 = I_5 = 0 \text{ mA}$, $V_8 = V_{\text{CC}}$ 2) $I_1 = I_4 = I_5 = 0 \text{ mA}$, $V_8 = V_{\text{CC}}$, $T_{\text{amb}} < 90 \text{ }^\circ\text{C}$. 3) For the receiver in all modes. 4) Standby mode					

Table 5 Typical values of electric parameters

Symbol	Parameter	Measurement mode	Typical value	Unit
$V_{diff(hys)}$	Differential hysteresis voltage	V_{CC} from 4,5 to 5,5 V	150	mV
$ SR $	CANH, CANL slew rate	V_{CC} from 4,5 to 5,5 V; $R_8 = 47\text{ k}\Omega$	7,0	V/ μ s
I_{SC7}	High level CAN short circuit current	V_{CC} from 4,5 to 5,5 V; $V_7 = -36\text{ V}$	-100	mA

FUNCTIONAL DESCRIPTION

The HT2551A provides differential transmit capability to the bus and differential receive capability to the CAN controller. Data transfer rate is up to 1 Mbit/s.

Output stage has good load capacity. It guarantees 2V peak-to-peak output voltage for 60 Ω load. HT2551A has thermal and short circuit protection, high immunity to EMI and is fully compatible with the "ISO 11898-24 V" standard.

The IC provides three operation modes: high-speed, reduced RFI mode, standby mode. The design of HT2551A permits possibility of adjustment of rise and fall slope of output stages (transistors).

Pin R_S is used to select one of three modes of operation: high-speed, reduced RFI or standby. High level applied to this pin switches the IC to standby mode, low level – to high-speed mode. The high-speed mode is selected by connecting pin R_S to ground. To reduce RFI, connect pin R_S by resistor R_{ext} to ground. The rise and fall slope of output stages (transistors) can be regulated with R_{ext} resistance.

To select high-speed dominant mode a low level voltage ($\sim 1\text{ V}$) is applied to TXD pin and R_S is connected to ground, CANH and CANL pins are connected by 60 Ω resistor. Guaranteed peak-to-peak output voltage (high and low level) will be 1,5 V for all operating supply voltage range

To select recessive mode a high level voltage ($\sim 4\text{ V}$) is applied to TXD pin and R_S is connected to ground. In recessive mode bus output voltage $V_{6,7}$ is about ($\sim 2.5\text{ V}$).

High level ($\sim 4\text{ V}$) applied to pin R_S switches IC to standby mode (with low power consumption); in this mode consumption current doesn't exceed 270 μ A. In this mode transmitter is turn off and consumption current of receiver and all circuit is significantly decreased.

Reference voltage value V_{REF} per 05 output is half of supply voltage.

Table 6 - Truth table of the transceiver

Supply voltage range, V_{CC} , V	TXD pin	CANH pin	CANL pin	Bus state	RXD output
4,5 ÷ 5,5	L	H	L	Dominant	L
4,5 ÷ 5,5	H	Floating	Floating	Recessive	H *
4,5 ÷ 5,5	X	Floating, if $V_{RS} > 0,75 V_{CC}$	Floating, if $V_{RS} > 0,75 V_{CC}$	Floating	H *
0 ÷ 5,5	Floating	Floating	Floating	Floating	X
Notes 1 H – high level voltage; L – low level voltage; X – don't care (H or L). 2 Floating state – half of sum of output levels on pins 06 and 07 ($V_{O(CANL)} + V_{O(CANH)} / 2$). * If another bus node is transmitting a dominant bit, then RXD shall be low					

Table 7 – Transceiver mode table

R_S pin state	Mode	R_S pin resulting voltage or current
$V_{RS} > 0,75 V_{CC}$	Standby	- $I_{RS} < 10 \mu A$
$10 \mu A < -I_{RS} < 200 \mu A$	Slope control (Reduced RFI)	$0,4 V_{CC} < V_{RS} < 0,6 V_{CC}$
$V_{RS} < 0,3 V_{CC}$	High – speed	- $I_{RS} < 500 \mu A$


Table 8 - Truth table of the receiver

Input differential voltage V_{DIFF}^*, B	RXD pin
$V_{DIFF} > 0,9 \text{ V}$	L
$0,5 \text{ V} < V_{DIFF} < 0,9 \text{ V}$	**
$V_{DIFF} < 0,5 \text{ V}$	H
Absent	H

* Input difference voltage V_{DIFF} , V is determined by formula

$$V_{DIFF} = V_7 - V_6 \quad , \quad (1)$$

 V_7 – CANH output voltage, V;
 V_6 – CANL output voltage, V
 ** Not determined (hysteresis zone)


Fig. 4 – t_{onTXD} , t_{onRXD} , t_{offTXD} , t_{offRXD} parameters measurement timing diagram




Fig. 5 – $V_{diff(hys)}$ parameter measurement timing diagram





Fig. 6 – t_{WAKE} parameter measurement timing diagram



$$t_{dRXDL} \leq 15 \mu s$$

Fig. 7 – t_{dRXDL} parameter measurement timing diagram






Fig. 8 – Application diagramm

SOP8 package information


TOP VIEW
正视图



SIDE VIEW
侧视图



SIDE VIEW
侧视图




机械尺寸/mm Dimensions			
字符 SYMBOL	最小值 MIN	典型值 NOMINAL	最大值 MAX
A	—	—	1.75
A1	0.10	0.15	0.25
A2	1.30	1.40	1.50
b	0.35	—	0.50
c	0.19	—	0.25
D	4.80	4.90	5.00
E	3.80	3.90	4.00
E1	5.80	6.00	6.20
e	1.27 BSC		
h	0.25	—	0.45
L	0.50	—	0.80
θ	0°	—	8°

MSOP8 package information


TOP VIEW

正视图




SIDE VIEW

侧视图



SIDE VIEW

侧视图




机械尺寸/mm Dimensions			
字符 SYMBOL	最小值 MIN	典型值 NOMINAL	最大值 MAX
A	—	—	1.10
A1	0.05	—	0.15
A2	0.75	0.85	0.95
A3	0.30	0.35	0.40
b	0.28	—	0.36
c	0.15	—	0.19
D	2.90	3.00	3.10
E	2.90	3.00	3.10
E1	4.70	4.90	5.10
e	0.65 BSC		
L1	0.95 REF		
L	0.40	—	0.70
θ	0°	—	8°

DFN8L(3X3X0.75-P0.65) package information


TOP VIEW

正视图




SIDE VIEW

侧视图




BOTTOM VIEW

背视图



SIDE VIEW





侧视图



机械尺寸/mm

字符 SYMBOL	最小值 MIN	典型值 NOMINAL	最大值 MAX
A	0.70	0.75	0.80
A1	-	0.02	0.05
A2	0.203 REF		
b	0.23	0.28	0.32
D	2.90	3.00	3.10
D2	2.20	2.30	2.40
e	0.65 BSC		
E	2.90	3.00	3.10
E2	1.40	1.50	1.60
L	0.25	0.30	0.35
h	0.30	0.35	0.40
K	0.40	0.45	0.50

DIP8 package information



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	3.60	3.80	4.00
A1	0.51	—	—
A2	3.20	3.30	3.40
A3	1.55	1.60	1.65
b	0.44	—	0.52
b1	0.43	0.46	0.49
B1	1.52REF		
c	0.25	—	0.29
c1	0.24	0.25	0.26
D	9.15	9.25	9.35
E1	6.25	6.35	6.45
e	2.54BSC		
eA	7.62REF		
eB	7.62	—	9.30
eC	0	—	0.84
L	3.00	—	—