


# POLYMER PTC RESETTABLE FUSE



Part Number: TLC-USMD200/8

## 1、Physical Dimensions(size of 1210)

Part Number	A		B		C		D	Unit:mm Marking
	Min	Max	Min	Max	Min	Max		
TLC-USMD200/8	3.00	3.43	2.35	2.80	0.60	1.00	0.30	T20



## 2、Electrical Characteristics

Part Number	I <sub>H</sub> (A)	I <sub>T</sub> (A)	V <sub>max</sub> (V)	I <sub>max</sub> (A)	T <sub>trip</sub> (Max time to trip)		P <sub>d typ</sub> (W)	R <sub>min</sub> (Ω)	R <sub>1max</sub> (Ω)
					Current(A)	Time(S)			
TLC-USMD200/8	2.00	4.00	8	40	8.00	1.00	0.70	0.02	0.09

I<sub>H</sub>: Holding Current: maximum current at which the device will not trip in 25°C still air.

I<sub>T</sub>: Tripping Current minimum current at which the device will trip in 25°C still air.

V<sub>max</sub>: Maximum voltage device can withstand without damage at rated current.

I<sub>max</sub>: Maximum fault current device can withstand without damage at rated voltage.

T<sub>trip</sub>: Maximum time to trip(s) at assigned current.

P<sub>d typ</sub>: Rated working power.

R<sub>min</sub>: Minimum resistance of device prior to trip at 25°C.



R<sub>1max</sub>: Maximum resistance of device is measured one hours post reflow at 25°C.

Notes: All electrical function test is conducted after PCB mounted.

## 3、Thermal Derating

TLC-USMD200/8	Maximum ambient operating temperature								
	-40°C	-20°C	0°C	25°C	40°C	50°C	60°C	70°C	85°C
Hold Current(A)	3.20	2.80	2.40	2.00	1.80	1.60	1.40	1.20	1.00
Trip Current(A)	6.40	5.60	4.80	4.00	3.60	3.20	2.80	2.40	2.00

## 4、Solder Reflow Recommendations



Notes: If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.

## 5、Package Information

Packing quantity: 3500PCS/Reel

Note: Reel packaging per EIA-481-1 standard

## 6、Agency Recognition: TUV



Caution: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame. Specifications are subject to change without notice.

TEL: 86-0769-3892 0554

FAX: 86-0769-8793 2077

E-mail: [Tina@tlcet.com.cn](mailto:Tina@tlcet.com.cn)

Address: No.18, 5th GaoLi Road, TangXia Town, DongGuan, GuangDong, P.R China 523710