

产品规格书

Product Specification

CUSTOMER

客户:

CUSTOMER PN

客户 PN:

HANG CRYSTAL P/N

杭晶物料编码:

1532H-125.000KWVDTSL

MODEL

产品型号:

**Oscillator SMD 3.2x2.5, HCMOS,
1.8~3.3V**

NOMINAL FREQUENCY

频率:

125.000MHz

ISSUE DATE

日期: **2022 / 05 / 05**

CUSTOMER'S APPROVAL

客户确认

(PLEASE RETURN A COPY WITH APPROVAL)
(请将确认的复印件返回我司)

APPROVED

QA

MB.

James J

SUZHOU HANGJING ELEC&TECH CO., LTD

苏州杭晶电子科技有限公司

No. 207, Blk. B, Chenlei Science &
Technology Park, No. 1, First Qunxing Road,
Suzhou Industrial Park, Jiangsu, China
TEL: 86 (0)512 65916689
FAX: 86 (0)512 65918005

Revision	Description / ECN	Prepared	Approved	Date
1	Initial release	MB.	James Jiang	2022-05-05
2	Not issued			
3	Not issued			
4	Not issued			

1. MAXIMUM RATINGS, OPERATING AND STORAGE CONDITIONS

PARAMETER		SYMB.	MIN	TYP	MAX	Unit	Conditions / Remarks
1	Maximum voltage range	V _{MAX}	-0.5		+4.5	V _{DC}	Between V _{CC} and GND
2	Nominal supply voltage	V _{CC}	1.62	1.80	3.63	V _{DC}	--
3	Output load capacitance	C _L		15		pF	HCMOS
4	Operating temperature range	T _{OP}	-40	+25	+85	°C	--
5	Storage temperature range	T _{ST}	-55		125	°C	--
6	Enable / Disable function (→ Output TRISTATE)	E/D	Pin 1 = HIGH → Output pin 3 is enabled				
		Note 1	Pin 1 = LOW → Output pin 3 is disabled (high impedance)				

Note 1: Output pin 3 is enabled when E/D input pin 1 is left open (floating).

2. ELECTRICAL PARAMETER LIMITS

PARAMETER		SYMB.	MIN	TYP	MAX	Unit	Conditions / Remarks
1	Nominal frequency	F _N	125.000			MHz	--
2	Frequency stability (overall)	Δf/F _N	-25		+25	ppm	Note 1
3	Aging first year	Δf/F _{A1}	-3.0		+3.0	ppm	at +25°C
4	Output voltage level HIGH	V _{OH}	90%V _{CC}			V _{DC}	HCMOS level 90%V _{CC} MIN
5	Output voltage level LOW	V _{OL}			10%V _{CC}	V _{DC}	HCMOS level 10%V _{CC} MAX
6	Output amplitude rise time	t _R			5.0	ns	At 20~80%V _{CC} / 15pF / +25°C
7	Output amplitude fall time	t _F			5.0	ns	At 80~20%V _{CC} / 15pF / +25°C
8	Output amplitude symmetry	DC	45		55	%	At 50%V _{CC} / 15pF / +25°C
9	Current consumption	I _{CC}			30	mA	With output load C _L ±10%
10	Standby current	I _{STB}			10	μA	Output disabled (pin 1 = LOW)
11	Startup time	t _{STR}			10	ms	V _{P-P} reach >90% of amplitude


Note 1: Including tolerance at +25°C, deviations over operating temperature range, input voltage changes, output load changes, shock and vibration.

3. PRODUCT MARKING

1	FF.fff	Nominal frequency in MHz (three digits after decimal point)								HCI YM •FF.fff					
2	HCI	Company logo													
3	Y	Year code of manufacturing (see table below)													
Year		2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032		
Code		V	W	X	Y	Z	A	B	C	D	E	F	G		
4	M	Month code of manufacturing (see table below)													
Month		Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
Code		A	B	C	D	E	F	G	H	J	K	L	M		

4. OUTLINE DRAWING

Package descriptions	Package model	Remarks
1 Ceramic seam seal SMD package 3.2x2.5mm with 4 pads for Oscillator	3225p4 h12	With E/D function on pin 1


5. RELIABILITY TEST INFORMATION


Test item	Test method	Criteria
1 Temperature Cycle (GB/T2423.22-2002, Method Nb)	10 cycles from -55°C to $+125^{\circ}\text{C}$. Tested after 24 ± 2 h at room temperature.	$\pm 5.0\text{ppm}$
2 Low Temperature Storage (GB/T 2423.1-2001, Method Aa)	72h at $-55^{\circ}\text{C}\pm 3^{\circ}\text{C}$ constant temperature. Tested after 24 ± 2 h at room temperature.	$\pm 5.0\text{ppm}$
3 High Temperature Storage(GB/T 2423.2-2001, Method Ba)	72h at $+125^{\circ}\text{C}\pm 3^{\circ}\text{C}$ constant temperature. Tested after 24 ± 2 h at room temperature.	$\pm 5.0\text{ppm}$
4 Humidity (GB/T 2423.3-2006, Method Cab)	96h at $+40^{\circ}\text{C} \pm 3^{\circ}\text{C}$, with $90\pm 3\%$ RH. Tested after 24 ± 2 h at room temperature.	$\pm 5.0\text{ppm}$
5 Vibration (GB/T 2423.10-1995, Method Fc)	Apply 0.75mm vibration at frequency $10\sim 500$ Hz, for 2h. 10 cycles in each direction of 3 axis, test after 1h.	$\pm 5.0\text{ppm}$
6 Shock (GB/T 2423.5-1995,Method Ea)	Peak 1000m/s^2 , with 6ms half sine wave, 3.7m/s, in 3 perpendicular axis, 3 cycles /direction, test after 1h.	$\pm 5.0\text{ppm}$
7 Drop (GB/T 2423.8-1995, M. Ed)	Free drop onto wooden plate from 1.0 m height for 3times.	$\pm 5.0\text{ppm}$
8 Solderability (GB/T2423.28-2005, Method Tc)	Dip into $245 \pm 5^{\circ}\text{C}$ solder bath for 2 ± 0.5 seconds. Inspection under 8-12X magnifier.	>95% cover.
9 Terminal Strength (JIS-C-6429 Method 1 & 2)	Mount on a glass-epoxy board (100x50x1.6mm), then bend to 2mm displacement (velocity 1mm/sec) and keep for 5 seconds. or pulling force 0.5 kg for at least 60seconds	No damage
10 Resistance to Solder Heat (GB/T 2423.28-2005,Test Tb Meth. 1B)	Reflow at Preheat to $150^{\circ}\text{C}\pm 5^{\circ}\text{C}$ for 60 to 120sec, and peak $265^{\circ}\text{C}\pm 5^{\circ}\text{C}$ for 10s ± 3 sec, Tested after 24 ± 2 h at room temp.	$\pm 5.0\text{ppm}$

6. ENVIRONMENTAL COMPLIANCE INFORMATION

		Compliance information
1	RoHS	This product is fully RoHS compliant, 6/6 compliant per EU legislation.
2	RoHS 2	This product is RoHS compliant per DIRECTIVE 2015/863 (also called RoHS10). In regards of CE marking directive for finished products, we can provide RoHS test reports and MDS to show compliance, but since our product is not a final application we have no CE mark.
3	Lead-Free	This product is considered Lead-Free, Lead (Pb) contamination is controlled to be below 200ppm.
4	Halogen-Free	This product is compliant to IEC 61249-2-21:2003 (Br<800ppm / Cl<800ppm).
5	REACH (SVHC)	This product does not contain substances (SVHC) listed by REACH, we continuously monitor updates of the list of SVHC's
6	PFOS / PFOA Free	This product is free of any PFOS / PFOA.
7	Electrostatic Discharge (ESD) sensitivity	This product is ESD sensitive and requires precautions for handling and storage. Follow JEITA EIAJ ED-4701 or JSD22 or ANSI-ESD-S20-20 or IEC 61000-4-2.
8	Moisture Sensitivity	This product is hermetically sealed and does NOT fall under the classification of moisture sensitivity per J-STD-020C (Standard is for non-hermetically sealed components). If required we suggest to use LEVEL 1

7. RECOMMENDED SOLDERING INFORMATION


RECOMMENDED REFLOW SOLDER PROFILE – PEAK TEMPERATURE UP TO +260 °C



8. PACKAGING

Carrier

Parameter	STANDARD PACKAGING	ALTERNATE PACKAGING
1 A0	2.8±0.1	
2 B0	3.6±0.1	
3 K0	1.25±0.1	
4 B1	4.2±0.1	
5 P0	4.0±0.1	
6 P1	4.0±0.1	
7 T	0.3±0.05	
8 W	8.0±0.2	




Note 1: All dimensions in [mm].

Note 2: All dimensions not specified or not being shown follow EIA-481 standard.

Reel

QTY per reel: 3,000pcs MAX

Parameter	STANDARD PACKAGING	ALTERNATE PACKAGING
9 A	178 ⁺⁰ _{-1.5}	180 ⁺⁰ _{-1.5}
10 B	2.0±0.5	2.0±0.5
11 ØC	13.2±0.2	13.2±0.2
12 ØD	21±0.8	21±0.8
13 N	62±2	62±2
14 W1	8.0 ^{+2.0} ₋₀	8.0 ^{+2.0} ₋₀
15 W2	11.4 ^{+2.0} ₋₀	11.4 ^{+2.0} ₋₀



Note 1: All dimensions in [mm]. Dimension W1 is measured near the Hub (N).

Note 2: All dimensions not specified or not being shown follow EIA-481 standard.

Unreeling information

oscillator product's orientation

16	This product is a polarized component which requires a certain orientation; Pin 1 is identified on top side marking with a DOT. In the carrier tape is the component oriented with pin 1 towards the sprocket holes. (per EIA-481)
----	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

