

Technical drawing of a cable assembly. The drawing shows a cable with a length dimension of $300 \pm 5\text{mm}$. The left end is labeled "A端" (A end) and the right end is labeled "B端" (B end). The cable has a central section with a width dimension of 16 . The cable is labeled "15 插端子面" (15 Plug terminal surface) and "16 端子面" (16 Terminal surface). The cable is labeled "②" and "③". The cable is labeled "镀锡5mm" (Tin-plated 5mm).

A端	线材	B端	备注
1	白色	镀锡5mm	
2	白色	镀锡5mm	
3	白色	镀锡5mm	
4	白色	镀锡5mm	
5	白色	镀锡5mm	
6	白色	镀锡5mm	
7	白色	镀锡5mm	
8	白色	镀锡5mm	
9	白色	镀锡5mm	
10	白色	镀锡5mm	
11	白色	镀锡5mm	
12	白色	镀锡5mm	
13	白色	镀锡5mm	
14	白色	镀锡5mm	
15	白色	镀锡5mm	
16	白色	镀锡5mm	

- 1) 100%外形尺寸:所有尺寸与图示一致。
- 2) 外观:a)电线圆实平滑,颜色均匀,外被表面无破损、划伤、脏污、变形等缺陷;
- 3) 结构:线材和各插头五金以及各接触件应牢固无松动,标志清晰,正确无误;
- 4) 导通性能:100%测试,DC00V,绝缘 $\geq 20M\Omega$,导通电阻 $<1\Omega$,无断路或触不良现象,测试时应加摇摆测试。

序号号	名称	规格	数量	备注
1	元器件Components	X3025HM-2x08-N2（胶壳）	1PCS	
2	元器件Components	X3025T-PSN（端子）	16PCS	
3	线缆Cable	UL1007/22AWG. 白色	16PCS	裁线长度：300mm

				XKB星城 Connection	Item details		RVE.	
							A0	
					UNIT			
RVE.	DESCRIPTION		DATE		SCALE	Free		
DESIGNED		DATE			PAGE	1 OF 1		
CHECKED		DATE		DRAWING NO.				
APPROVED		DATE		X3025T-2x08-PSN-A22W16-L300-X3025T-T5				