

1. FIGURE AND DIMENSIONS (图示及尺寸)

The diagram shows a front view of a 19-inch rack-mounted device. The overall width is labeled as 150 ± 5MM. The device has two main sections, each with a 19-pin connector on the left (labeled 'A端' and 'B端' respectively) and a 20-pin connector on the right (labeled '插端子面'). The connectors are labeled with numbers 1 through 20. The device is divided into three main horizontal sections: a top section (labeled ①), a middle section (labeled ②), and a bottom section (labeled ③). The top section has a 19-pin connector on the left and a 20-pin connector on the right. The middle section has a 19-pin connector on the left and a 20-pin connector on the right. The bottom section has a 19-pin connector on the left and a 20-pin connector on the right. The device is shown in a perspective view, with the front face labeled '插端子面'.

A端	线材	B端	备注
1	黑色	20	
2	黑色	19	
3	黑色	18	
4	黑色	17	
5	黑色	16	
6	黑色	15	
7	黑色	14	
8	黑色	13	
.....			
16	黑色	5	
17	黑色	4	
18	黑色	3	
19	黑色	2	
20	黑色	1	

- 1) 100%外形尺寸:所有尺寸与图示一致。
- 2) 外观:a)电线圆实平滑,颜色均匀,外被表面无破损、划伤、脏污、变形等缺陷;
- 3) 结构:线材和各插头五金以及各接触件应牢固无松动,标志清晰,正确无误;
- 4) 导通性能:100%测试,DC00V,绝缘 $\geq 20M\Omega$,导通电阻 $<1\Omega$,无断路或触不良现象,测试时应加摇摆测试。

序号号	名称	规格	数量	备注
1	元器件Components	X3025HM-2x10-N2（胶壳）	2PCS	
2	元器件Components	X3025T-PSN（端子）	40PCS	
3	线缆Cable	UL1007/22AWG. 黑色	20PCS	裁线长度：150mm

				XKLB·星城 Connection	Item details		RVE.
							A0
					UNIT		 
RVE.	DESCRIPTION		DATE		SCALE	Free	
DESIGNED		DATE			PAGE	1 OF 1	
CHECKED		DATE		DRAWING NO.			
APPROVED		DATE		X3025T-2x10-PSN-A22B20-L150-X3025T-F			