

CMP/CMB/CMI/CMF65R170DT

650V, 0.15Ω typ., 25A N-Channel Super Junction Power MOSFET

General Description

The 65R170DT is power MOSFET using Cmos's advanced super junction technology. The resulting devices provide all benefits of a fast switching super junction MOSFET while offering an extremely fast and robust body diode. This combination of extremely low switching, commutation and conduction losses together with highest robustness make especially resonant switching applications more reliable, more efficient and lighter.

Features

- Ultra-fast body diode
- Low On-Resistance
- 100% avalanche tested
- RoHS Compliant
- Deep Trench


Product Summary

BVDSS	R _{DS(on)} max.	ID
650V	0.17Ω	25A

Applications

- Charger
- Power Supply

TO-220/263/262/220F Pin Configuration



Absolute Maximum Ratings

Symbol	Parameter	220/263/262	220F	Units
V _{DS}	Drain-Source Voltage	650		V
V _{GS}	Gate-Source Voltage	±30		V
I _D @T _C =25°C	Continuous Drain Current	25	25*	A
I _D @T _C =100°C	Continuous Drain Current	16	16*	A
I _{DM}	Pulsed Drain Current (Note 1)	100	100*	A
EAS	Single Pulse Avalanche Energy (Note 2)	540		mJ
P _D @T _C =25°C	Total Power Dissipation	250	45	W
T _{STG}	Storage Temperature Range	-55 to 150		°C
T _J	Operating Junction Temperature Range	-55 to 150		°C

* Drain current limited by maximum junction temperature.

Thermal Data

Symbol	Parameter	220/263/262	220F	Unit
R _{θJA}	Thermal Resistance Junction-ambient Max.	62.5	62.5	°C/W
R _{θJC}	Thermal Resistance Junction-case Max.	0.50	2.78	°C/W

CMP/CMB/CMI/CMF65R170DT

650V, 0.15Ω typ., 25A N-Channel Super Junction Power MOSFET

Electrical Characteristics ($T_J=25^{\circ}\text{C}$, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V$, $I_D=250\mu A$	650	---	---	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=10V$, $I_D=10A$	---	150	170	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	$V_{GS}=V_{DS}$, $I_D=250\mu A$	3.5	---	5.5	V
I_{DSS}	Drain-Source Leakage Current	$V_{DS}=650V$, $V_{GS}=0V$	---	---	10	uA
I_{GSS}	Gate-Source Leakage Current	$V_{GS}=\pm 30V$, $V_{DS}=0V$	---	---	± 100	nA
g_{fs}	Forward Transconductance	$V_{DS}=15V$, $I_D=10A$	---	9	---	S
R_g	Gate Resistance	$V_{DS}=0V$, $V_{GS}=0V$, $f=1\text{MHz}$	---	4.0	---	Ω
Q_g	Total Gate Charge	$V_{DS}=300V$, $I_D=25A$ $V_{GS}=10V$	---	50	---	nC
Q_{gs}	Gate-Source Charge		---	15	---	
Q_{gd}	Gate-Drain Charge		---	26	---	
$T_{d(on)}$	Turn-On Delay Time	$V_{DD}=300V$, $I_D=12.5A$ $R_G=10\Omega$, $V_{GS}=10V$	---	35	---	ns
T_r	Rise Time		---	60	---	
$T_{d(off)}$	Turn-Off Delay Time		---	80	---	
T_f	Fall Time		---	30	---	
C_{iss}	Input Capacitance	$V_{DS}=100V$, $V_{GS}=0V$, $f=1\text{MHz}$	---	1400	---	pF
C_{oss}	Output Capacitance		---	45	---	
C_{rss}	Reverse Transfer Capacitance		---	3	---	

Diode Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_S	Continuous Source Current	$V_G=V_D=0V$, Force Current	---	---	25	A
I_{SM}	Pulsed Source Current		---	---	100	A
V_{SD}	Diode Forward Voltage	$V_{GS}=0V$, $I_S=15A$, $T_J=25^{\circ}\text{C}$	---	0.93	1.5	V

Note :







1. Repetitive rating: Pulse width limited by maximum junction temperature.
2. The EAS data shows Max. rating . The test condition is $V_{DD}=80V$, $V_{GS}=10V$, $L=30\text{mH}$, $I_{AS}=6A$.

This product has been designed and qualified for the consumer market.

Cmos assumes no liability for customers' product design or applications.

Cmos reserves the right to improve product design , functions and reliability without notice. Please refer to the latest version of specification.

Typical Characteristics




CMP/CMB/CMI/CMF65R170DT

650V, 0.15Ω typ., 25A N-Channel Super Junction Power MOSFET

Package Dimension

TO-220

Unit :mm



DIM	MILLIMETERS
A	10.0±0.3
A1	8.64±0.2
A2	1.15±0.1
A3	5.0±0.2
B	15.8±0.4
B1	13.2±0.3
C	4.56±0.1
C1	1.3±0.2
D	0.8±0.2
E	3.6±0.2
F	2.95±0.3
G	6.5±0.3
H	0.5±0.1
K	3.1±0.2
L	13.2±0.4
M	1.25±0.1
N	2.54±0.1
P	2.4±0.3
Q	9.0±0.3
T	W:0.35
DIA	⊙1.5(deep 0.2)


CMP/CMB/CMI/CMF65R170DT

650V, 0.15Ω typ., 25A N-Channel Super Junction Power MOSFET

Package Dimension

TO-263

Unit :mm



DIM	MILLIMETERS
A	9.8 ± 0.2
a	7.4 ± 0.4
B	4.5 ± 0.2
b1	1.3 ± 0.05
b2	2.4 ± 0.2
H	15.5 ± 0.3
h	1.54 ± 0.2
h1	10.5 ± 0.2
h2	9.2 ± 0.1
h3	1.54 ± 0.2
h4	2.7 ± 0.2
L	2.4 ± 0.2
1	1.3 ± 0.1
11	0.8 ± 0.1
12	1.3 ± 0.1
13	0.5 ± 0.1
N	2.54 ± 0.1
R	$0.5R \pm 0.05$


CMP/CMB/CMI/CMF65R170DT

650V, 0.15Ω typ., 25A N-Channel Super Junction Power MOSFET

Package Dimension

TO-262

Unit :mm



DIM	MILLIMETERS
A	9.98 ± 0.2
a	7.4 ± 0.4
B	4.5 ± 0.2
b1	1.3 ± 0.05
b2	2.4 ± 0.2
H	23.9 ± 0.3
h	3.1 ± 0.2
h1	9.16 ± 0.2
h2	13.2 ± 0.2
L	0.5 ± 0.1
l1	1.3 ± 0.1
l2	0.8 ± 0.1
N	2.45 ± 0.1


CMP/CMB/CMI/CMF65R170DT

650V, 0.15Ω typ., 25A N-Channel Super Junction Power MOSFET

Package Dimension

TO-220F

Unit :mm



DIM	MILLIMETERS
A	10.16 ± 0.3
A1	7.00 ± 0.1
A2	3.3 ± 0.2
A3	9.5 ± 0.2
B1	15.87 ± 0.3
B2	4.7 ± 0.2
B3	6.68 ± 0.4
C	3.3 ± 0.2
C1	12.57 ± 0.3
C2	10.02 ± 0.5
D	2.54 ± 0.05
D1	1.28 ± 0.2
D2	0.8 ± 0.1
K	3.1 ± 0.3
E1	2.54 ± 0.1
E3	0.5 ± 0.1
E4	2.76 ± 0.2
DIA	$\odot 1.5$ (deep 0.2)