

ID	$R_{DS(ON)}$ (Typ)	VDSS
23A	120mΩ	550V

Applications:


- Switch Mode Power Supply(SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)
- AC-DC Switching Power Supply

Features:

- Low gate charge
- Low $R_{DS(on)}$ per chip area(Low FOM)
- Very low switching and conduction loss
- Extremely high commutation ruggedness
- Ultra fast body diode

Ordering Information

Part Number	Package	Marking	Packing	Qty.
RSF55R140F	T0-220F	RSF55R140F	Tube	50 PCS



Absolute Maximum Ratings $T_c = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	RSF55R140F	Units
VDSS	Drain-to-Source Voltage	500	V
ID	Continuous Drain Current $T_C=25^\circ\text{C}$	23	A
ID	Continuous Drain Current $T_C=100^\circ\text{C}$	14.8	
IDM	Pulsed Drain Current $T_P=100\mu\text{s}$	69	
PD	Power Dissipation	123	W
VGS	Gate- to- Source Voltage	± 30	V
EAS	Single Pulse Avalanche Energy $L=10\text{mH}, V_{DS}=100\text{V}, T_J=25^\circ\text{C}$	451	mJ
dv/dt	MOSFET dv/dt ruggedness $V_{DS} = 0\ldots 400\text{V}$	50	V/ns
dv/dt	Reverse diode dv/dt $V_{DS} = 0\ldots 400\text{V}$ $T_J = 25^\circ\text{C}, I_{SD} \leq I_D$	15	
TL TPKG	Maximum Temperature for Soldering	300	$^\circ\text{C}$
	Leads at 0.063in(1.6mm)from Case for 10 seconds Package Body for 10 seconds	260	
TJ and TSTG	Operating Junction and Storage Temperature Range	-55 to 150	

* Drain Current Limited by Maximum Junction Temperature

Caution: Stresses greater than those listed in the "Absolute Maximum Ratings" Table may cause permanent damage to the device.

Thermal Resistance

Symbol	Parameter	RSF55R140F	Units	Test Conditions
R θ JC	Junction-to-Case	1.01	°C / W	Drain lead soldered to water cooled heatsink, PD adjusted for a peak junction temperature of + 150 °C
R θ JA	Junction-to- Ambient	41.18		1 cubic foot chamber, free air.

OFF Characteristics TJ= 25°C unless otherwise specified

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
BVDSS	Drain- to- source Breakdown Voltage	550	--	--	V	VGS=0V ID=250 μ A
IDSS	Drain- to- Source Leakage Current	--	--	5	μ A	VDS=550V VGS=0V
IGSS	Gate- to- Source Forward Leakage	--	--	100	nA	VGS=30V VDS=0V
	Gate- to- Source Reverse Leakage	--	--	-100		VGS=-30V VDS=0V

ON Characteristics TJ=25°C unless otherwise specified

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
RDS(on)	Static Drain- to- Source On-Resistance	--	120	140	m Ω	VGS=10V ID=6.9A
VGS(TH)	Gate Threshold Voltage	3	4	5	V	VGS=VDS ID=250 μ A

Resistive Switching Characteristics Essentially independent of operating temperature

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
td(ON)	Turn- on Delay Time	--	22	--	nS	VDS=400V ID=13A RG=15 Ω VGS=10V
trise	Rise Time	--	27	--		
td(OFF)	Turn- OFF Delay Time	--	48	--		
tfall	Fall Time	--	16	--		

Dynamic Characteristics Essentially independent of operating temperature

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
Ciss	Input Capacitance	--	1432	--	pF	VGS=0V VDS=100V f=1.0MHz
Coss	Output Capacitance	--	71	--		
Crss	Reverse Transfer Capacitance	--	0.32	--		
RG	Gate Resistance	--	6.8	--	Ω	VDS=0V VGS=0V f=1.0MHz
Qg	Total Gate Charge	--	34	--	nC	VDS=400V ID=13A VGS=10V
Qgs	Gate- to- Source Charge	--	8.3	--		
Qgd	Gate-to-Drain(" Miller") Charge	--	14.5	--		

Source- Drain Diode Characteristics

Symbol	Parameter	Min.	Typ.	Max.	Units	Test Conditions
IS	Continuous Source Current	--	--	23	A	Integral pn- diode in MOSFET
ISM	Maximum Pulsed Current	--	--	80	A	
VSD	Diode Forward Voltage	--	--	1.0	V	IS=25A VGS=0V
trr	Reverse Recovery Time	--	129	--	nS	VR=300V IS=13A di/dt=100A/μs
Qrr	Reverse Recovery Charge	--	0.84	--	μC	
Irr	Peak Reverse Recovery Current	--	12	--	A	

Notes:

* 1. Repetitive rating, pulse width limited by maximum junction temperature.

Typical Feature Curve

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-state Resistance




Fig 4. On-state Resistance with Temperature




Figure 5. Capacitance




Figure 6. Gate Charge




Figure 7. Forward characteristics of reverse diode




Figure 8. Power Dissipation Derating Curve




Figure 9. Breakdown Voltage with Temperature




Figure 10. Normalized Threshold Voltage vs. Temperature




Figure 11. Coss Capacitor Stored Energy




Figure 12. Maximum Drain Current




Figure 13. Safe Operating Area





Figure 14. Maximum Transient Thermal Characteristics



Test Circuits and Waveforms

Figure A: Gate Charge Test Circuit and Waveform




Figure B: Resistive Switching Test Circuit and Waveform







Figure C: Unclamped Inductive Switching Test Circuit and Waveform



Package outline drawing (TO-220F Unit: mm)


Disclaimers:

Reasunos Semiconductor Technology Co.Ltd (Reasunos) reserves the right to make changes without notice in order to improve reliability,function or design and to discontinue any product or service without notice .Customers should obtain the latest relevant information before orders and should verify that such information in current and complete.All products are sold subject to Reasunos's terms and conditions supplied at the time of orderacknowledgement.

Reasunos Semiconductor Technology Co.Ltd warrants performance of its hardware products to the specifications at the time of sale.Testing,reliability and quality control are used to the extene Reasunos deems necessary to support this warrantee. Except where agreed upon by contr- actual agreement,testing of all parameters of each product is not necessarily performed.

Reasunos Semiconductor Technology Co.Ltd does not assume any liability arising from the use of any product or circuit designs described herein.Customers are responsible for their products and applications using Reasunos's components.To minimize risk,customers must provide adequate design and operating safeguards.

Reasunos Semiconductor Technology Co.Ltd does not warrant or convey any license eith- er expressed or implied under its patent rights,nor the rights of others.Reproduction of inform- ation in Reasunos's data sheets or data books is permissible only if reproduction is without modification oralteration.Reproduction of this information with any alteration is an unfair and deceptive business practice. Reasunos Semiconductor Technology Co.Ltd is not responsi- ble or liable for such altered documentation.

Resale of Reasunos's products with statements different from or beyond the parameters stated by Reasunos Semiconductor Technology Co.Ltd for that product or service voids all exp- ress or implied warranties for the associated Reasunos's product or service and is unfair and deceptive business practice. Reasunos Semiconductor Technology Co.Ltd is not responsi- ble or liable for such statements.

Life Support Policy:

Reasunos Semiconductor Technology Co.Ltd's Products are not authorized for use as cri- tical components in life support devices or systems without the expressed written approval of Reasunos Semiconductor Technology Co.Ltd.

As used herein:

1. Life support devices or systems are devices or systems which: a.are intended for surgical implant into the human body, b.support or sustain life,c.whose failuer to when properly used in accordance with instructions for used provided in the laeling,can be reasonably expected to result in significant injury to the user.

2.A critical component is any component of a life support device or system whose failure to system whose failure to perform can be reasonably expected to cause the failure of the life support device or system,or to affect its safety or effectiveness.