

Part Number: 1202530366

**Product Description:** Contrinex Inductive Sensor,

M8 Housing, 4mm Operating Distance, Non-

embeddable, NPN, NO, 2m 3-wire PVC Cable, 35mm

**Housing Length** 

Series Number: 120253

**Status:** Not Recommended For New Design **Product Category:** Inductive and Photoelectric

Sensors

**Engineering Number: DW-AD-631-M8** 



### **Documents & Resources**

### **Specifications**

1202530366-000.pdf

## **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<del>0</del> per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

#### **Compliance Statements**

- EU RoHS
- REACH SVHC
- Low-Halogen

### **Industry Documents**

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

• chemSHERPA (xml)

### **Substances of Interest**

PFAS

**EU RoHS Certificate of Compliance** 

Additional Product Compliance Information

**UKCA - Declaration of Conformity** 

**CE - Declaration of Conformity** 

### **Part Details**

#### **General**

Status	Not Recommended For New Design
Category	Inductive Sensors
Series	120253
Description	Contrinex Inductive Sensor, M8 Housing, 4mm Operating Distance, Non-embeddable, NPN, NO, 2m 3- wire PVC Cable, 35mm Housing Length
IP Rating	IP67
Product Name	Contrinex
Туре	Inductive
UPC	191130066018

### **Electrical**

Output	NO
Polarity	NPN
Switching Frequency	≤ 3500 Hz

# **Physical**

Connection	Cable (PVC 2m, 3-wire)
Length	35mm
Material - Housing	Stainless Steel
Material - Sensing Face	PBTP
Mounting Style	Non-embeddable
Operating Distance	4mm
Output	NO

Sensor Housing Size	M8
Temperature Range - Operating	-25° to +70°C

This document was generated on Nov 07, 2025