




MBR2040CD~MBR20200CD

20.0 AMP Schottky Barrier Rectifier

1. Features


- Metal silicon junction, majority carrier conduction.
- Low power loss, high efficiency.
- High current capability.
- High reliability.
- Guardring for overvoltage protection.
- RoHS Compliant.

TO-252



2. Mechanical Data

- Case:Molded Plastic,TO252 .
- Epoxy:UL 94V-0 rate flame retardant.
- Terminals:Plated Leads Solderable per MIL-STD-750,Method-2026.
- Marking:marked on body.
- Mounting Position : Any.



3. Maximum Ratings and Electrical Characteristics

Electrical Characteristics Rating at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	MBR 2040CD	MBR 2045CD	MBR 2060CD	MBR 20100CD	MBR 20150CD	MBR 20200CD	UNIT
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	40	45	60	100	150	200	V
Maximum RMS Voltage	V _{RMS}	28	31.5	42	70	105	140	V
Maximum DC Blocking Voltage	V _{DC}	40	45	60	100	150	200	V
Average Rectified Output Current @T _c =100℃	I _{F(AV)}	20						A
Peak Forward Surge Current 8.3ms Single half sine-wave superimposed @T _j =25℃ on rated load (JEDEC Method)	I _{FSM}	150						A
I ² t Rating for Fusing (t < 8.3ms)	I ² t	93.38						A ² s
Maximum Instantaneous Forward Voltage @I _F =10A	V _{FM}	0.70		0.80	0.85	0.92		V
Maximum DC reverse current @T _j =25℃ at rated DC blocking voltage @T _j =125℃	I _R	0.05						mA
		20						
Typical Thermal Resistance	R _{θJC}	2						℃/W
Operating Temperature Range	T _j	-55 to+150				-55 to+175		℃
Storage Temperature Range	T _{STG}	-55 to+150				-55 to+175		℃



4. Rating And Characteristic Curves

Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Forward Surge Current Capability





Fig. 4 Typical Reverse Characteristics






MBR2040CD~MBR20200CD


20.0 AMP Schottky Barrier Rectifier

5. Soldering Parameters





Reflow Condition		Lead-free
Pre Heat	Temp. min(T_s (min))	150℃
	Temp. max(T_s (min))	200℃
	Time(min to max)(t_s)	60~120s
Aver. ramp up rate(Liquidus Temp.)(T_L)to peak		3℃/s max
T_s (max) to T_L -Ramp-up Rate		3℃/s max
Reflow	Temp.(T_L)(Liquidus)	217℃
	Temp.(t_L)(Liquidus)	60~150s
Peak Temp.(T_p)		260 ^{+0/-5} ℃
Time within actual peak Temp.(t_p)		30s max
Ramp-down Rate		6℃/s max
Time 25℃ to peak Tempe.(T_p)		8 minutes max
Do not exceed		260℃

6. Dimensions



Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
A	0.270	0.285	6.85	7.25
B	0.232	0.248	5.90	6.30
C	0.202	0.218	5.13	5.53
D	0.252	0.268	6.40	6.80
E	0.114	0.130	2.90	3.30
F	0.086	0.094	2.19	2.39
G	0.018	0.033	0.45	0.85
H	0.087	0.094	2.20	2.40
I	0.016	0.024	0.41	0.61
J			0°	8°
K	0.057	0.073	1.45	1.85
L	0.016	0.024	0.41	0.61
M	0.000	0.005	0.00	0.12
N	0.024	0.039	0.60	1.00

7. Part Marking System



8. Package Information

Package	Tape Width (mm)	Reel Size		Quantity(pcs)
		mm	inch	
TO252	16	330	13	2500



Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without from XINNUO.
- XINNUO reserves the right to make changes to this document and its products and specifications.
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown her are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.