



| 未注公差/General tolerances(mm) |       |       |       |       |       |       |       |       |       | 2     | 3     | 4     | 5      | 6     |
|-----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|-------|
| 0                           | >3    | >6    | >10   | >18   | >30   | >50   | >80   | >120  | >180  | >250  | >315  | >400  |        |       |
| ~                           | 3     | 6     | 10    | 18    | 30    | 50    | 80    | 120   | 180   | 250   | 315   | 400   | 500    | >500  |
| ±0.12                       | ±0.18 | ±0.22 | ±0.26 | ±0.31 | ±0.37 | ±0.57 | ±0.80 | ±0.93 | ±1.05 | ±1.15 | ±1.60 | ±2.20 | ±2.50  | ±2.50 |
|                             |       |       |       |       |       |       |       |       |       |       |       |       | 0.1/10 | ±2°   |

| REV | ECN | DESCRIPTION | DRAFT | DATE |
|-----|-----|-------------|-------|------|
|     |     |             |       |      |



DB16H — 14.5 — XXP — C — S/P

(Series No.) (Pitch) (Poles) Slotted/Phillips

(Color):GN:(Green), BK:(Black), BU:(Blue), RD:(Red), GY:(Gray)  
OG:(Orange), WT:(White), YL:(Yellow), CR:(Clear)

|                      |              |           |
|----------------------|--------------|-----------|
| Pressure line column | Copper alloy | Ni Plated |
| Screw                | Steel        | Zn Plated |
| Housing              | PA66         | UL94V-2   |
| NAME OF PART         | MATERIAL     | NOTES     |

|   |        |                   |   |
|---|--------|-------------------|---|
| UL 标准/UL Standard:                                  | B      | C                 | D |
| 额定电压/额定 Voltage(V)/Current(A)                       | 600/65 | /                 | / |
| IEC 标准/IEC Standard:                                |        |                   |   |
| 额定电压/额定 Voltage(V)/Current(A)                       |        | 750/76            |   |
| 螺栓扭矩/Torque Tightening(N·m/Lb.in)                   |        | M5 1.5N.m/13Lb.in |   |
| 线径范围(硬线和软线) Wire Range(rigid and flexible)(mm²/AWG) |        | 16.0/20-6         |   |
| 间距/Pitch(mm)/线数范围/Poles                             |        | 14.5/01-12        |   |
| 剥线长度/Stripping length(mm)                           |        | /                 |   |
| 使用温度范围/Operating temperature(°C)                    |        | -40~+105          |   |
| 符合RoHS环保要求/Conform to RoHS                          |        | Yes               |   |

|                             |              |                        |                    |
|-----------------------------|--------------|------------------------|--------------------|
| MAT NO.:                    | /            | NAME:                  | DB16H-14.5-XXP-C-S |
| STATUS:                     | /            |                        |                    |
| APPD: Jting Chen 2025.06.16 |              |                        |                    |
| CHKD: Duck Mao 2025.06.16   |              |                        |                    |
| DFT: Steven Lu 2025.06.16   |              |                        |                    |
| SIZE: A4                    | → 000 (inch) | TYPE: CUSTOMER_DRAWING | SCALE: 1:1         |
|                             |              |                        | SHEET 1/1          |

**DORABO** 宁波地博电气有限公司  
NINGBO DORABO ELECTRICAL CO., LTD