



# 产品承认书 SPECIFICATION FOR APPROVAL

客户名称:  
CUSTOMER

我司料号:  
OUR PART NO.

XRC0.4\*3.0\*9T-SMT

我司品名:  
OUR PART NAME

Surface-mount coil inductor

送样日期:  
DATE SAMPLES

数量:  
QUANTITY

## 制造确认 MANUFACTURER APPROVE

拟制 DRAWN	审核 CHECKED	确认 APPROVED
Hu Fangting	RaoPing	ZhongCuilan

## 客户确认 CUSTOMER APPROVE

客户名称 CUSTOMER NAME:

客户料号 CUSTOMER P/N:

规格型号 DESCRIPTION: Inner diameter 3.0mm 0.4 wire 9TS

检查结果: ☐ 合格 ☐ 不合格

签名及盖章:

INSPECT RESULT ACCEPT REJECT

SIGNATURE AND STAMP

说明 REMARK:

如对本承认书内容有异议请提出或标记发送至我司，本承认书在未收到异议回复时于本承认书提供一周后生效。

Should you have any objections to the contents of this acknowledgment, please submit or mark them for delivery to our company. This acknowledgment shall take effect one week after its issuance, provided no objections are received.

东莞市祥如电子有限公司

Dongguan xiangru electronics co., ltd

Tel: 0769-86346548 Fax: 0769-86346358

email: dgxiangru@126.com



## 修订记录 Revision record


[illegible]

## 产品承认书 SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/10/15
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	Inner diameter 3.0mm 0.4 wire 9TS
我司物料编号 OUR PART NO	XRC0.4*3.0*9T-SMT	我司品名 OUR PART NAME	Surface-mount coil inductor

### 外观尺寸 Appearance of size

单位 Unit: mm




PO.	B	H	P	Tape Model	Xg F Juan
XRC0.4*3.0*9T-SMT	3.7±0.2	4.3±0.2	4.4±0.2	NH-010	Left

(以上尺寸为手工测量只做参考详细尺寸以实物为准) (The above dimensions are measured by hand for reference only. The detailed dimensions are subject to the physical objects.)

### 电路图 Schematic Diagram:

### 实物图 Physical map:



材质 Material	供应商 Supplier	线径 Wire diameter	圈数 Number of laps	内径 Inner diameter	
2PEW-N	Rongxing	0.4	9T	3.0±0.05	

### 备注 Note:

1.图中阴影线部份需去漆上锡，最小在MIN处，最大到MAX处。

The shaded area in the diagram requires paint removal and soldering, with the minimum at the MIN mark and the maximum at the MAX mark.

2.外观重点检查剥皮处理残留，针孔测试无破损，切口平整、无毛刺；爬锡测试95%以上爬锡测试95%以上。

Visual inspection focuses on residual stripping treatment, pinhole testing with no damage, clean cut edges free of burrs; Solder creep test: 95% or higher solder creep test: 95% or higher

3.材料符合RoHS标准。

The material complies with RoHS standards.

4.产品工艺：剥皮，自动上锡（千岛308H）。

Product Process: Stripping, Automatic Soldering (Qian Dao 308H)

5.产品包装方式：盘装。

Product Packaging Method: Tray-packed

1、本公司产品适用于 AV 设备、OA 设备、家电、信息服务等一般电子设备中。

**Our products are designed and promoted for use in general electronic devices such as audio-video equipment, office automation equipment, home appliance and information service.**

2、当本公司的产品使用在一般电子设备以外的领域时，对于此所引发的设备失效我司将不承担任何法律责任。

**In case of using the product for the purpose other than general electronics devices, we shall not be held liable for any dysfunctions in or damage to the equipment with which the product is used.**

3、本承认书只保证我司产品作为一个单体时的质量情况，当我司产品被安装到贵司产品上时，请贵司对使用在贵司电路上的产品情况进行了有效评价和确认。

**Our specification limits the quality of the component as a single unit. Please ensure the component is thoroughly evaluated in your application circuit.**

4、不要对产品施加过大的振动或机械冲击；

**Do not apply excessive vibration or mechanical shock to products.**

5、为防止断线，请不要使用锋利的物体接触线圈，如镊子；

**Do not touch wire with sharp objects such as tweezers to prevent wire breakage.**

6、在产品贴装时不要使用过大的压力，避免磁芯断裂。

**Do not apply excessive stress to products mounted on boards to prevent core breakage.**

7、为保证端子电极的焊接特性和包装材料处于良好状态，请于本公司发货后 6 个月内使用本产品。同时，由于端子电极的焊接特性会随时间发生变化，如果贮存时间超过 6 个月，请首先确认其焊接特性后再安装使用。

**To maintain the solderability of terminal electrodes and to keep the packing material in good condition, product should be used within 6 months from the time of delivery. And the solderability of products electrodes may decrease as time passes, so in case of storage over 6 months, solderability shall be checked**

8、存放货物的仓库应满足以下条件 Store products in a warehouse in compliance with the following condition:

条件 Conditions	元件含包装物 Packing status	元件自身 Component itself
温度 Temperature	-25~+40℃	-25~+85℃
湿度 Humidity	30~70%RH	30~70%RH

9、不要使产品遭受温度和湿度的快速变化。

**Do not subject products to rapid changes in temperature and humidity.**

10、不要将产品存放在化学环境中，如硫酸气体或碱性气体中，否则会降低电极端子的焊接特性和使电感器腐蚀。

**Do not store the products in chemical atmosphere such as one containing sulfurous acid gas or alkaline gas, that will causes poor solderability and corrosion of inductors.**

11、为了避免受潮气、灰尘等物质的影响，产品应保管于货架上。

**Store products on pallets to protect from humidity, dust, etc**

12、产品应避免热冲击、振动以及直接光照等等。

**Avoid heat shock, vibration, direct sunlight, etc.**

