

修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
AO		NEW DWG	黄艳兰	

- NOTES:
1. Material:
Insulation:PA6T,UL94V-0(Natural)
Pin:Phosphor Bronze/Tin-Plated
Tab:Brass/Tin-Plated
 2. Current Rating: 2A AC,DC
 3. Voltage Rating: 100V AC,DC
 4. Temperature Rang: -40°C~+105°C
 5. Contact Resistance: 20mΩ Max
 6. Insulation Resistance: 500MΩ Min
 7. Withstanding Voltage: 500V AC/minute

Poles	DIM(mm)			
	A	B	C	
8	10.30	4.50	8.50	±0.20
10	11.80	6.00	10.00	±0.25
12	13.30	7.50	11.50	
14	14.80	9.00	13.00	
16	16.30	10.50	14.50	
18	17.80	12.00	16.00	
20	19.30	13.50	17.50	
22	20.80	15.00	19.00	
24	22.30	16.50	20.50	
26	23.80	18.00	22.00	



深圳市华德共创科技有限公司
Shenzhen Huade co-create Technology Co.,LTD
电话: 0755-27111216 传真: 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表			TITLE: 产品名称: MX1.5双排卧贴/503148			
X.X	±0.30	X.X*	±3°	APPD: 核准: 谢亮	PART NO: 产品编号: HDGC1502DRS-2XnP	
X.XX	±0.20	X.XX*	±2°	CHECK: 校对: 王建业	DATE	SCALE
X.XXX	±0.15	X.XXX*	±1°	DRAW: 绘图: 黄艳兰	UNIT	CODE NUMBER
					1:1	mm
						A001