

	1	2	3	4	5	6	7	8																																																	
A	红色对插标识点 Red Insertion Marker					焊接端 Welded end																																																			
B																																																									
C	产品材质及表面处理Product material and surface treatment 外壳enclosure: 黄铜镀铬 (Brass chrome plated) 自锁装置Self-locking device: 黄铜镀镍 (Brass nickel plated) 线夹头Wire chuck: 黄铜镀镍 (Brass nickel plated) 内套Inner sleeve: 黄铜镀镍 (Brass nickel plated) 螺帽nut:黄铜镀铬 (Brass chrome plated) 导体conductor: 黄铜镀金 (Brass gilded) 绝缘体insulator:PPS 护套jacket: TPU			<table><tr><td>S4</td><td>Y1T</td><td>2F</td><td>1</td><td>04</td><td>1C</td><td>S</td><td>A</td><td>R</td><td>D</td><td>92</td><td>Z</td><td>N2</td><td>☒</td></tr><tr><td>类型</td><td>分体式外壳</td><td>系列</td><td>导体类型</td><td>导体数量</td><td>键位</td><td>绝缘体材质</td><td>外壳材质及电镀</td><td>定位点颜色</td><td>线夹类型</td><td>电缆直径</td><td>护套</td><td>螺帽款式</td><td>颜色默认黑色</td></tr><tr><td>type</td><td>Split-type casing</td><td>series</td><td>Conductor type</td><td>Number of conductors</td><td>Keys</td><td>Insulator material</td><td>Housing material and plating</td><td>Anchor point color</td><td>Clamp type</td><td>Cable diameter</td><td>jacket</td><td>Nut style</td><td>The color is black by default</td></tr></table>							S4	Y1T	2F	1	04	1C	S	A	R	D	92	Z	N2	☒	类型	分体式外壳	系列	导体类型	导体数量	键位	绝缘体材质	外壳材质及电镀	定位点颜色	线夹类型	电缆直径	护套	螺帽款式	颜色默认黑色	type	Split-type casing	series	Conductor type	Number of conductors	Keys	Insulator material	Housing material and plating	Anchor point color	Clamp type	Cable diameter	jacket	Nut style	The color is black by default					
S4	Y1T	2F	1	04	1C	S	A	R	D	92	Z	N2	☒																																												
类型	分体式外壳	系列	导体类型	导体数量	键位	绝缘体材质	外壳材质及电镀	定位点颜色	线夹类型	电缆直径	护套	螺帽款式	颜色默认黑色																																												
type	Split-type casing	series	Conductor type	Number of conductors	Keys	Insulator material	Housing material and plating	Anchor point color	Clamp type	Cable diameter	jacket	Nut style	The color is black by default																																												
D	产品性能Product performance 防护等级 (Ingress protection):插合时IP66/68 若电缆外形足够圆, 并且组装过程保证密封良好, 那么可以达到IP68防护等级 插合端针直径 (Mating pin diameter): (Φ0.9) / (Φ2.3) 测试电压 (Test Voltage): 875V 工作电压 (Operating Voltage): 400V Φ0.9导体额定电流 (Rated current of Φ0.9 conductor): 3A Φ2.3导体额定电流 (Rated current of Φ2.3 conductor): 25A 插拔测试 (Plugging and unplugging test)>3000次 产品耐温 (The product is temperature resistant):-55° C / +150° C 盐雾腐蚀 (Salt Spray Corrosion):>72 hr 屏蔽性能 (Shielding performance): >75 dB (<10MHz) >40 dB (<1GHz) 抗振动 (Vibration-resistant):10-2000Hz, 15g 抗冲击 (Impact-resistant):100g, 6ms			<table><tr><td colspan="2">未标注公差 Tolerances are not indicated</td><td colspan="2">视图 view</td></tr><tr><td colspan="2">0~5: ±0.1</td><td colspan="2">设计 DESIGNED</td></tr><tr><td colspan="2">6~10: ±0.15</td><td colspan="2">校对 CHECKED</td></tr><tr><td colspan="2">11~50: ±0.2</td><td colspan="2">审核 APPROVED</td></tr><tr><td colspan="2">51~100: ±0.25</td><td colspan="2">日期 date</td></tr><tr><td colspan="2">100+: ±25%</td><td colspan="2"></td></tr></table>		未标注公差 Tolerances are not indicated		视图 view		0~5: ±0.1		设计 DESIGNED		6~10: ±0.15		校对 CHECKED		11~50: ±0.2		审核 APPROVED		51~100: ±0.25		日期 date		100+: ±25%				<table><tr><td colspan="2">比例 SCALE</td><td colspan="2">1:1</td></tr></table>		比例 SCALE		1:1		<table><tr><td colspan="2">型号 MODEL</td><td colspan="2">S4. Y1T. 2F. 104. 1C. SARD92ZN2</td></tr><tr><td colspan="2">名称 PARTNAME</td><td colspan="2">S4直式插头 (2F) 护套款</td></tr></table>		型号 MODEL		S4. Y1T. 2F. 104. 1C. SARD92ZN2		名称 PARTNAME		S4直式插头 (2F) 护套款		<table><tr><td colspan="2">单位 UNIT</td><td colspan="2">mm</td></tr><tr><td colspan="2">版本 REV</td><td colspan="2">A/0</td></tr></table>		单位 UNIT		mm		版本 REV		A/0		东莞市通瑞电子科技有限公司 Dongguan Tongrui Electronic Technology Co., Ltd	
未标注公差 Tolerances are not indicated		视图 view																																																							
0~5: ±0.1		设计 DESIGNED																																																							
6~10: ±0.15		校对 CHECKED																																																							
11~50: ±0.2		审核 APPROVED																																																							
51~100: ±0.25		日期 date																																																							
100+: ±25%																																																									
比例 SCALE		1:1																																																							
型号 MODEL		S4. Y1T. 2F. 104. 1C. SARD92ZN2																																																							
名称 PARTNAME		S4直式插头 (2F) 护套款																																																							
单位 UNIT		mm																																																							
版本 REV		A/0																																																							
	1	2	3	4	5	6	7	8																																																	
						www.cntfre.com																																																			