SCT3060ARHR-VB Datasheet
N-Channel 650V (D-S) SiC Power MOSFET

PRODUCT SUMMARY		
V_{DS} (V)	650	
$R_{DS(on)}$ at 25 °C (Ω)	V_{GS} = 18 V	0.05
Q_g (nC)	90	

FEATURES

- Low figure-of-merit (FOM) R_{on} x Q_g
- Low input capacitance (C_{iss})
- Reduced switching and conduction losses
- Ultra low gate charge (Q_g)
- Avalanche energy rated (UIS)

RoHS

APPLICATIONS

- Server and telecom power supplies
- Switch mode power supplies (SMPS)
- Power factor correction power supplies (PFC)
- DC/DC converter

TO-247



•Pin1 D - Drain
•Pin2 S - Source(Power)
•Pin3 S - Source(Driver)
•Pin4 G - Gate



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS (T_C = 25 °C, unless otherwise noted)					
PARAMETER			SYMBOL	LIMIT	UNIT
Drain-Source Voltage			V_{DS}	650	V
Gate-Source Voltage			V_{GS}	-10 / +22	
Continuous Drain Current (T_J = 150 °C)	V_{GS} at 18 V	T_C = 25 °C	I_D	40	A
		T_C = 100 °C		32	
Pulsed Drain Current [a]			I_{DM}	120	
Linear Derating Factor				2.1	W/°C
Single Pulse Avalanche Energy [b]			E_{AS}	225	mJ
Maximum Power Dissipation			P_D	187	W
Operating Junction and Storage Temperature Range			T_J, T_{stg}	-55 to +175	°C
Drain-Source Voltage Slope	T_J = 125 °C		dV/dt	50	V/ns
Reverse Diode dV/dt [d]				15	
Soldering Recommendations (Peak Temperature) [c]	for 10 s			260	°C

Notes

a. Repetitive rating; pulse width limited by maximum junction temperature.
b. V_{DD} = 100 V, starting T_J = 25 °C, L = 0.5mH, R_g = 25 Ω, I_{AS} = 30A.
c. 1.6 mm from case.
d. $I_{SD} \leq I_D$, dI/dt = 100 A/μs, starting T_J = 25 °C.

THERMAL RESISTANCE RATINGS				
PARAMETER	**SYMBOL**	**TYP.**	**MAX.**	**UNIT**
Maximum Junction-to-Ambient	R_{thJA}	-	40	°C/W
Maximum Junction-to-Case (Drain)	R_{thJC}	-	0.8	

SPECIFICATIONS (T_J = 25 °C, unless otherwise noted)						
PARAMETER	**SYMBOL**	**TEST CONDITIONS**	**MIN.**	**TYP.**	**MAX.**	**UNIT**
Static						
Drain-Source Breakdown Voltage	V_{DS}	V_{GS} = 0 V, I_D = 1 mA	650	-	-	V
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	Reference to 25 °C, I_D = 1 mA	-	0.70	-	V/°C
Gate-Source Threshold Voltage (N)	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 10 mA	2	-	5	V
Gate-Source Leakage	I_{GSS}	V_{GS} = +22 V	-	-	100	nA
		V_{GS} = -10 V	-	-	100	μA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 650V, V_{GS} = 0 V	-	10	-	μA
		V_{DS} = 650 V, V_{GS} = 0 V, T_J = 125 °C	-	-	100	
Drain-Source On-State Resistance	$R_{DS(on)}$	V_{GS} = 18 V, I_D = 20A	-	0.05	-	Ω
Forward Transconductance	g_{fs}	V_{DS} = 0 V, I_D = 30 A	-	12	-	S
Dynamic						
Input Capacitance	C_{iss}	V_{GS} = 0 V, V_{DS} = 600 V, f = 1 MHz	-	2000	-	pF
Output Capacitance	C_{oss}		-	175	-	
Reverse Transfer Capacitance	C_{rss}		-	9	-	
Effective Output Capacitance, Energy Related [a]	$C_{o(er)}$	V_{DS} = 0 V to 400 V, V_{GS} = 0 V	-	156	-	
Effective Output Capacitance, Time Related [b]	$C_{o(tr)}$		-	268	-	
Total Gate Charge	Q_g	V_{GS} = -5/18 V, I_D = 20 A, V_{DS} = 400 V	-	70	-	nC
Gate-Source Charge	Q_{gs}		-	20	-	
Gate-Drain Charge	Q_{gd}		-	23	-	
Turn-On Delay Time	$t_{d(on)}$	V_{DD} = 400 V, I_D = 20A, V_{GS} = -5/18 V , R_g = 2 Ω	-	12	15	ns
Rise Time	t_r		-	10	13	
Turn-Off Delay Time	$t_{d(off)}$		-	20	-	
Fall Time	t_f		-	10	-	
Gate Input Resistance	R_g	f = 1 MHz, open drain	-	2.2	-	Ω
Drain-Source Body Diode Characteristics						
Continuous Source-Drain Diode Current	I_S	MOSFET symbol showing the integral reverse p - n junction diode	-	-	40	A
Pulsed Diode Forward Current	I_{SM}		-	-	120	
Diode Forward Voltage	V_{SD}	T_J = 25 °C, I_S = 20 A, V_{GS} = 0	-	-	4.1	V
Reverse Recovery Time	t_{rr}	T_J = 25 °C, I_F = I_S = 20 A, dI/dt = 1000 A/μs, V_R = 400 V	-	20	-	ns
Reverse Recovery Charge	Q_{rr}		-	60	-	μC
Reverse Recovery Current	I_{RRM}		-	10	-	A

Notes

a. $C_{oss(er)}$ is a fixed capacitance that gives the same energy as C_{oss} while V_{DS} is rising from 0 % to 60 % V_{DSS}.

b. $C_{oss(tr)}$ is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 % to 60 % V_{DSS}.



Fig.1 Output characteristics Tj=25℃



Fig.2 Output characteristics Tj=175℃



Fig.3 Normalized On-Resistance vs. Temperature



Fig.4 On-Resistance vs. Drain Current For Various Temperatures



Fig.5 On-Resistance vs. Temperature For Various Gate Voltage



Fig.6 Transfer Characteristic For Various Junction Temperatures



Fig.7 Body Diode Characteristic at 25℃



Fig.8 Threshold Voltage vs. Temperature



Fig.9 Gate Charge Characteristics



Fig.10 3rd Quadrant Characteristic at 25℃



Figure 11. Output Capacitor Stored Energy



Fig.12 Capactitances vs. Drain-Source Voltage(0-200V)



Fig.13 Capactitances vs. Drain-Source Voltage(0-600V)



Figure 14. Clamped Inductive Switching Energy vs. Drain Current(V_{DD}=400V)



Figure 15. Clamped Inductive Switching Energy vs. Drain Current(V_{DD}=520V)



Figure 16. Clamped Inductive Switching Energy vs. $R_{g(ext)}$



Figure 17. Clamped Inductive Switching Energy vs. Temperature



Figure 18. Switching Times vs. $R_{g(ext)}$

TO-247-4L


E
A
E3
(6.35)
Q
S
D
E2
(Ø3)
(12.7)
(8.38)
E5
L2
L1
L
Polish
1
2
3
4
e1
e
4x b
B
A
A2
A1
c
ØP
E1
E4
D2
D1
ØP1
D3
b3
4
3
2
1
b1
3x b2

DIM.	MILLIMETERS		
	MIN.	NOM.	MAX.
A	4.83	5.02	5.21
A1	2.29	2.41	2.54
A2	1.91	2.00	2.16
b	1.07	1.20	1.33
b1	2.39	2.67	2.94
b2	1.07	1.30	1.60
b3	2.39	2.53	2.69
c	0.55	0.60	0.68
D	23.30	23.45	23.60
D1	16.25	16.55	17.65
D2	0.95	1.19	1.25
D3	5.55	5.71	6.01
E	15.75	15.94	16.13
E1	13.10	14.02	14.15
E2	3.68	4.40	5.10
E3	1.00	1.45	1.90
E4	12.38	13.26	13.43
E5	1.95	2.15	2.35
e	2.54 BSC.		
e1	5.08 BSC.		
L	17.31	17.57	17.82
L1	3.97	4.19	4.37
L2	2.35	2.50	2.65
ØP	3.51	3.61	3.65
ØP1	7.19 ref.		
Q	5.49	5.79	6.00
S	6.04	6.17	6.30

Notes

- All dimensions are in mm
- Dimension D and E do not include mold flash.
- Creepage 1 is 8.40 mm (ref.) which is the distance alongside the surface between drain (pin 1) and trough the notch towards source (pin 2). Creepage 2 is 7.70 mm (ref.) which is the distance from end of the copper slug on the backside of the package to either pin 2, pin 3 or pin 4

Disclaimer

All products due to improve reliability, function or design or for other reasons, product specifications and data are subject to change without notice.

Taiwan VBsemi Electronics Co., Ltd., branches, agents, employees, and all persons acting on its or their representatives (collectively, the "Taiwan VBsemi"), assumes no responsibility for any errors, inaccuracies or incomplete data contained in the table or any other any disclosure of any information related to the product.(www.VBsemi.com)

Taiwan VBsemi makes no guarantee, representation or warranty on the product for any particular purpose of any goods or continuous production. To the maximum extent permitted by applicable law on Taiwan VBsemi relinquished: (1) any application and all liability arising out of or use of any products; (2) any and all liability, including but not limited to special, consequential damages or incidental ; (3) any and all implied warranties, including a particular purpose, non-infringement and merchantability guarantee.

Statement on certain types of applications are based on knowledge of the product is often used in a typical application of the general product VBsemi Taiwan demand that the Taiwan VBsemi of. Statement on whether the product is suitable for a particular application is non-binding. It is the customer's responsibility to verify specific product features in the products described in the specification is appropriate for use in a particular application. Parameter data sheets and technical specifications can be provided may vary depending on the application and performance over time. All operating parameters, including typical parameters must be made by customer's technical experts validated for each customer application. Product specifications do not expand or modify Taiwan VBsemi purchasing terms and conditions, including but not limited to warranty herein.

Unless expressly stated in writing, Taiwan VBsemi products are not intended for use in medical, life saving, or life sustaining applications or any other application. Wherein VBsemi product failure could lead to personal injury or death, use or sale of products used in Taiwan VBsemi such applications using client did not express their own risk. Contact your authorized Taiwan VBsemi people who are related to product design applications and other terms and conditions in writing.

The information provided in this document and the company's products without a license, express or implied, by estoppel or otherwise, to any intellectual property rights granted to the VBsemi act or document. Product names and trademarks referred to herein are trademarks of their respective representatives will be all.

Material Category Policy

Taiwan VBsemi Electronics Co., Ltd., hereby certify that all of the products are determined to be RoHS compliant and meets the definition of restrictions under Directive of the European Parliament 2011/65 / EU, 2011 Nian. 6. 8 Ri Yue restrict the use of certain hazardous substances in electrical and electronic equipment (EEE) - modification, unless otherwise specified as inconsistent.(www.VBsemi.com)

Please note that some documents may still refer to Taiwan VBsemi RoHS Directive 2002/95 / EC. We confirm that all products identified as consistent with the Directive 2002/95 / EC European Directive 2011/65 /.

Taiwan VBsemi Electronics Co., Ltd. hereby certify that all of its products comply identified as halogen-free halogen-free standards required by the JEDEC JS709A. Please note that some Taiwanese VBsemi documents still refer to the definition of IEC 61249-2-21, and we are sure that all products conform to confirm compliance with IEC 61249-2-21 standard level JS709A.