STGP10M65DF2-VB Datasheet

600V Trench and Fieldstop IGBT

PRODUCT SUMMARY		
V_{CE} (V)	600	
I_C (A)	20 (TC=25°C)	10(TC=100°C)
V_{CE} (sat) (V)	1.7	
I_{CM} (A)	30	

FEATURES

- Very Low VCEsat
- Low turn-off losses
- High speed switching
- Maximum junction temperature 175°C
- Ultra low gate charge (Q_g)
- Avalanche energy rated (UIS)

RoHS COMPLIANT
HALOGEN FREE

TO-220



Top View



APPLICATIONS

- Telecommunications
  - Server and telecom power supplies
- Lighting
  - High-intensity discharge (HID)
  - Fluorescent ballast lighting
- Consumer and computing
  - ATX power supplies
- Industrial
  - Welding
  - Battery chargers
- Renewable energy
  - Solar (PV inverters)
- Switch mode power supplies (SMPS)

Package pin definition

- Pin1 G - Gate
- Pin2 C & backside - Collector
- Pin3 E - Emitter

ABSOLUTE MAXIMUM RATINGS (T_C = 25 °C, unless otherwise noted)

PARAMETER			SYMBOL	LIMIT	UNIT
Collector-Emitter Voltage			V_{CE}	600	V
Gate-Emitter Voltage			V_{GE}	±30	
Continuous Collector Current (T_J = 150 °C)	V_{GE} at 15 V	T_C = 25 °C	I_C	20	A
		T_C = 100 °C		10	
Pulsed Collector Current [a]			I_{CM}	30	
Diode Forward Current [b]			I_F	10	A
Maximum Power Dissipation		T_C = 25 °C	P_D	150	W
		T_C = 100 °C		62	W
Operating Junction and Storage Temperature Range			T_J, T_{stg}	-55 to +175	°C
Short Circuit Withstand Time TC=150°C	VGE= 15V, VCE≤ 400V		t_{SC}	3	μs
Short Circuit Withstand Time TC=100°C	VGE= 15V, VCE≤330V			5	
Soldering Recommendations (Peak Temperature) [c]	for 10 s			260	°C

Notes

a. Repetitive rating; pulse width limited by maximum junction temperature.

b. Current limited by maximum junction temperature.

c. 1.6 mm from case.

THERMAL RESISTANCE RATINGS				
PARAMETER	**SYMBOL**	**TYP.**	**MAX.**	**UNIT**
Maximum Junction-to-Ambient	R_{thJA}	-	78	°C/W
Maximum Junction-to-Case	R_{thJC}	-	3.6	

SPECIFICATIONS (T_J = 25 °C, unless otherwise noted)							
PARAMETER	**SYMBOL**	**TEST CONDITIONS**		**MIN.**	**TYP.**	**MAX.**	**UNIT**
Static							
Collector-Emitter Breakdown Voltage	BV_{CE}	V_{GE} = 0 V, I_C = 250 μA		600	-	-	V
		V_{GE} = 0 V, I_C = 1 mA		600	-	-	
Gate-Source Threshold Voltage (N)	$V_{GE(th)}$	V_{CE} = V_{GE}, I_D = 250 μA		4	5	6	V
Zero Gate Voltage Collector Current	I_{CES}	V_{CE} = 600 V, V_{GE} = 0 V, T_J = 25 °C		-	1	20	μA
		V_{CE} = 600 V, V_{GE} = 0 V, T_J = 150 °C		-	1000	-	μA
Gate-Emitter Leakage Current	I_{GES}	V_{CE} = 0 V, V_{GS} = ± 2 0 V		-	-	100	nA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	V_{GE} = 15 V	I_C = 10 A	-	1.7	2.1	V
Forward Transconductance	g_{fs}	V_{CE} = 20 V, I_C = 10 A		-	18	-	S
Dynamic							
Input Capacitance	C_{ies}	V_{GE} = 0 V, V_{CE} = 25 V, f = 500 KHz		-	1136	-	pF
Output Capacitance	C_{oes}			-	9 1	-	
Reverse Transfer Capacitance	C_{res}			-	32	-	
Turn-on Energy	E_{on}	V_{CE} = 400 V , V_{GE} = 0 /15V, I_C = 10 A, R_g = 10Ω		-	0.46	-	nJ
Turn-off Energy	E_{off}			-	0.36	-	
Total Gate Charge	Q_g	V_{GE} = 15 V	I_C = 10 A, V_{CE} = 400 V	-	8 2	-	nC
Gate-Emitter Charge	Q_{ge}			-	19	-	
Gate to Collector Charge	Q_{gc}			-	25	-	
Turn-On Delay Time	$t_{d(on)}$	V_{CE} = 400 V , V_{GE} = 0 /15V, I_C = 10 A, R_g = 10Ω		-	28	-	ns
Rise Time	t_r			-	42	-	
Turn-Off Delay Time	$t_{d(off)}$			-	186	-	
Fall Time	t_f			-	34	-	
Internal emitter inductance measured 5 mm	L_E			-	13	-	nH
Diode Characteristics							
Diode Forward Current	I_F	IGBT symbol showing the integral reverse junction diode		-	-	10	A
Pulsed Diode Forward Current	I_{FM}			-	-	30	
Diode Forward Voltage	V_F	I_F = 10 A		-	1.65	2.0	V
Reverse Recovery Time	t_{rr}	T_J = 25 °C, I_F = 10 A, dI_F/dt = 200 A/μs, V_R = 400 V		-	70	-	ns
Reverse Recovery Charge	Q_{rr}			-	0.48	-	μC
Reverse Recovery Current	I_{RRM}			-	8	-	A



Figure 1. **Forward bias safe operating area** (D=0, T_C=25°C, T_{vj}≤175°C; V_{GE}=15V. Recommended use at V_{GE}≥7.5V)



Figure 2. **Power dissipation as a function of case temperature** (T_{vj}≤175°C)



Figure 3. **Collector current as a function of case temperature**



Figure 4. **Typical output characteristic**



Figure 5. **Typical output characteristic** (T_{vj}=150°C)



Figure 6. **Typical transfer characteristic** (V_{CE}=20V)



Figure 7. **Typical collector-emitter saturation voltage as a function of junction temperature**



Figure 8. **Typical switching times as a function of collector current**



Figure 9. **Typical switching times as a function of gate resistor**



Figure 10. **Typical switching times as a function of junction temperature**



Figure 11. **Gate-emitter threshold voltage as a function of junction temperature**



Figure 12. **Typical switching energy losses as a function of collector current**



Figure 13. **Typical switching energy losses as a function of gate resistor**



Figure 14. **Typical switching energy losses as a function of junction temperature**



Figure 15. **Typical switching energy losses as a function of collector emitter voltage**



Figure 16. **Typical gate charge**



Figure 17. **Typical capacitance as a function of collector-emitter voltage**



Figure 18. **IGBT transient thermal impedance**



Figure 19. **Diode transient thermal impedance as a function of pulse width**



Figure 20. **Typical reverse recovery time as a function of diode current slope**

TO-220AB



DIM.	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	4.25	4.65	0.167	0.183
b	0.69	1.01	0.027	0.040
b(1)	1.20	1.73	0.047	0.068
c	0.36	0.61	0.014	0.024
D	14.85	15.49	0.585	0.610
E	10.04	10.51	0.395	0.414
e	2.41	2.67	0.095	0.105
e(1)	4.88	5.28	0.192	0.208
F	1.14	1.40	0.045	0.055
H(1)	6.09	6.48	0.240	0.255
J(1)	2.41	2.92	0.095	0.115
L	13.35	14.02	0.526	0.552
L(1)	3.32	3.82	0.131	0.150
Ø P	3.54	3.94	0.139	0.155
Q	2.60	3.00	0.102	0.118
ECN: X12-0208-Rev. N, 08-Oct-12 DWG: 5471				

Notes

* M = 1.32 mm to 1.62 mm (dimension including protrusion) Heatsink hole for HVM

Disclaimer

All products due to improve reliability, function or design or for other reasons, product specifications and data are subject to change without notice.

Taiwan VBsemi Electronics Co., Ltd., branches, agents, employees, and all persons acting on its or their representatives (collectively, the "Taiwan VBsemi"), assumes no responsibility for any errors, inaccuracies or incomplete data contained in the table or any other any disclosure of any information related to the product.(www.VBsemi.com)

Taiwan VBsemi makes no guarantee, representation or warranty on the product for any particular purpose of any goods or continuous production. To the maximum extent permitted by applicable law on Taiwan VBsemi relinquished: (1) any application and all liability arising out of or use of any products; (2) any and all liability, including but not limited to special, consequential damages or incidental ; (3) any and all implied warranties, including a particular purpose, non-infringement and merchantability guarantee.

Statement on certain types of applications are based on knowledge of the product is often used in a typical application of the general product VBsemi Taiwan demand that the Taiwan VBsemi of. Statement on whether the product is suitable for a particular application is non-binding. It is the customer's responsibility to verify specific product features in the products described in the specification is appropriate for use in a particular application. Parameter data sheets and technical specifications can be provided may vary depending on the application and performance over time. All operating parameters, including typical parameters must be made by customer's technical experts validated for each customer application. Product specifications do not expand or modify Taiwan VBsemi purchasing terms and conditions, including but not limited to warranty herein.

Unless expressly stated in writing, Taiwan VBsemi products are not intended for use in medical, life saving, or life sustaining applications or any other application. Wherein VBsemi product failure could lead to personal injury or death, use or sale of products used in Taiwan VBsemi such applications using client did not express their own risk. Contact your authorized Taiwan VBsemi people who are related to product design applications and other terms and conditions in writing.

The information provided in this document and the company's products without a license, express or implied, by estoppel or otherwise, to any intellectual property rights granted to the VBsemi act or document. Product names and trademarks referred to herein are trademarks of their respective representatives will be all.

Material Category Policy

Taiwan VBsemi Electronics Co., Ltd., hereby certify that all of the products are determined to be RoHS compliant and meets the definition of restrictions under Directive of the European Parliament 2011/65 / EU, 2011 Nian. 6. 8 Ri Yue restrict the use of certain hazardous substances in electrical and electronic equipment (EEE) - modification, unless otherwise specified as inconsistent.(www.VBsemi.com)

Please note that some documents may still refer to Taiwan VBsemi RoHS Directive 2002/95 / EC. We confirm that all products identified as consistent with the Directive 2002/95 / EC European Directive 2011/65 /.

Taiwan VBsemi Electronics Co., Ltd. hereby certify that all of its products comply identified as halogen-free halogen-free standards required by the JEDEC JS709A. Please note that some Taiwanese VBsemi documents still refer to the definition of IEC 61249-2-21, and we are sure that all products conform to confirm compliance with IEC 61249-2-21 standard level JS709A.