



REV.	DESCRIPTION	ECN NO.	NAME	DATE
------	-------------	---------	------	------

Part No	CKT	A	B	C	D
WF-PA2.0-2PF1	2	2.00	4.55	7.95	6.10
WF-PA2.0-3PF1	3	4.00	6.55	9.95	8.10
WF-PA2.0-4PF1	4	6.00	8.55	11.95	10.10
WF-PA2.0-5PF1	5	8.00	10.55	13.95	12.10
WF-PA2.0-6PF1	6	10.00	12.55	15.95	14.10
WF-PA2.0-7PF1	7	12.00	14.55	17.95	16.10
WF-PA2.0-8PF1	8	14.00	16.55	19.95	18.10
WF-PA2.0-9PF1	9	16.00	18.55	21.95	20.10
WF-PA2.0-10PF1	10	18.00	20.55	23.95	22.10
WF-PA2.0-11PF1	11	20.00	22.55	25.95	24.10
WF-PA2.0-12PF1	12	22.00	24.55	27.95	26.10
WF-PA2.0-13PF1	13	24.00	26.55	29.95	28.10
WF-PA2.0-14PF1	14	26.00	28.55	31.95	30.10
WF-PA2.0-15PF1	15	28.00	30.55	33.95	32.10
WF-PA2.0-16PF1	16	30.00	32.55	35.95	34.10

序号	品名	材质
1	2.0 R型卧式WTB胶芯 2.0 Pitch R/A Wire To Board Housing(H=5.7)	PA6T UL94V-0 米黄色 LCP UL94V-0 本色
2	2.0 R型卧式WTB端子 2.0 Pitch S/T Wire To Board Terminal(H=8.7)	铜合金/表面镀锡 Copper Alloy/ Tin Plating
3	2.0 R型卧式WTB焊片 2.0 Pitch R/A Wire To Board Fitting Nail(H=5.7)	铜合金/表面镀锡 Copper Alloy/ Tin Plating

技术指标(Technical Index):  
 1.塑件表面应光洁、无毛边、无明显收缩、缺陷、裂纹等现象。  
 (The surface of the plastic parts should be smooth, no rough edges, no obvious shrinkage, defects, cracks and other phenomena)  
 2.工作温度(Temperature range): -25°C~+85°C.  
 3.额定电压(Rated voltage): 250V, AC/DC.  
 4.额定电流: 3.0A, AC/DC.  
 5.接触电阻(Contact resistance): ≤20mΩ.  
 6.绝缘电阻(Insulation resistance): ≥1000MΩ.  
 7.耐电压(Withstanding voltage): 800V AC/minute.

GENERAL TOLERANCE	DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD				
DIM. x. ±0.50 x.x ±0.20 x.xx ±0.10 GENERAL ANGLE: x.* ±1°	TITLE: 2.00Pitch R型卧式WTB				
	DWG. NO.: WF-PA2.0-XPf1		CHECKED: MAX		
	PART NO.: WF-PA2.0-XPf1		DRAWN: ELLA		
	UNIT: mm	SCALE: none	SHEET: 1 of 1	DWG. SIZE: A4	LAYER: bxconn
	APPROVED: WILL				

