





修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW DWG		



- (1)Temperature: -25℃~85℃
- (2)Relative humidity: ≤85% RH
- (3)Rating: AC/DC 150V 1A
- (4)Contact Resistance:≤30m ohm
- (5)Insulation Resistance:≥500M ohm
- (6)Withstand Voltage: AC 500V for 1min
- (7)Soldering Temperature: 260±5℃ 5±0.5s

 深圳市华德共创科技有限公司 Shenzhen Huade co-create Technology Co.,LTD 电话: 0755-27111216 传真: 0755-29940187							
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表				TITLE: 产品名称: DF13 1.25间距单排立贴针座			
X.X ±0.30	X.X* ±3°	APPD: 核准: 谢亮		PART NO: 产品编号: HDGC1252WV-S-5P			
X.XX ±0.30	X.XX* ±2°	CHECK: 校对: 王建业		DATE	SCALE	UNIT	CODE NUMBER
X.XXX ±0.10	X.XXX* ±1°	DRAW: 绘图: 黄艳兰			1:1	mm	A001