

Specification Features:

- ◆ Low Forward Voltage Drop
- ◆ LL-34 Package (JEDEC)
- ◆ Through-Hole Device Type Mounting Hermetically Sealed Glass
- ◆ Compression Bonded Construction
- ◆ All External Surfaces Are Corrosion Resistant And Leads Are Readily Solderable
- ◆ Solderable RoHS Compliant
- ◆ Solder Hot Dip Tin (Sn) Lead Finish



SURFACE MOUNT LL34 Cathode Band Color: Black

Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units
P_D	Power Dissipation	200	mW
T_{STG}	Storage Temperature Range	-65 to +125	$^\circ\text{C}$
T_J	Operating Junction Temperature	+125	$^\circ\text{C}$
V_{RRM}	Repetitive Peak Reverse Voltage	30	V
V_R	Maximum DC Blocking Voltage	30	V
$I_{F(AV)}$	Average Forward Rectified Current	200	mA
I_{FSM}	Peak Forward Surge Current	4	A




ELECTRICAL SYMBOL

These ratings are limiting values above which the serviceability of the diode may be impaired.

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Condition	Limits			Unit
			Min	Typ	Max	
B_V	Breakdown Voltage	$I_R = 10\mu\text{A}$	30			Volts
I_R	Reverse Leakage Current	$V_R = 25\text{V}$			2	μA
V_F	Forward Voltage	$I_F = 0.1\text{mA}$ $I_F = 1\text{mA}$ $I_F = 10\text{mA}$ $I_F = 30\text{mA}$ $I_F = 100\text{mA}$			0.24 0.32 0.40 0.50 0.80	Volts
T_{RR}	Reverse Recovery Time	$I_F = I_R = 10\text{mA}$ $R_L = 100\Omega$ $I_{RR} = 1\text{mA}$		5		nS
C	Capacitance	$V_R = 1\text{V}, f = 1\text{MHz}$		7	10	pF

Package Outline



DIM	LL-34			
	Millimeters		Inches	
	Min	Max	Min	Max
A	3.30	3.60	0.130	0.142
B	1.40	1.50	0.055	0.059
C	0.35	0.50	0.014	0.020

Notes:

1. All dimensions are within DO213AC JEDEC standard.
2. LL-34 polarity denoted by cathode band.

Revision History

Rev.	Change	Date
V1.0	Initial version	2/23/2024

Important Notice

JSMSEMI Semiconductor (JSMSEMI) PRODUCTS ARE NEITHER DESIGNED NOR INTENDED FOR USE IN MILITARY AND/OR AEROSPACE, AUTOMOTIVE OR MEDICAL DEVICES OR SYSTEMS UNLESS THE SPECIFIC JSMSEMI PRODUCTS ARE SPECIFICALLY DESIGNATED BY JSMSEMI FOR SUCH USE. BUYERS ACKNOWLEDGE AND AGREE THAT ANY SUCH USE OF JSMSEMI PRODUCTS WHICH JSMSEMI HAS NOT DESIGNATED FOR USE IN MILITARY AND/OR AEROSPACE, AUTOMOTIVE OR MEDICAL DEVICES OR SYSTEMS IS SOLELY AT THE BUYER' S RISK.

JSMSEMI assumes no liability for application assistance or customer product design. Customers are responsible for their products and applications using JSMSEMI products.

Resale of JSMSEMI products or services with statements diferent from or beyond the parameters stated by JSMSEMI for that product or service voids all express and any implied warranties for the associated JSMSEMI product or s ervice. JSMSEMI is not responsible or liable for any such statements.

JSMSEMI All Rights Reserved. Information and data in this document are owned by JSMSEMI wholly and may not be edited, reproduced, or redistributed in any way without the express written consent from JSMSEMI.

Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the JSMSEMI product that you intend to use.

For additional information please contact Kevin@jsmsemi.com or visit www.jsmsemi.com