



PRODUCT SPECIFICATION SHEET



Customer	-		
Customer P/N	TBA		
Product Type	Temperature Compensated Crystal Oscillator		
Part Number	9T26000002	Version	S0
Part Description	SMD TCXO 2.0 x 1.6		
Nominal Frequency	26.000000MHz		

Prepared	Han Shuang
Reviewed	Kuro Peng
Approved	Jay Lee
Date	2020-10-30

Customer's Approval & Date :

廣東惠倫晶體科技股份有限公司

中国广东省东莞市黄江镇东环路鸡啼岗段68号
68 Donghuan Road, Jitigang Village, Huangjiang,
Dongguan, Guangdong Province, P. R. China



WEB : <http://www.dgylec.com/>

TEL : +86 (0) 769 - 38879888

FAX : +86 (0) 769 - 38879889

EMAIL : yl@dgylec.com



Moisture Sensitivity Level 1

CONTENTS

#	Item	Page
1	History of Specification Revision	3
2	Electrical Specifications	4
	2.1 Operation conditions	4
	2.2 Output characteristics	4
	2.3 Frequency characteristics	4
	2.4 Phase noise characteristics	5
3	Product Design	6
	3.1 Package dimensions and pad functions	6
	3.2 Recommended land pattern	6
	3.3 Recommended reflow profile	6
4	Testing Circuit	7

1. History of Specification Revision

Ver.	Contents	Date	Reviser	Remark
S0	Initial release	2020-10-30	Han Shuang	

2. Electrical Specifications

2.1 Operation conditions

#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Nominal frequency	26.000000			MHz	
2	Supply voltage (V_{CC})	1.7	1.8	3.3	V	
3	Current consumption	-	-	1.5	mA	
4	Operating temperature range	-40	-	+85	°C	
5	Storage temperature range	-40	-	+90	°C	

2.2 Output characteristics

#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Output type	Clipped sine wave			-	Decoupling capacitor is required in external circuit
2	Standard output Load	10 K Ω //10 pF			-	
3	Output level	0.8	-	1.5	V_{pp}	
4	Duty cycle	40	50	60	%	
5	Harmonics	-	-	-5	dBc	
6	Start-up time vs. frequency	-	-	2.0	ms	Within ± 1.0 ppm of final frequency
7	Start-up time vs. output level	-	-	2.0	ms	Reach 90% of final V_{pp} output level

2.3 Frequency characteristics

#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Nominal frequency	26.000000			MHz	
2	Frequency tolerance before reflow	-1.0	-	+1.0	ppm	At $25\pm 2^\circ\text{C}$, before reflow, refer to nominal frequency
3	Frequency tolerance after reflow	-2.0	-	+2.0	ppm	At $25\pm 2^\circ\text{C}$, after 2 times of reflow, refer to nominal frequency (See below NOTE 1)
4	Frequency stability vs. temperature	-0.5	-	+0.5	ppm	Refer to frequency at 25°C within operating temperature range
5	Frequency stability vs. supply voltage	-0.2	-	+0.2	ppm	$\pm 5\%$ V_{CC} variation
6	Frequency stability vs. load variation	-0.2	-	+0.2	ppm	$\pm 5\%$ load variation
7	Aging over 1st year	-1.0	-	+1.0	ppm	At $25\pm^\circ\text{C}$

NOTE 1: Frequency is measured after 24 hours after reflow cycles.


2. Electrical Specifications (Cont.)

2.4 Phase noise characteristics


#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Phase noise at 10Hz offset	-	-	-83	dBc/Hz	
2	Phase noise at 100Hz offset	-	-	-108	dBc/Hz	
3	Phase noise at 1kHz offset	-	-	-135	dBc/Hz	
4	Phase noise at 10kHz offset	-	-	-148	dBc/Hz	
5	Phase noise at 100kHz offset	-	-	-148	dBc/Hz	
6	Phase noise at 1MHz offset	-	-	-148	dBc/Hz	

3. Product Design


3.1 Package dimensions and pad functions




3.2 Recommended land pattern



3.3 Recommended reflow profile



4. Testing Circuit



External Components:

Parts	Function	Recommended
C1	AC noise bypass for V _{DD}	10nF
C3	DC block for output	10nF
RL	Load resistance	10KΩ
CL	Load capacitance	10pF