

1	2	3	4	5	6	7	8	9	10		
							REV.	ECN NO.	DESCRIPTION	APP.	DATE
							A				
F											F
E											E
D											D
C											C
B											B
A											A

6.65

2.05

PLUG

AFTER MATING

USB TYPE-C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND

6.40

4.80

3.50

2.50

1.50

0.50

0.30(12X)

0.60(4X)

1.80(2X)

0.80(2X)

0.60(4X)

9.24

11.24

4.00

4.60

5.70

2.10

P.C.B EDGE

PRODUCT EDGE

RECOMMENDED PCB LAYOUT(TOP VIEW)

THICKNESS 0.80MM;DEFAULT TOLERANCE:±0.05

TOLERANCES
一般公差

UNIT : mm

DISTANCE

X.

±0.30

.X

±0.25

.XX

±0.15

.XXX

±0.10

ANGLE

X°

±2°

.X°

±1°

.XX°

±0.5°

DRAWN

TONY

CHECKED

JACK

APPROVE

DAVID

TITLE : TYPE-C 16PIN 单排 沉板1.0mm L=6.5mm

PARTS NO. :

DWG NO. :

SIZE A4

SCALE 1:1

SHEET 1 of 1

REV. A

THIS PRODUCT SHOULD MEET HAZARDOUS MATERIAL CONTROL DIERCTIVE OF JUN SHENG JIE FROM RAW MATERIAL TO MANUFACTURING, PACKAGE AND DELIVERY.

JSJ_frame_C

Rev. A 2016/08/17

2	3	4	5	6	7	8	9	10
---	---	---	---	---	---	---	---	----

