


1.Features

- $V_{DS(V)} = -30V$
- $I_D = -5.3A$
- $R_{DS(ON)} < 38m\Omega (V_{GS} = -10V)$
- $R_{DS(ON)} < 59m\Omega (V_{GS} = -4.5V)$

2.Pinning Information

Pin	Symbol	Description
1,3	S2,S1	SOURCE
2,4	G2,G1	GATE
5,6,7,8	D2,D1	DRAIN



3.Absolute Maximum Ratings $T_A = 25^\circ C$

Parameter	Symbol	Rating	Units
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	± 20	
Drain Current (Continuous)	I_D	-5.3	A
Drain Current (Pulsed) ^a	I_{DM}	-20	
Total Power Dissipation @ $T_A = 25^\circ C$	P_D	2	W
Maximum Diode Forward Current	I_S	-1.9	A
Storage Temperature Range	T_J, T_{STG}	-55 to 150	$^\circ C$
Thermal Resistance Junction to Ambient (PCB mounted) ^b	$R_{\theta JA}$	50	$^\circ C/W$

Notes:

a: Repetitive Rating: Pulse width limited by the maximum junction temperature.

b: 1-in² 2oz Cu PCB board.



4. Electrical Characteristic ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Off Characteristics						
Drain-source breakdown voltage	BV_{DSS}	$V_{GS}=0V, I_D=-250\mu A$	-30			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-24V, V_{GS}=0V$			-1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$			± 100	nA
On Characteristics ^b						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-1	-1.5	-2.5	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=-10V, I_D=-5.3A$		38	41	m Ω
		$V_{GS}=-4.5V, I_D=-3.9A$		59	75	m Ω
Forward Transconductance	g_{FS}	$V_{DS}=-10V, I_D=-5.3A$		11		S
Dynamic Characteristics ^c						
Input Capacitance	C_{iss}	$V_{DS}=-15V, V_{GS}=0V, f=1MHz$		504		pF
Output Capacitance	C_{oss}			68		pF
Reverse Transfer Capacitance	C_{rss}			56		pF
Switching Characteristics ^c						
Total Gate Charge	Q_g	$V_{DS}=-15V, I_D=-3.6A$ $V_{GS}=-10V$		12		nC
Gate-Source Charge	Q_{gs}			2.3		nC
Gate-Drain Charge	Q_{gd}			1.4		nC
Turn-on Delay Time	$t_{D(on)}$	$V_{DD}=-15V, R_L=5\Omega, I_D=-3A$ $V_{GEN}=-10\Omega, R_G=6\Omega$		8.1		ns
Turn-on Rise Time	t_r			3.3		ns
Turn-Off Delay Time	$t_{D(off)}$			29.3		ns
Turn-Off Fall Time	t_f			5.6		ns
Drain-Source Diode Characteristics						
Drain-Source Diode Forward Voltage	V_{SD}	$V_{GS}=0V, I_S=-1.9A$			-1.3	V

Notes: Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.



5.1Typical Characteristic

Figure 1: Output Characteristics	Figure 2: Transfer Characteristics
Figure 3: Breakdown Voltage Variation withTemperature	Figure 4: On-Resistance Variation with Temperature
Figure 5: Gate Threshold Variation with Temperature	Figure 6: Gate Charge



5.2Typical Characteristic






Figure 9: Switching Test Circuit and Switching Waveforms



6.SOP-8 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	A3	b	c	D	E	E1	e	h	L
Min	-	0.05	1.30	0.60	0.39	0.20	4.80	5.80	3.80	1.24	0.30	0.50
Max	1.75	0.20	1.50	0.70	0.47	0.24	5.00	6.20	4.00	1.30	0.50	0.80

Symbol	L1	θ
Min	1.00	0°
Max	1.10	8°



7.Ordering Information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW APM4953	SOP-8	3000	Tape and reel



8.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.