

1.Description

The SOP-8 has been modified through a customized leadframe for enhanced thermal characteristics and multiple-die capability making it ideal in a variety of power applications. With these improvements, multiple devices can be used in an application with dramatically reduced board space. The package is designed for vapor phase, infra red, or wave soldering techniques. Power dissipation of greater than 0.8W is possible in a typical PCB mount application.


2.Features

- $V_{DS(V)} = -55V$
- $I_D = -3.4A$
- $R_{DS(ON)} < 105m\Omega (V_{GS} = -10)$
- $R_{DS(ON)} < 170m\Omega (V_{GS} = -4.5V)$
- Generation V Technology
- Ultra Low On-Resistance
- Surface Mount
- Dynamic dv/dt Rating
- Fast Switching
- Lead-Free

3.Pinning Information

Pin	Symbol	Description
2,4	G	GATE
1,3	S	SOURCE
5,6,7,8	D	DRAIN

SOP-8





4. Absolute Maximum Ratings $T_A=25^{\circ}\text{C}$ unless otherwise noted

Parameter	Symbol	Rating	Units
Drain-Source Voltage	V_{DS}	-55	V
Continuous Drain Current, $V_{GS}=10\text{V}$	I_D	-3.4	A
Continuous Drain Current, $V_{GS}=10\text{V}$		-2.7	A
Pulsed Drain Current ①	I_{DM}	-27	A
Power Dissipation	P_D	2	W
Power Dissipation		1.3	W
Linear Derating Factor		0.016	W/ $^{\circ}\text{C}$
Gate-to-Source Voltage	V_{GS}	± 20	V
Gate-to-Source Voltage Single Pulse $t_p < 10\mu\text{s}$	V_{GSM}	± 30	V
Single Pulse Avalanche Energy ②	E_{AS}	114	mJ
Peak Diode Recovery dv/dt ③	dv/dt	5	V/ns
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	$^{\circ}\text{C}$

5. Thermal Resistance Rating

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ⑤	$R_{\theta JA}$		62.5	$^{\circ}\text{C/W}$



6. Electrical Characteristics $T_J=25^\circ\text{C}$

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D=250\mu\text{A}$, $V_{GS}=0\text{V}$	-55			V
Breakdown Voltage Temp. Coefficient	$\Delta V_{(BR)DSS}/T_J$	$I_D=1\text{mA}$, Reference to 25°C		-0.054		V/ $^\circ\text{C}$
Static Drain-to-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=-10\text{V}$, $I_D=-3.4\text{A}$ ④		95	105	m Ω
		$V_{GS}=-4.5\text{V}$, $I_D=-2.7\text{A}$ ④		150	170	
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$, $I_D=-250\mu\text{A}$	-1			V
Forward Transconductance	g_{FS}	$V_{DS}=-10\text{V}$, $I_D=-3.1\text{A}$	3.3			S
Drain-to-Source Leakage Current	I_{DSS}	$V_{DS}=-55\text{V}$, $V_{GS}=0\text{V}$			-2	μA
		$V_{DS}=-55\text{V}$, $V_{GS}=0\text{V}$, $T_J=55^\circ\text{C}$			-25	
Gate-to-Source Forward Leakage	I_{GSS}	$V_{GS}=-20\text{V}$			-100	nA
Gate-to-Source Reverse Leakage		$V_{GS}=20\text{V}$			100	
Total Gate Charge	Q_g	$I_D=-4.5\text{A}$		26	38	nC
Gate-to-Source Charge	Q_{gs}	$V_{DS}=-44\text{V}$, $V_{GS}=-10\text{V}$		3	4.5	
Gate-to-Drain ("Miller") Charge	Q_{gd}	See Fig. 10 ④		8.4	13	
Turn-On Delay Time	$t_{D(on)}$	$V_{DD}=-28\text{V}$		14	22	ns
Rise Time	t_r	$I_D=-1\text{A}$		10	15	ns
Turn-Off Delay Time	$t_{D(off)}$	$R_G=6\Omega$		43	64	ns
Fall Time	t_f	$R_D=16\Omega$ ④		22	32	ns
Input Capacitance	C_{iss}	$V_{GS}=0\text{V}$		690		pF
Output Capacitance	C_{oss}	$V_{DS}=-25\text{V}$		210		pF
Reverse Transfer Capacitance	C_{rss}	$f=1.0\text{MHz}$, See Fig. 9		86		pF




Source-Drain Ratings and Characteristics						
Continuous Source Current (Body Diode)	I_S	MOSFET symbol showing the integral reverse p-n junction diode.			-2	A
Pulsed Source Current (Body Diode) ①	I_{SM}				-27	
Diode Forward Voltage	V_{SD}		$T_J=25^{\circ}\text{C}$, $I_S=-1.7\text{A}$, $V_{GS}=0\text{V}$ ③		-1.2	V
Reverse Recovery Time	t_{rr}	$T_J=25^{\circ}\text{C}$, $I_F=-1.7\text{A}$		54	80	ns
Reverse Recovery Charge	Q_{rr}	$dI/dt=100\text{A}/\mu\text{s}$ ③		85	130	nC

Notes:

- ① Repetitive rating; pulse width limited by max.junction temperature.(See fig.11)
- ② Starting $T_J=25^{\circ}\text{C}$, $L=20\text{mH}$, $R_G=25\Omega$, $I_{AS}=-3.4\text{A}$.(See Figure 8)
- ③ $I_{SD}\leq -3.4\text{A}$, $dI/dt\leq -150\text{A}/\mu\text{s}$, $V_{DD}\leq V_{(BR)DSS}$, $T_J\leq 150^{\circ}\text{C}$.
- ④ Pulse width $\leq 300\mu\text{s}$; duty cycle $\leq 2\%$.
- ⑤ When mounted on 1 inch square copper board, $t<10$ sec.




7.1Typical Characteristics





7.2Typical Characterisitics





7.3 Typical Characteristics




Fig 9. Typical capacitance Vs.Drain-to-Source Voltage




Fig 10. Typical Gate Charge Vs.Gate-to-Source Voltage





Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



8.SOP-8 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	A3	b	c	D	E	E1	e	h	L
Min	-	0.05	1.30	0.60	0.39	0.20	4.80	5.80	3.80	1.24	0.30	0.50
Max	1.75	0.20	1.50	0.70	0.47	0.24	5.00	6.20	4.00	1.30	0.50	0.80

Symbol	L1	θ
Min	1.00	0°
Max	1.10	8°



9.Ordering information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW IRF7342TR	SOP-8	3000	Tape and reel



10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.