

## 1.Features

---

- 100Watts peak pulse power ( $t_p=8/20\mu s$ )
- Bidirectional configurations
- Solid-state silicon-avalanche technology
- Low clamping voltage
- Low leakage current

## 2.Applications

---

- Microprocessor based equipment
- Personal Digital Assistants (PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Pagers Peripherals


## 3.Mechanical Data

---

- SOD-523 package
- Molding compound flammability rating: UL 94V-0
- Packaging: Tape and Reel
- RoHS Compliant

## 4.Pinning information

---



**SOD-523**



## 5. Absolute Maximum Ratings


Parameter	Symbol	Value	Units
Peak Pulse Power ( $t_p=8/20\mu s$ )	$P_{PP}$	100	Watts
Peak Pulse Current ( $t_p=8/20\mu s$ )(note1)	$I_{PP}$	10	A
ESD per IEC 61000-4-2(Air)	$V_{ESD}$	25	kV
ESD per IEC 61000-4-2(Contact)		25	kV
Lead Soldering Temperature	$T_L$	260(10seconds)	°C
Junction Temperature	$T_J$	-55 to 150	°C
Storage Temperature	$T_{STG}$	-55 to 150	°C



## 6. Electrical Characteristic (T<sub>A</sub>=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Reverse Stand-Off Voltage	V <sub>RWM</sub>				3.3	V
Reverse Breakdown Voltage	V <sub>BR</sub>	I <sub>T</sub> =1mA	3.8		5	V
Reverse Leakage Current	I <sub>R</sub>	V <sub>RWM</sub> =3.3V, T=25°C			1	uA
Clamping Voltage	V <sub>C</sub>	I <sub>PP</sub> =10A, t <sub>p</sub> =8/20μs			10	V
Junction capacitance	C <sub>J</sub>	V <sub>R</sub> =0V, f=1MHz		13	15	pF

## 7. Electrical Parameters (T<sub>A</sub>=25°C unless otherwise noted)




Symbol	Parameter
I <sub>PP</sub>	Maximum Reverse Peak Pulse Current
V <sub>C</sub>	Clamping Voltage @ I <sub>PP</sub>
V <sub>RWM</sub>	Working Peak Reverse Voltage
I <sub>R</sub>	Maximum Reverse Leakage Current @ V <sub>RWM</sub>
V <sub>BR</sub>	Breakdown Voltage @ I <sub>T</sub>
I <sub>T</sub>	Test Current

Notes: 8/20μs pulse waveform.




## 8. Typical characteristic





## 9.SOD-523 Package Outline Dimensions




**DIMENSIONS (mm are the original dimensions)**

Symbol	A	b <sub>p</sub>	C	D	E	H <sub>E</sub>	θ
Min	0.58	0.3	0.100	1.15	0.75	1.5	5°
Max	0.68	0.4	0.135	1.25	0.85	1.7	



## 10. Ordering information



Order Code	Package	Base QTY	Delivery Mode
UMW BSD5C031V	SOD-523	3000	Tape and reel



## **11.Disclaimer**

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.