

1.Description

The 72XX series is a positive voltage regulator circuit developed using CMOS technology, offering low dropout voltage, high-precision output voltage, and ultra-low current consumption. Due to its built-in low on-resistance transistor, it achieves a low output voltage dropout while also offering high input voltage tolerance, with a maximum operating voltage of 12V, making it suitable for applications requiring high voltage resistance.

3.Applications


- Regulated Power Supply for Battery-Powered Equipment Communication Equipment
- Regulated Power Supply for Home Appliances and Toys Phones

2.Features

- High Output Voltage Accuracy: $\pm 3\%$
- Ultra-low power consumption: 3uA typical
- Low output voltage temperature drift: 50ppm typical
- High input voltage: up to 12V to maintain output voltage regulation
- Package: TO-92, SOT89-3, SOT23-3

4.Pinning Information

Pin number		Symbol	Description
TO-92/SOT-89	SOT-23		
1	1	GND	Chip Ground
2	3	VIN	Start Input
3	2	VOUT	Chip Output






5.Model Selection


Name	Model	Maximum input voltage (V)	Output voltage (V)	Tolerance	Package
72XX	7218	12	1.8	±3%	TO92 SOT89-3 SOT23-3
	7225	12	2.5	±3%	
	7227	12	2.7	±3%	
	7230	12	3	±3%	
	7233	12	3.3	±3%	
	7236	12	3.6	±3%	
	7250	12	5	±3%	

6.Block Diagram





7.Application Circuit



8.Absolute Maximum Ratings

Project	Symbol	Description	Limit Value	Unit
Voltage	V_{IN}	Maximum Input Voltage	15	V
Power Consumption	P_D	Power Consumption	400	mW
Temperature	T_w	Operating Temperature	-25 to 70	°C
	T_c	Storage Temperature	-50 to 125	°C
	T_h	Soldering Temperature	260	°C,10s



9.1 Electrical Characteristics (7218, T_{OPT}=25°C)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Output Voltage	V _{OUT}	V _{IN} =2.8V, I _{OUT} =40mA	1.746	1.8	1.854	V
Output Current	I _{OUT}	V _{IN} =2.8V, V _{OUT} ≥1.62V	150			mA
Load Regulation	ΔV _{OUT}	V _{IN} =2.8V, 1mA≤I _{OUT} ≤60mA		45	90	mV
Dropout Voltage	V _{DIF}	I _{OUT} =40mA		170		mV
Quiescent Current	I _{SS}	V _{IN} =2.8V, no load		2	3	μA
Line Regulation	ΔV _{OUT} /(ΔV _{IN} *V _{OUT})	2.8V≤V _{IN} ≤12V, I _{OUT} =40mA		0.2	0.3	%/V
Input Voltage	V _{IN}				12	V
Temperature Coefficient	ΔV _{OUT} /T _A	V _{IN} =2.8V, I _{OUT} =40mA, 0°C≤T _A ≤85°C		±0.7		mV/°C

9.2 Electrical Characteristics (7225, T_{OPT}=25°C)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Output Voltage	V _{OUT}	V _{IN} =3.5V, I _{OUT} =40mA	2.425	2.5	2.575	V
Output Current	I _{OUT}	V _{IN} =3.5V, V _{OUT} ≥2.25V	180			mA
Load Regulation	ΔV _{OUT}	V _{IN} =3.5V, 1mA≤I _{OUT} ≤60mA		45	90	mV
Dropout Voltage	V _{DIF}	I _{OUT} =40mA		110		mV
Quiescent Current	I _{SS}	V _{IN} =3.5V, no load		2	3	μA
Line Regulation	ΔV _{OUT} /(ΔV _{IN} *V _{OUT})	3.5V≤V _{IN} ≤12V, I _{OUT} =40mA		0.2	0.3	%/V
Input Voltage	V _{IN}				12	V
Temperature Coefficient	ΔV _{OUT} /T _A	V _{IN} =3.5V, I _{OUT} =40mA, 0°C≤T _A ≤85°C		±0.7		mV/°C



9.3 Electrical Characteristics (7227, T_{OPT}=25°C)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Output Voltage	V _{OUT}	V _{IN} =3.7V, I _{OUT} =40mA	2.619	2.7	2.781	V
Output Current	I _{OUT}	V _{IN} =3.7V, V _{OUT} ≥2.43V	200			mA
Load Regulation	ΔV _{OUT}	V _{IN} =3.7V, 1mA≤I _{OUT} ≤60mA		45	90	mV
Dropout Voltage	V _{DIF}	I _{OUT} =40mA		100		mV
Quiescent Current	I _{SS}	V _{IN} =3.7V, no load		2	3	μA
Line Regulation	ΔV _{OUT} /(ΔV _{IN} *V _{OUT})	3.7V≤V _{IN} ≤12V, I _{OUT} =40mA		0.2	0.3	%/V
Input Voltage	V _{IN}				12	V
Temperature Coefficient	ΔV _{OUT} /T _A	V _{IN} =3.7V, I _{OUT} =40mA, 0°C≤T _A ≤85°C		±0.7		mV/°C

9.4 Electrical Characteristics (7230, T_{OPT}=25°C)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Output Voltage	V _{OUT}	V _{IN} =4V, I _{OUT} =40mA	2.91	3	3.09	V
Output Current	I _{OUT}	V _{IN} =4V, V _{OUT} ≥2.7V	250			mA
Load Regulation	ΔV _{OUT}	V _{IN} =4V, 1mA≤I _{OUT} ≤60mA		45	90	mV
Dropout Voltage	V _{DIF}	I _{OUT} =40mA		95		mV
Quiescent Current	I _{SS}	V _{IN} =4V, no load		2	3	μA
Line Regulation	ΔV _{OUT} /(ΔV _{IN} *V _{OUT})	4V≤V _{IN} ≤12V, I _{OUT} =40mA		0.2	0.3	%/V
Input Voltage	V _{IN}				12	V
Temperature Coefficient	ΔV _{OUT} /T _A	V _{IN} =4V, I _{OUT} =40mA, 0°C≤T _A ≤85°C		±0.7		mV/°C



9.5 Electrical Characteristics (7233, T_{OPT}=25°C)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Output Voltage	V _{OUT}	V _{IN} =4.3V, I _{OUT} =40mA	3.201	3.3	3.399	V
Output Current	I _{OUT}	V _{IN} =4.3V, V _{OUT} ≥2.97V	250			mA
Load Regulation	ΔV _{OUT}	V _{IN} =4.3V, 1mA≤I _{OUT} ≤60mA		45	90	mV
Dropout Voltage	V _{DIF}	I _{OUT} =40mA		90		mV
Quiescent Current	I _{SS}	V _{IN} =4.3V, no load		2	3	μA
Line Regulation	ΔV _{OUT} /(ΔV _{IN} *V _{OUT})	4.3V≤V _{IN} ≤12V, I _{OUT} =40mA		0.2	0.3	%/V
Input Voltage	V _{IN}				12	V
Temperature Coefficient	ΔV _{OUT} /T _A	V _{IN} =4.3V, I _{OUT} =40mA, 0°C≤T _A ≤85°C		±0.7		mV/°C

9.6 Electrical Characteristics (7236, T_{OPT}=25°C)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Output Voltage	V _{OUT}	V _{IN} =4.5V, I _{OUT} =40mA	3.492	3.6	3.708	V
Output Current	I _{OUT}	V _{IN} =4.5V, V _{OUT} ≥3.15V	250			mA
Load Regulation	ΔV _{OUT}	V _{IN} =4.5V, 1mA≤I _{OUT} ≤60mA		45	90	mV
Dropout Voltage	V _{DIF}	I _{OUT} =40mA		80		mV
Quiescent Current	I _{SS}	V _{IN} =4.5V, no load		2	3	μA
Line Regulation	ΔV _{OUT} /(ΔV _{IN} *V _{OUT})	4.5V≤V _{IN} ≤12V, I _{OUT} =40mA		0.2	0.3	%/V
Input Voltage	V _{IN}				12	V
Temperature Coefficient	ΔV _{OUT} /T _A	V _{IN} =4.5V, I _{OUT} =40mA, 0°C≤T _A ≤85°C		±0.7		mV/°C




9.7 Electrical Characteristics (7250, T_{OPT}=25°C)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Output Voltage	V _{OUT}	V _{IN} =6V, I _{OUT} =40mA	4.85	5	5.15	V
Output Current	I _{OUT}	V _{IN} =6V, V _{OUT} ≥4.5V	250			mA
Load Regulation	ΔV _{OUT}	V _{IN} =6V, 1mA≤I _{OUT} ≤60mA		45	90	mV
Dropout Voltage	V _{DIF}	I _{OUT} =40mA		60		mV
Quiescent Current	I _{SS}	V _{IN} =6V, no load		2	3	μA
Line Regulation	ΔV _{OUT} /(ΔV _{IN} *V _{OUT})	6V≤V _{IN} ≤12V, I _{OUT} =40mA		0.2	0.3	%/V
Input Voltage	V _{IN}				12	V
Temperature Coefficient	ΔV _{OUT} /T _A	V _{IN} =6V, I _{OUT} =40mA, 0°C≤T _A ≤85°C		±0.7		mV/°C



10.1 TO-92 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	B	C	D	E	E1	F	L
Min	1.10	3.50	4.50	4.40	0.35	1.27	13.50	0.35
Max	1.30	3.90	4.90	4.90	0.45	TYP	14.50	0.40



10.2 SOT-89 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	B	C	D	E	F	H	H1	L	L1	L2
Min	1.450	2.950	0.330	4.450	2.450	1.650	0.450	0.370	0.900	4.100	4.100
Max	1.550	3.050	0.430	4.550	2.550	1.750	0.580	0.480	1.000	4.300	4.350



10.3 SOT-23 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	b	c	D	E	E1	e	e1	L	L1
Min	1.050	0.000	1.050	0.300	0.100	2.820	1.500	2.650	0.950	1.800	0.300	0.200
Max	1.250	0.100	1.150	0.500	0.200	3.020	1.700	2.950	BSC	2.000	0.600	

Symbol	θ
Min	0°
Max	8°



11.Ordering Information

Order Code	Package	Base QTY	Delivery Mode
UMW HT7233-1	SOT-89	1000	Tape and reel



12.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.