


1.Features

- $V_{DS(V)}=30V$
- $ID=78A$
- $R_{DS(ON)}<4.8m\Omega(V_{GS}=10V)$
- $R_{DS(ON)}<6.8m\Omega(V_{GS}=4.5V)$
- Very Low $R_{DS(ON)}$ at 4.5V V_{GS}
- Ultra-Low Gate Impedance
- Lead-Free
- Fully Characterized Avalanche Voltage and Current

2.Pinning information

Pin	Symbol	Description
1	G	GATE
2	D	DRAIN
3	S	SOURCE

TO-220



3.Absolute Maximum Ratings

Parameter		Symbol	Rating	Units
Drain-to-Source Voltage		V_{DS}	30	V
Gate-to-Source Voltage		V_{GS}	± 20	V
Continuous Drain Current, $V_{GS}=10V$ (Silicon Limited)	$T_C=25^{\circ}C$	I_D	92 ④	A
Continuous Drain Current, $V_{GS}=10V$ (Silicon Limited)	$T_C=100^{\circ}C$		65	A
Continuous Drain Current, $V_{GS}=10V$ (Package Limited)	$T_C=25^{\circ}C$		78	A
Pulsed Drain Current ①		I_{DM}	370	A
Maximum Power Dissipation ⑥	$T_C=25^{\circ}C$	P_D	75	W
Maximum Power Dissipation ⑥	$T_C=100^{\circ}C$		38	W
Linear Derating Factor			0.5	W/ $^{\circ}C$
Storage Temperature Range		T_J, T_{STG}	-55 to 175	$^{\circ}C$
Soldering Temperature, for 10 seconds (1.6mm from case)			300	$^{\circ}C$
Mounting torque, 6-32 or M3 screw			10lbin (1.1Nm)	



4.Thermal resistance rating

Parameter	Symbol	Typ	Max	Units
Junction-to-Case ⑥	$R_{\theta JC}$		2	°C/W
Case-to-Sink, Flat Greased Surface	$R_{\theta CS}$	0.5		°C/W
Junction-to-Ambient ⑤	$R_{\theta JA}$		62	°C/W



5. Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)


Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	$I_D=250\mu\text{A}$, $V_{GS}=0\text{V}$	30			V
Breakdown Voltage Temp. Coefficient	$\Delta BV_{DSS}/\Delta T_J$	$I_D=1\text{mA}$, Reference to 25°C		21		mV/ $^\circ\text{C}$
Static Drain-to-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=10\text{V}$, $I_D=40\text{A}$ ③		3.8	4.8	m Ω
		$V_{GS}=4.5\text{V}$, $I_D=32\text{A}$ ③		5.5	6.8	
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$, $I_D=50\mu\text{A}$	1.35	1.8	2.35	V
Gate Threshold Voltage Coefficient	$\Delta V_{GS(th)}/\Delta T_J$			-7.1		mV/ $^\circ\text{C}$
Drain-to-Source Leakage Current	I_{DSS}	$V_{DS}=24\text{V}$, $V_{GS}=0\text{V}$			1	μA
		$V_{DS}=24\text{V}$, $V_{GS}=0\text{V}$, $T_J=125^\circ\text{C}$			150	μA
Gate-to-Source Forward Leakage	I_{GSS}	$V_{GS}=20\text{V}$			100	nA
Gate-to-Source Reverse Leakage		$V_{GS}=-20\text{V}$			-100	nA
Forward Transconductance	g_{FS}	$V_{DS}=15\text{V}$, $I_D=32\text{A}$	196			S
Total Gate Charge	Q_g	$V_{DS}=15\text{V}$, $V_{GS}=4.5\text{V}$ $I_D=32\text{A}$		15	23	nC
Pre-Vth Gate-to-Source Charge	Q_{gs1}			3.6		nC
Post-Vth Gate-to-Source Charge	Q_{gs2}			2.2		nC
Gate-to-Drain Charge	Q_{gd}			5.9		nC
Gate Charge Overdrive	Q_{gdor}			3.9		nC
Switch Charge ($Q_{gs2} + Q_{gd}$)	Q_{sw}			8.1		nC
Output Charge	Q_{oss}	$V_{DS}=16\text{V}$, $V_{GS}=0\text{V}$		11		nC
Gate Resistance	R_g			2	3.5	Ω
Turn-On Delay Time	$t_{D(on)}$	$V_{DD}=15\text{V}$, $V_{GS}=4.5\text{V}$ ③ $I_D=32\text{A}$, $R_G=1.8\Omega$		14		ns
Rise Time	t_r			96		ns
Turn-Off Delay Time	$t_{D(off)}$			16		ns
Fall Time	t_f			34		ns
Input Capacitance	C_{iss}	$V_{GS}=0$, $V_{DS}=15\text{V}$, $f=1.0\text{MHz}$		2139		pF
Output Capacitance	C_{oss}			464		pF
Reverse Transfer Capacitance	C_{rss}			199		pF



Avalanche Characteristics						
Single Pulse Avalanche Energy ②	E_{AS}				114	mJ
Avalanche Current ①	I_{AR}				32	A
Repetitive Avalanche Energy ①	E_{AR}				7.5	mJ
Diode Characteristics						
Continuous Source Current (Body Diode)	I_S	MOSFET symbol showing the integral reverse p-n junction diode.			92④	A
Pulsed Source Current (Body Diode) ①	I_{SM}				370	A
Diode Forward Voltage	V_{SD}	$T_J=25^{\circ}\text{C}, I_S=32\text{A}, V_{GS}=0\text{V}$ ③			1	V
Reverse Recovery Time	t_{rr}	$T_J=25^{\circ}\text{C}, I_F=32\text{A}, V_{DD}=15\text{V}$		23	35	ns
Reverse Recovery Charge	Q_{rr}	$dI/dt=200\text{A}/\mu\text{s}$ ③		39	59	nC
Forward Turn-On Time	t_{on}	Intrinsic turn-on time is negligible (turn-on is dominated by L_S+L_D)				




6.1 Typical Characteristics






6.2Typical Characteristics





6.3 Typical Characteristics





6.4 Typical Characteristics




Figure 13: Maximum Effective Transient Thermal Impedance, Junction-to-Case




Figure 14a: Unclamped Inductive Test Circuit




Figure 14b: Switching Time Test Circuit




Figure 15a: Unclamped Inductive Waveforms





Figure 16b: Switching Time Waveforms



7.TO-220 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	A3	B	B1	C	C1	D	E	F	G
Min	9.7	8.44	1.05	4.8	15.4	12.9	4.28	1.1	0.6	3.4	2.65	5.2
Max	10.3	8.84	1.25	5.2	16.2	13.5	4.68	1.5	1.0	3.8	3.25	5.8

Symbol	H	K	L	L1	M	N	P	Q	T	DIA
Min	0.4	2.9	12.8	2.7	1.15	2.49	2.1	8.7	W:0.35	⌀1.5
Max	0.6	3.3	13.6	3.3	1.35	2.59	2.7	9.3		(deep 0.2)



8.Ordering information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW IRLB8748PBF	TO-220	1000	Tube and box



9.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.