

1.Description

The UMW TLP621-1,2 and -4 consist of a photo-transistor optically coupled to a gallium arsenide infrared emitting diode. The TLP621-2 offers two isolated channels in an eight lead plastic DIP, which the TLP621-4 provides four isolated channels in a sixteen plastic DIP.


2.Features

- Collector-Emitter Voltage: 55V (min)
- Current Transfer Ratio: 50% (min)
- Rank GB: 100% (min)
- UL-Approved: UL1577, File No.E547318


3.Applications

- Programmable Controller
- AC/DC-Input Module
- Solid State Relay


4.Pinning information



1: Anode
2: Cathode
3: Emitter
4: Collector



1,3: Anode
2,4: Cathode
5,7: Emitter
6,8: Collector



1,3,5,7: Anode
2,4,6,8: Cathode
9,11,13,15: Emitter
10,12,14,16: Collector



5. Absolute Maximum Ratings

Parameter		Symbol	Ratings		Unit
			UMW TLP621-1	UMW TLP621-2,-4	
LED	Forward Current	I_F	60	50	mA
	Forward Current Derating	$\Delta I_F/^\circ\text{C}$	$-0.7(T_a > 39^\circ\text{C})$	$-0.5(T_a = 25^\circ\text{C})$	mA/ $^\circ\text{C}$
	Pulse Forward Current	I_{FP}	1(100 μs pulse, 100pps)		A
	Power Dissipation	P_D	100	70	mW
	Power Dissipation Derating	$\Delta P_D/^\circ\text{C}$	-1	-0.7	mW/ $^\circ\text{C}$
	Reverse Voltage	V_R	5		V
	Junction Temperature	T_J	125		$^\circ\text{C}$
DETECTOR	Collector-Emitter Voltage	V_{CEO}	55		V
	Emitter-Collector Voltage	V_{ECO}	7		V
	Collector Current	I_C	50		mA
	Collector Power Dissipation (1 Circuit)	P_C	150	100	mW
	Collector Power Dissipation Derating (1 Circuit, $T_a \geq 25^\circ\text{C}$)	$\Delta P_D/^\circ\text{C}$	-1.5	-1	mW/ $^\circ\text{C}$
	Junction Temperature	T_J	125		$^\circ\text{C}$
Storage Temperature Range		T_{STG}	-55 to 125		$^\circ\text{C}$
Operating Temperature Range		T_{OPR}	-55 to 100		$^\circ\text{C}$
Lead Soldering Temperature		T_{SOL}	260(10s)		$^\circ\text{C}$
Total Package Power Dissipation		P_T	250	150	mW
Total Package Power Dissipation Derating ($T_a \geq 25^\circ\text{C}$)		$\Delta P_T/^\circ\text{C}$	-2.5	-1.5	mW/ $^\circ\text{C}$
Isolation Voltage (Note 1)		BV_S	5000(AC, 1min. R.H. $\leq 60\%$)		Vrms

(Note 1):

Device considered a two terminal device : LED side pins shorted together and DETECTOR side pins shorted together.



6.Recommended Operating Conditions

Parameter	Symbol	Min	Typ	Max	Units
Supply Voltage	V_{CC}		5	24	V
Forward Current	I_F		16	20	mA
Collector Current	I_C		1	10	mA
Operating Temperature	T_{OPR}	-25		85	°C

7.Current Transfer Ratio

Type	Classification (Note 1)	Current Transfer Ratio (%) (I_C/I_F)		Marking of Classification
		$I_F=5mA, V_{CE}=5V, T_a=25^{\circ}C$		
		Min	Max	
UMW TLP621-1	(None)	50	600	BLANK, Y, Y, G, G, B, B, GB
	Rank Y	50	150	Y, Y
	Rank GR	100	300	G, G
	Rank BL	200	600	B, B
	Rank GB	100	600	G, G, B, B, GB
UMW TLP621-2	(None)	50	600	BLANK, GR, BL, GB
UMW TLP621-4	Rank GB	100	600	GR, BL, GB



8. Electrical Characteristics

Parameter	Symbol	Conditions	Min	Typ	Max	Units
LED						
Forward Voltage	V_F	$I_F=10\text{mA}$	1	1.15	1.3	V
Reverse Current	I_R	$V_R=5\text{V}$			10	μA
Capacitance	C_T	$V=0, f=1\text{MHz}$		30		pF
Detector						
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=0.5\text{mA}$	55			V
Emitter-Collector Breakdown Voltage	$V_{(BR)ECO}$	$I_E=0.1\text{mA}$	7			V
Collector Dark Current	I_{CEO}	$V_{CE}=24\text{V}$		10	100	nA
		$V_{CE}=24\text{V}, T_a=85^\circ\text{C}$		2	50	μA
Capacitance (Collector to Emitter)	C_{CE}	$V=0, f=1\text{MHz}$		10		pF

9. Coupling Electrical Characteristics ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Current Transfer Ratio	I_C/I_F	$I_F=5\text{mA}, V_{CE}=5\text{V}$	50		600	%
		$I_F=5\text{mA}, V_{CE}=5\text{V}, \text{Rank GB}$	100		600	%
Saturated CTR	$I_C/I_{F(SAT)}$	$I_F=1\text{mA}, V_{CE}=0.4\text{V}$		60		%
		$I_F=1\text{mA}, V_{CE}=0.4\text{V}, \text{Rank GB}$	30			%
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=2.4\text{mA}, I_F=8\text{mA}$			0.4	V
		$I_C=0.2\text{mA}, I_F=1\text{mA}$		0.2		V
		$I_C=0.2\text{mA}, I_F=1\text{mA}, \text{Rank GB}$			0.4	V



10. Isolation Characteristics (Ta=25°C)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Capacitor (Input To Output)	C_s	$V_s=0, f=1\text{MHz}$		0.8		pF
Isolation Resistance	R_s	$V_s=500\text{V}$	1×10^{12}	10^{14}		Ω
Isolation Voltage	BV_s	AC, 1 minute	5000			Vrms
		AC, 1 second, in oil		10000		Vrms
		DC, 1 minute, in oil		10000		Vdc

11. Switch Characteristics (Ta=25°C)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Rise Time	t_r	$V_{CC}=10\text{V}, I_C=2\text{mA}$ $R_L=100\Omega$		2		μs
Fall Time	t_f			3		μs
Turn-on Time	t_{on}			3		μs
Turn-off Time	t_{off}			3		μs
Turn-on Time	t_{ON}	$R_L=1.9\text{k}\Omega$ (Fig.1) $V_{CC}=5\text{V}, I_F=16\text{mA}$		2		μs
Storage Time	t_s			15		μs
Turn-off Time	t_{OFF}			25		μs

12. Test circuit





Fig.1 Switching Time Test Circuit









13.1Typical Characteristic






13.2 Typical Characteristic

Figure 7: $I_F - V_F$ Figure 8: $\Delta V_F / \Delta T_a - I_F$ Figure 9: $I_{FP} - V_{FP}$ Figure 10: $I_{CEO} - T_A$ Figure 11: $I_C - V_{CE}$ Figure 12: $I_C - V_{CE}$




13.3Typical Characteristic





14.1 DIP-4 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	B	B1	b	b1	c	D	D1	d	E	E1	e
Min	4.60	6.40	6.35	1.64	1.60	6.45	8.86	3.43	4.55	3.48	3.05	2.55
Max			6.45			6.55					3.55	3.05

Symbol	F	H	h
Min	2.29	0.50	0.50
Max	2.79		



14.2 SOP-4 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	b	C	D	D1	E	E1	E2	e	H1
Min	6.15	4.33	1.1	3.4	0.05	2.29	7.37	0.75	9.85	0.26
Max	6.65	4.83	1.3	3.9	0.6	2.79	7.87	1.25	10.45	



15.Ordering information



yy: Year Code
ww: Week Code

Order Code	Marking	Package	Base QTY	Delivery Mode
UMW TLP621GB-1	621GB	DIP-4	5000	Tube and box
UMW TLP621GB-1S	621GB	SOP-4	2000	Tape and reel



16.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.