

FEATURES

- * For surface mount application
- * Built-in strain relief
- * Excellent clamping capability
- * Low profile package
- * High temperature soldering guaranteed:
260°C / 10 seconds at terminals


MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Metallurgically bonded construction
- * Polarity: Color band denotes cathode end
- * Mounting position: Any

VOLTAGE RANGE

3.3 to 300 Volts

1000mW



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating 25°C ambient temperature unless otherwise specified.
Single phase half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

MAXIMUM RATINGS (T_A = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	VALUE	UNIT
Maximum steady state power dissipation at T _L = 75 °C (fig. 1) ⁽¹⁾	P _{tot}	1000	mW
Maximum steady state power dissipation at T _A = 25 °C (fig. 1) ⁽²⁾	P _{tot}	500	mW
Maximum instantaneous forward voltage at 200 mA for all types ⁽³⁾	V _F	1.2	V
Operating junction and storage temperature range	T _J , T _{STG}	-65 to +150	°C
Typical thermal resistance, junction to lead	R _{θJL} ⁽¹⁾	50	°C/W
Typical thermal resistance, junction to ambient	R _{θJA} ⁽²⁾	250	°C/W

Notes

- ⁽¹⁾ Mounted on PCB with 5.0 mm x 5.0 mm copper pads attached to each terminal
- ⁽²⁾ Mounted on minimum recommended pad layout
- ⁽³⁾ Pulse test: 300 μs pulse width, 1 % duty cycle

1SMAF4728A THRU 1SMAF4777A




Fig. 1 - Steady State Power Derating




Fig. 3 - Typical Zener Voltage




Fig. 2 - Typical Zener Voltage




Fig. 4 - Typical Temperature Coefficients




Fig. 5 - Typical Temperature Coefficients





Fig. 6 - Typical Zener Impedance

1SMAF4728A THRU 1SMAF4777A

ELECTRICAL CHARACTERISTICS

SYMBOL	PARAMETER
V_Z	Reverse Zener voltage at I_{ZT}
I_{ZT}	Reverse current
Z_{ZT}	Maximum Zener impedance at I_{ZT}
I_{ZK}	Reverse current
Z_{ZK}	Maximum Zener impedance at I_{ZK}
I_R	Reverse leakage current at V_R
V_R	Reverse voltage
I_F	Forward current
V_F	Forward voltage at I_F
I_{ZM}	Maximum DC Zener current



Zener Voltage Regulator

Characteristics at $T_a = 25^\circ\text{C}$

Type	Marking	Zener Voltage Range ⁽¹⁾					Dynamic Impedance	Reverse Current		Admissible Zener Current
		V _{ZT} (at I _{ZT})			I _{ZT}	Z _{ZT} (at I _{ZT})	I _R	at V _R		
		Min (V)	Nom (V)	Max (V)	(mA)	Max (Ω)	Max (μA)	(V)	I _{ZM} (mA)	
1SMAF4728A	728A	3.10	3.3	3.50	75	10	100	1	285	
1SMAF4729A	729A	3.40	3.6	3.80	69	10	100	1	263	
1SMAF4730A	730A	3.70	3.9	4.10	64	9.0	50	1	243	
1SMAF4731A	731A	4.06	4.3	4.56	58	9.0	25	1	219	
1SMAF4732A	732A	4.50	4.7	4.93	53	8.0	10	1	203	
1SMAF4733A	733A	4.84	5.1	5.36	49	7.0	10	1	186	
1SMAF4734A	734A	5.32	5.6	5.92	45	5.0	10	2	170	
1SMAF4735A	735A	5.86	6.2	6.51	41	2.0	10	3	154	
1SMAF4736A	736A	6.46	6.8	7.18	37	3.5	10	4	140	
1SMAF4737A	737A	7.12	7.5	7.88	34	4.0	10	5	127	
1SMAF4738A	738A	7.79	8.2	8.67	31	4.5	10	6	116	
1SMAF4739A	739A	8.60	9.1	9.59	28	5.0	10	7	104	
1SMAF4740A	740A	9.50	10	10.5	25	7.0	10	7	95	
1SMAF4741A	741A	10.4	11	11.6	23	8.0	5	8	86	
1SMAF4742A	742A	11.4	12	12.6	21	9.0	5	9	79	
1SMAF4743A	743A	12.4	13	14.1	19	10	5	10	71	
1SMAF4744A	744A	13.8	15	15.8	17	14	5	11	63	
1SMAF4745A	745A	15.2	16	17.1	16	16	5	12	58	
1SMAF4746A	746A	16.8	18	19.2	14	20	5	13	52	
1SMAF4747A	747A	19.0	20	21.2	13	22	5	15	47	
1SMAF4748A	748A	20.8	22	23.3	12	23	5	17	43	
1SMAF4749A	749A	22.8	24	26.0	11	25	5	18	38	
1SMAF4750A	750A	25.3	27	28.9	9.5	35	5	21	35	

Characteristics at Ta = 25°C

Type	Marking	Zener Voltage Range ⁽¹⁾				Dynamic Impedance	Reverse Current		Admissible Zener Current
		V _{ZT} (at I _{ZT})			I _{ZT}	Z _{ZT} (at I _{ZT})	I _R	at V _R	
		Min (V)	Nom (V)	Max (V)	(mA)	Max (Ω)	Max (μA)	(V)	I _{ZM} (mA)
1SMAF4751A	751A	28.2	30	32.0	8.5	40	5	23	31
1SMAF4752A	752A	31.3	33	34.9	7.5	45	5	25	28
1SMAF4753A	753A	34.2	36	37.9	7.0	50	5	27	26
1SMAF4754A	754A	37.2	39	41.5	6.5	60	5	30	24
1SMAF4755A	755A	40.9	43	45.6	6.0	70	1	32	22
1SMAF4756A	756A	44.9	47	49.8	5.5	80	1	35	20
1SMAF4757A	757A	48.6	51	54.0	5.0	95	1	38	18
1SMAF4758A	758A	53.6	56	58.8	4.5	110	1	42	17
1SMAF4759A	759A	58.9	62	65.6	4.0	125	1	47	15
1SMAF4760A	760A	64.6	68	71.7	3.7	150	1	52	14
1SMAF4761A	761A	71.2	75	78.8	3.3	175	1	56	12
1SMAF4762A	762A	77.9	82	87.0	3.0	200	1	62	11
1SMAF4763A	763A	86.0	91	96.0	2.8	250	1	69	10
1SMAF4764A	764A	95.0	100	105	2.5	350	1	76	9.5
1SMAF4765A	765A	104	110	116	2.3	450	1	84	8.6
1SMAF4766A	766A	114	120	127	2.0	550	1	91	7.8
1SMAF4767A	767A	125	135	142	1.9	700	1	100	7.0
1SMAF4768A	768A	140	150	157	1.7	900	1	110	6.3
1SMAF4769A	769A	155	165	172	1.6	1100	1	120	5.8
1SMAF4770A	770A	170	180	191	1.4	1200	1	135	5.2
1SMAF4771A	771A	189	200	211	1.2	1400	1	150	4.7
1SMAF4772A	772A	209	220	231	1.0	1600	1	165	4.3
1SMAF4773A	773A	229	240	251	1.0	1800	1	180	3.9
1SMAF4774A	774A	249	260	271	1.0	2000	1	190	3.7
1SMAF4775A	775A	269	280	291	1.0	2100	1	205	3.4
1SMAF4776A	776A	289	300	315	1.0	2300	1	230	3.1
1SMAF4777A	777A	313	330	346	1.0	2500	1	250	2.8

(1) V_{ZT} is tested with pulses (20 ms)