



Parameter	Symbol	Rating	Units
Load Voltage	V <sub>L</sub>	350	V
Load Current	I <sub>L</sub>	0.12	A
On-Resistance	R <sub>on</sub>	15	Ω
I/O Breakdown Voltage	V <sub>io</sub>	2500	Vrms



SOP-4



1. LED Anode
2. LED Cathode
- 3.4. Drain(MOS FET)

## SUPSiC PhotoRelays

- Long life (No limit on mechanical and electrical lifetime)
- Bounce-free switching
- Higher speed and high frequency switching
- Higher sensitivity (less power consumption)
- Immunity to EMI or RFI


NEW

## Applications

- Telecom/Datacom switching
- Multiplexers
- Meter reading systems
- Data acquisition
- Medical equipment
- Battery monitoring
- I/O Sub-Systems
- Robotics
- Aerospace
- Home/Safety security systems
- Process Control
- Energy Management
- Reed Relay EMR Replacement
- Programmable Controllers

## TPYES

Category	Output Rating		Package	Part No.	Packing Quantity
	Load Voltage	Load Current			
AC/DC	350V	0.12A	SOP-4	GAQY210KSX	2000pcs /reel



## Absolute Maximum Ratings (Ta = 25°C)













Item		Symbol	Value	Units	Note
Input	Continuous LED Current	I <sub>F</sub>	50	mA	
	Peak LED Current	I <sub>FP</sub>	1000	mA	f=100Hz, duty=1%
	LED Reverse Voltage	V <sub>R</sub>	5	V	
	Input Power Dissipation	P <sub>In</sub>	75	mW	
Output	Load Voltage	V <sub>L</sub>	350	V(AC peak or DC)	
	Load Current	I <sub>L</sub>	0.12	A	
	Peak Load Current	I <sub>Peak</sub>	0.24	A	100ms(1 pulse)
	Output Power Dissipation	P <sub>out</sub>	300	mW	
Total Power Dissipation		P <sub>T</sub>	350	mW	
I/O Breakdown Voltage		V <sub>I/O</sub>	2500	Vrms	RH=60%, 1min
Operating Temperature		T <sub>opr</sub>	-40 to 85	°C	
Storage Temperature		T <sub>stg</sub>	-40 to 100	°C	
Pin Soldering Temperature		T <sub>sol</sub>	260	°C	10 sec max.

## Electrical Characteristics (Ta = 25°C)


Item		Symbol	MIN.	TYP.	MAX.	Units	Conditions	
Input	LED Forward Voltage	V <sub>F</sub>		1.12	1.4	V	I <sub>F</sub> =10mA	
	Operation LED Current	I <sub>Fon</sub>		0.5	2.0	mA		
	Recovery LED Current	I <sub>Foff</sub>		0.35	0.5	mA		
	Recovery LED Voltage	V <sub>Foff</sub>	0.7			V		
Output	On-Resistance	R <sub>on</sub>		15	22	Ω	I <sub>F</sub> =5mA, I <sub>L</sub> =100mA, Time to flow is within 1 sec.	
	Off-State Leakage Current	I <sub>Leak</sub>			0.10	uA	V <sub>L</sub> =Rating	
	Output Capacitance	C <sub>out</sub>		44		pF	V <sub>L</sub> =0, f=1MHz	
	Over current protection Over current protection NEW	Cut off current	I <sub>Shut</sub>	100	180	240	mA	I <sub>F</sub> = 5 mA Within 20 ms
		Detection time	Shut		50	μs	I <sub>F</sub> = 5 mA VL = 350 V DC short circuit	
Transmis sion	Turn-On Time	T <sub>on</sub>		0.08	0.2	ms	I <sub>F</sub> =5mA, I <sub>L</sub> =100mA,	
	Turn-Off Time	T <sub>off</sub>		0.02	0.1	ms		
Coupled	I/O Isolation Resistance	R <sub>I/O</sub>	10 <sup>10</sup>			Ω	DC500V	
	I/O Capacitance	C <sub>I/O</sub>		0.8	1.5	pF	f=1MHz	

Please obey the following conditions to ensure proper device operation and resetting. Input LED current (Recommended value): IF ≥5mA and ≤30mA


## Engineering Data





## Engineering Data




## Dimensions and Package




## Tape dimensions



**Using Methods**Examples of resistance value to control LED forward current ( $I_F=5\text{mA}$ )

E1	R1 (Approx)
3.3V	300 $\Omega$
5.0V	600 $\Omega$
12V	1.9K $\Omega$
24V	4.1K $\Omega$



LED forward current must be more than 5mA , at  $I(\text{MIN})$  ,and less than 30mA , at  $I(\text{MAX})$ .**Recommended Operating Conditions**

Please obey the following conditions to ensure proper device operation and resetting. Input LED current (Recommended value):

Characteristic	Symbol	Min	Typ.	Max	Unit
Forward current	$I_F$	5.0	7.0	30	mA

**Protection Circuit**


Output spike voltages:if an inductive load generates spike voltages which exceed the absolute maximum rating, the spike voltage shall be limited.

Clamp diode is connected in parallel with the load.  
Absorb capacity with external diode.CR Snubber is connected in parallel with the load.  
Absorb capacity with buffer capacity.When adding diodes, buffer circuits (C-R), and other protections, they need to be installed near the MOS RELAY to be effective.  
Adding protection elements may result in a slow reset time, so adjust them according to the actual situation before use.

Note: When developing designs using this product, perform the expected performance of the equipment under the operating conditions recommended by the guidelines in this document. Continuous use under heavy loads (including, but not limited to, the application of high temperatures/current/voltage and significant changes in temperature, etc.) may result in deterioration of the reliability of this product.

**Recommended Soldering Conditions****(a) Infrared reflow soldering :**

- Peak reflow soldering : 260°C or below (package surface temperature)
- Time of peak reflow temperature : 10 sec
- Time of temperature higher than 230°C : 30-60 sec
- Time to preheat temperature from 180~190°C : 60-120 sec
- Time(s) of reflow : Two
- Flux : Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.)

**Recommended Temperature Profile of Infrared Reflow****(b) Wave soldering :**

- Temperature : 260°C or below (molten solder temperature)
- Time : 10 seconds or less
- Preheating conditions : 120°C or below (package surface temperature)
- Time(s) of reflow : One
- Flux : Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.)

**(c) Cautions :**

- Fluxes : Avoid removing the residual flux with freon-based and chlorine-based cleaning solvent.
- Avoid shorting between portion of frame and leads.