


DESCRIPTION

PUSB3F96X-JSM is an ultra-low capacitance Transient Voltage Suppressor (TVS) designed to protection for high-speed data interfaces. With typical capacitance of 0.2pF (I/O to I/O) only, PUSB3F96X-JSM is designed to protect parasitic-sensitive systems against over-voltage and over current transient events. It complies with IEC 61000-4-2(ESD), Level 4 ($\pm 15\text{KV}$ air, $\pm 8\text{KV}$ contact discharge), IEC 61000-4-4 (electrical fast transient-EFT) (40A, 5/50ns), very fast charged device model (CDM) ESD and cable discharge event (CDE), etc. PUSB3F96X-JSM uses ultra-small DFN2510 package. Each PUSB3F96X-JSM device can protect four high-speed data lines. The combined features of ultra-low capacitance, ultra-small size and high ESD robustness make PUSB3F96X-JSM ideal for high-speed data ports and high frequency lines (e.g., HDMI & DVI) applications. The low clamping voltage of the PUSB3F96X-JSM guarantees a minimum stress on the protected IC.



FEATURES

- ◆ Transient protection for high-speed data lines
IEC 61000-4-2(ESD) $\pm 25\text{KV}$ (Air)
 $\pm 20\text{KV}$ (Contact)
IEC 61000-4-4(EFT) 40A(5/50ns)
Cable Discharge Event(CDE)
- ◆ Package optimized for high-speed lines
- ◆ Ultra-small package (2.5mm*1.0mm*0.5mm)
- ◆ Protects four data lines
- ◆ Low capacitance: 0.2pF (I/O to I/O)
- ◆ Low leakage current
- ◆ Low clamping voltage
- ◆ Each I/O pin can withstand over 1000 ESD strikes for $\pm 8\text{KV}$ contact discharge

APPLICATIONS

- ◆ Serial ATA
- ◆ PCI Express
- ◆ Desktops, Servers and Notebooks
- ◆ MDDI Ports
- ◆ USB 2.0/3.0 Power and Data Line Protection
- ◆ Display Ports
- ◆ High Definition Multi-Media Interface (HDMI)
- ◆ Digital Visual Interface (DVI)

MACHANICAL DATA

- ◆ DFN2510 package
- ◆ Terminal: Matte tin plated.
- ◆ Packaging: Tape and Reel
- ◆ High temperature soldering guaranteed: 260°C/10s
- ◆ Reel size: 7 inch







ABSOLUTE MAXIMUM RATING

Symbol	Parameter	Value	Units
P _{pp}	Peak Pulse Power (8/20μs)	60	W
V _{ESD}	ESD per IEC 61000-4-2(Air) ESD per IEC 61000-4-2(Contact)	±25 ±20	kV
T _{OPT}	Operating Temperature	-55/+125	°C
T _{STG}	Storage Temperature	-55/+150	°C


ELECTRICAL CHARACTERISTICS (T_{amb}=25°C)

Symbol	Parameter	Test Condition	Min	Typ	Max	Units
V _{RWM}	Reverse Working Voltage	Any I/O pin to GND			5.0	V
V _{BR}	Reverse Breakdown Voltage	I _T =1mA Any I/O pin to GND	6.0		9.0	V
I _R	Reverse Leakage Current	V _{RWM} =5V Any I/O pin to GND			1.0	μA
V _C	Clamping Voltage	I _{pp} =1A, t _o =8/20μs Any I/O pin to GND			10	V
V _C	Clamping Voltage	I _{pp} =4A, t _o =8/20μs Any I/O pin to GND			15	V
C _{ESD}	Parastic Capactance	V _R =0V, f=1MHz Between I/O and GND		0.4	0.5	pF
C _{ESD}	Parasitic Capacitance	V _R =0V, f=1MHz Between I/O and I/O		02	0.3	pF

ELECTRICAL CHARACTERISTICS CURVE



PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions (mm)		
	Min.	Nom.	Max.
D	2.45	2.50	2.55
E	0.95	1.00	1.05
b1	0.35	0.40	0.45
b2	0.20REF		
b	0.15	0.20	0.25
L	0.33	0.38	0.43
Nd	2.00BSC		
e	0.50BSC		
R	0.10	0.125	0.15
A	0.45	0.50	0.55
c	0.15REF		
A1	0.00	-	0.05

Revision History

Rev.	Change	Date
V1.0	Initial version	2/23/2024

Important Notice

JSMSEMI Semiconductor (JSMSEMI) PRODUCTS ARE NEITHER DESIGNED NOR INTENDED FOR USE IN MILITARY AND/OR AEROSPACE, AUTOMOTIVE OR MEDICAL DEVICES OR SYSTEMS UNLESS THE SPECIFIC JSMSEMI PRODUCTS ARE SPECIFICALLY DESIGNATED BY JSMSEMI FOR SUCH USE. BUYERS ACKNOWLEDGE AND AGREE THAT ANY SUCH USE OF JSMSEMI PRODUCTS WHICH JSMSEMI HAS NOT DESIGNATED FOR USE IN MILITARY AND/OR AEROSPACE, AUTOMOTIVE OR MEDICAL DEVICES OR SYSTEMS IS SOLELY AT THE BUYER' S RISK.

JSMSEMI assumes no liability for application assistance or customer product design. Customers are responsible for their products and applications using JSMSEMI products.

Resale of JSMSEMI products or services with statements diferent from or beyond the parameters stated by JSMSEMI for that product or service voids all express and any implied warranties for the associated JSMSEMI product or s ervice. JSMSEMI is not responsible or liable for any such statements.

JSMSEMI All Rights Reserved. Information and data in this document are owned by JSMSEMI wholly and may not be edited, reproduced, or redistributed in any way without the express written consent from JSMSEMI.

Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the JSMSEMI product that you intend to use.

For additional information please contact Kevin@jsmsemi.com or visit www.jsmsemi.com