

REV.	ECN.NO.	MODIFY.CONTENT	DATE
A0		NEW	2013.02.29

NOTES:

1) MATERIAL:

HOUSING: LCP UL 94V-0

CONTACT: COPPER ALLOY

SHELL: STAINLESS STEEL

2) FINISH:


CONTACT: GOLD FLASH PLATED ON CONTACT AREA;

GOLD FLASH PLATING ON SOLDER TAILS,


WITH ENTIRE CONTACT UNDERPLATED NICKEL

SHELL: NICKEL UNDERPLATED OVERALL,


GOLD FLASH PLATED ON SOLDER TAILS




MICRO SIM CARD	
PIN NO.	DESCRIPTION
C1	VCC
C3	RST
C5	CLK
C7	
C2	GND
C4	VPP
C6	I/O
C8	



MICRO SIM CARD
芯片面朝下视图



INSERT CARD



RECOMMENDED PCB LAYOUT(TOP VIEW)


GENERAL TOLERANCES: ±0.05

GENERAL TOLERANCE		图号	设计	比例	1:1	
X.±0.45	x.±5°					
.X±0.35		品名	MICRO SIM 2.65H 6PIN CARD CONN.	审核	单位 mm	
.XX±0.25						
.XXX±0.15		料号	5001B-SIM265-087	核准	视角	
.xxx±0.5°						
页数	1/2	日期		2013/02/29	版本 A0	

东莞市文章济美电子有限公司

REV.	ECN.NO.	MODIFY.CONTENT	DATE
A0		NEW	2013.02.29


<图一>



<TABLE 1> PACKAGING QUANTITY

QTY/REEL	REEL/CARTON	QTY/CARTON
1000	10	10000

<图二>



NOTE:

1. 依<图一>示放置产品于下载中, 每穴放置1PCS产品.
2. 包装机包好后, 在REEL的个等分点贴上胶带, 以防止REEL张开, 每REEL贴1PCS标签, 如<图二>示
3. 包装数量见如<TABLE 1>示
4. 包装成箱见如<图三>示
箱底放保丽龙板, 再依次将指定数量的卷装产品用防水袋包好放入箱内, 四角分别放入四个三角护板, 最上层再放上保丽龙板.
5. 封箱, 在封好的纸箱上按客户要求写上料号, 数量等

GENERAL TOLERANCE	图号	设计	比例	1:1
X.±0.45	x.±5°	品名	MICRO SIM 2.65H 6PIN CARD CONN.包装图	审核
.X±0.35	.x.±2°			核准
.XX±0.25	.xx.±1°	料号	5001B-SIM265-087	日期 2013/02/29
.XXX±0.15	.xxx.±0.5°			
页号	2/2			东莞市文章济美电子有限公司