

1. Description

The HCPL-3180 is a gate driven optocoupler with an output current of 2.5 A, with an AlGaAs LED, which is coupled to a photosensitive integrated circuit through infrared light. This optocoupler can drive most low-power IGBTs and MOSFETs. In the motor control inverter and high-performance power system applications, it is very suitable for fast switching drive power IGBTs and MOSFETs.



3. Features

- 35kV/ μ s minimum Common Mode Rejection
- 2.5A maximum peak output current
- Wide operating V_{CC} Range: 10V~20V
- 400ns maximum propagation delay


2. Applications

- Uninterrupted Power Supply
- IGBT isolation / power MOSFET gate drive
- Induction heating
- Industrial inverters

4. Pinning Information



DIP-8



SOP- 8

Note: 0.1 μ F bypass capacitor must be connected between pins 5 and 8.



5. Insulation And Safety Related Specifications

Parameter	Symbol	Note	Value	Unit
Creepage Distance	L	Measured from input terminals to output terminals, shortest distance path along body	≥7	mm
Clearance Distance	L	Measured from input terminals to output terminals, shortest distance through air	≥7	mm
Insulation Thickness	DTI	Insulation thickness between emitter and detector	≥0.4	mm
Peak Isolation Voltage	V_{IORM}	DIN/EN/IEC EN60747-5-5.	1500	V_{peak}
Transient Isolation Voltage	V_{IOTM}	DIN/EN/IEC EN60747-5-5.	7000	V_{peak}
Isolation Voltage	V_{ISO}	For 1 min	5000	V_{rms}

6. Absolute Maximum Ratings $T_A = 25^\circ\text{C}$

Parameter		Symbol	Value	Units
Input	Forward Input Current	I_{FM}	25	mA
	Reverse Voltage	V_R	5	V
Output	Peak Output Current ⁽¹⁾	$I_{O(PEAK)}$	2.5	A
	Supply Voltage	$V_{CC}-V_{EE}$	-0.5 to 25	V
	Output Voltage	V_O	-0.5 to V_{CC}	V
Isolation Voltage		V_{ISO}	5000	V_{rms}
Output Power Dissipation ⁽²⁾		P_O	250	mW
Total Power Dissipation ⁽³⁾		P_T	295	mW
Operating Temperature		T_{opr}	-40 to 110	$^\circ\text{C}$
Storage Temperature		T_{stg}	-55 to 125	$^\circ\text{C}$
Soldering Temperature		T_{sol}	260	$^\circ\text{C}$



7.Recommended Operating Conditions

Parameter	Symbol	Min	Max	Units
Power Supply Voltage	$V_{DD}-V_{SS}$	10	20	V
Input Current (ON)	$I_{F(ON)}$	7	16	mA
Input Voltage (OFF)	$V_{F(OFF)}$	-3.6	0.8	V
Operating Temperature	T_A	-40	110	°C



8. Electro-optical Characteristics ($T_A=25^\circ\text{C}$)

All minimum and maximum specifications are at recommended operating conditions, unless otherwise noted

All typical values are at $T_A=25^\circ\text{C}$, $V_{CC}=30\text{V}$, and $V_{EE}=\text{GND}$.

Parameter	Symbol	Conditions		Min	Typ	Max	Units
Forward Voltage	V_F	$I_F=10\text{mA}$		1.2	1.5	1.8	V
Reverse Current	I_R	$V_R=5\text{V}$				10	μA
High Level Output Current ^{(1) (4)}	I_{OH}	$V_O=V_{CC}-4\text{V}$		0.5			A
		$V_O=V_{CC}-10\text{V}$		2			A
Low Level Output Current ^{(1) (4)}	I_{OL}	$V_O=V_{EE}+2.5\text{V}$		0.5			A
		$V_O=V_{EE}+10\text{V}$		2			A
High Level Output Voltage ^{(5) (6)}	V_{OH}	$I_F=10\text{mA}$	$I_O=-100\text{mA}$	$V_{DD}-4\text{V}$			V
Low Level Output Voltage	V_{OL}	$I_F=0\text{mA}$	$I_O=100\text{mA}$			0.5V	V
High Level Power Supply Current	I_{cch}	$V_O=\text{Open}$, $I_F=7$ to 16mA			1.8	3.8	mA
Low Level Power Supply Current	I_{ccl}	$V_O=\text{Open}$, $V_F=0$ to 0.8V			2.1	3.8	mA
Input The Turn On Current	I_{FLH}	$I_O=0\text{mA}$, $V_O>5\text{V}$			2.8	5	mA
Input The Turn Off Voltage	V_{FHL}	$I_O=0\text{mA}$, $V_O<5\text{V}$		0.8			V
UVLO Threshold	V_{UVLO+}	$I_F=10\text{mA}$, $V_O>5\text{V}$		7.1	7.8	8.5	V
	V_{UVLO-}	$I_F=10\text{mA}$, $V_O<5\text{V}$		6	6.7	7.5	V
UVLO Hysteresis	$UVLO_{HYS}$				1.1		V
Isolation Resistance	R_{ISO}	$V_{I-O}=500\text{V}$, 40~60% R.H.			10^{11}		Ω
Isolation Capacitance	C_{ISO}	$V_{I-O}=0\text{V}$, Freq=1MHZ			1		pF
Propagation Delay Time to Low Output Level ⁽⁷⁾	T_{PHL}	$I_F=7\text{mA}$ to 16mA $R_g=10\Omega$ $C_g=10\text{nF}$ $F=10\text{KHZ}$ Duty Cycle=50%			100	300	ns
Propagation Delay Time to High Output Level ⁽⁷⁾	T_{PLH}				100	300	ns
Pulse Width Distortion ⁽⁸⁾	PWD				3	100	ns
Propagation Delay Difference Between Any Two Parts ⁽⁸⁾	P_{DD}			-250		250	ns









Parameter	Symbol	Conditions	Min	Typ	Max	Units
Output Rise Time (10% To 90%)	T_R	$I_F=7\text{mA to }16\text{mA}, R_g=10\Omega, C_g=10\text{NF}$ $F=10\text{KHZ, Duty Cycle}=50\%$		50		ns
Output Drop Time(90%~10%)	T_F			50		ns
UVLO Turn On Delay	$T_{UVLO\ ON}$	$I_F=10\text{mA}, V_O>5\text{V}$		2		μs
UVLO Turn Off Delay	$T_{UVLO\ OFF}$	$I_F=10\text{mA}, V_O<5\text{V}$		0.4		μs
Output High Level Common Mode Transient Immunity ^{(9) (10)}	$ CM_H $	$T_A=25^\circ\text{C}, V_{DD}=30\text{V}$ $V_{CM}=2000\text{V}, I_F=7\sim16\text{mA}, V_F=0\text{V}$	35	50		KV/ μs
Output Low Level Common Mode Transient Immunity ^{(9) (11)}	$ CM_L $	$T_A=25^\circ\text{C}, V_{DD}=30\text{V}$ $V_{CM}=2000\text{V}, I_F=7\sim16\text{mA}, V_F=0\text{V}$	35	50		KV/ μs

- Maximum pulse width = 10 μs , maximum duty cycle = 0.2%. This value is intended to allow for component tolerances for designs with I_O peak minimum = 2.0 A. See Application section for additional details on limiting IOL peak.
- Derate linearly above +70°C, free air temperature at the rate of 4.8 mW/°C.
- Derate linearly above +70°C, free air temperature at the rate of 5.4 mW/°C. The maximum LED junction temperature should not exceed +125°C.
- Maximum pulse width = 50 μs , maximum duty cycle = 0.5%.
- In this test, V_{OH} is measured with a dc load current. When driving capacitive load V_{OH} will approach V_{CC} as I_{OH} approaches zero amps.
- Maximum pulse width = 1 ms, maximum duty cycle = 20%.
- t_{PHL} propagation delay is measured from the 50% level on the falling edge of the input pulse to the 50% level of the falling edge of the V_O signal. t_{PLH} propagation delay is measured from the 50% level on the rising edge of the input pulse to the 50% level of the rising edge of the V_O signal.
- PWD is defined as $|t_{PHL} - t_{PLH}|$ for any given device.
- Pin 1 and 4 need to be connected to LED common.
- Common mode transient immunity in the high state is the maximum tolerable dV_{CM}/dt of the common mode pulse V_{CM} to assure that the output will remain in the high state (i.e. $V_O > 10.0\text{ V}$).
- Common mode transient immunity in a low state is the maximum tolerable dV_{CM}/dt of the common mode pulse, V_{CM} , to assure that the output will remain in a low state (i.e. $V_O < 1.0\text{ V}$).



9.1 Typical Characteristic

Figure 1: V_{OH} vs. TemperatureFigure 2: I_{OH} vs. TemperatureFigure 3: V_{OH} vs. I_{OH} Figure 4: V_{OL} vs. TemperatureFigure 5: I_{OL} vs. TemperatureFigure 6: V_{OL} vs. I_{OL}



9.2 Typical Characteristic








Figure 7: I_{CC} vs. TemperatureFigure 8: I_{CC} vs. V_{CC} Figure 9: I_{FLH} vs. TemperatureFigure 10: Propagation Delay vs. V_{CC} Figure 11: Propagation Delay vs. I_F 

Figure 12: Propagation Delay vs. Temperature



9.3 Typical Characteristic





10. Test Circuits Diagrams







Figure 17. I_{OH} test circuitFigure 18. I_{OL} test circuitFigure 19. V_{OH} test circuitFigure 20. V_{OL} test circuitFigure 21. I_{FLH} test circuit

Figure 22. UVLO test circuit




Figure 23. t_{PLH} , t_{PHL} , t_r and t_f testcircuit and waveform

Figure 24. CMR testcircuit and waveform



11.1 DIP-8 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	B	B1	C	D	D1
Min	6.30	9.46	7.62	0.25	5°	0.40	2.54	4.20
Max	6.90	10.06	TYP.		15°	0.60	TYP.	4.80



11.2 SOP-8 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	B	B1	B2	C	D	D1	E
Min	6.30	1.45	9.46	7.62	0.25	0.6	-	2.54	3.20	4.00
Max	6.90		10.06	TYP		-	10.3	TYP	3.80	4.60



12.Ordering Information



yy: Year Code
ww: Week Code

Order Code	Marking	Package	Base QTY	Delivery Mode
UMW HCPL-3180-000E	3180	DIP-8	2250	Tube and box
UMW HCPL-3180-500E	3180	SOP-8	1000	Tape and reel



13.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.