


Description:

This N-Channel MOSFET uses advanced trench technology and design to provide excellent $R_{DS(on)}$ with low gate charge.

It can be used in a wide variety of applications.

Features:

- 1) $V_{DS}=30V, I_D=30A, R_{DS(on)} < 28m\Omega @ V_{GS}=10V$ (Typ: $18m\Omega$)
- 2) Low gate charge.
- 3) Green device available.
- 4) Advanced high cell density trench technology for ultra low $R_{DS(on)}$.
- 5) Excellent package for good heat dissipation.



Package Marking and Ordering Information:

Part NO.	Marking	Package	Packing
PC020NG	C020N	TO- 220S	50 pcs/Tube

Absolute Maximum Ratings: ($T_C=25^\circ C$ unless otherwise noted)

Symbol	Parameter	Ratings	Units
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	Continuous Drain Current	30	A
	Continuous Drain Current- $T_C=100^\circ C$	21	
I_{DM}	Pulsed Drain Current ¹	120	
P_D	Power Dissipation	71	W
E_{AS}	Single pulse avalanche energy ²	8.45	mJ
T_J, T_{STG}	Operating and Storage Junction Temperature Range	-55-+150	$^\circ C$

Thermal Characteristics:

Symbol	Parameter	Max	Units
$R_{\theta JC}$	Thermal Resistance, Junction to Case	1.75	$^\circ C/W$
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	80	$^\circ C/W$

Electrical Characteristics: ($T_C=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
Off Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250 μ A	30	---	---	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{GS} =0V, V _{DS} =30V	---	---	1	μ A
I _{GSS}	Gate-Source Leakage Current	V _{GS} =± 20V, V _{DS} =0A	---	---	± 100	nA
On Characteristics						
V _{GS(th)}	Gate-Source Threshold Voltage	V _{GS} =V _{DS} , I _D =250 μ A	1.2	1.6	2.5	V
R _{DS(on)}	Drain-Source On Resistance ³	V _{GS} =10V, I _D =10A	---	18	28	m Ω
		V _{GS} =4.5V, I _D =6A	---	24	36	m Ω
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =15V, V _{GS} =0V, f=1MHz	---	370	---	pF
C _{oss}	Output Capacitance		---	73	--	
C _{rss}	Reverse Transfer Capacitance		---	42	---	
Switching Characteristics						
t _{d(on)}	Turn-On Delay Time	V _{DS} =15V, I _D =1A, R _L =15 Ω , R _{ENG} =6 Ω ,V _{GS} =10V	---	5.7	---	ns
t _r	Rise Time		---	9.4	---	ns
t _{d(off)}	Turn-Off Delay Time		---	14.7	---	ns
t _f	Fall Time		---	3.7	---	ns
Q _g	Total Gate Charge	V _{GS} =10V, V _{DS} =15V, I _D =8A	---	7.2	---	nC
Q _{gs}	Gate-Source Charge		---	1.1	---	nC
Q _{gd}	Gate-Drain “Miller” Charge		---	1.6	---	nC
Drain-Source Diode Characteristics						
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _{SD} =1A	---	---	1.1	V
I _S	Continuous Drain Current	V _D =V _G =0V	---	---	30	A
I _{SM}	Pulsed Drain Current		---	---	120	A
T _{rr}	Reverse Recovery Time	I _F =8A, T _J =25 °C	---	12	---	ns
Q _{rr}	Reverse Recovery Charge	di/dt=100A/us	---	3.7	---	nC

Notes:

1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature
2. EAS condition : $T_J=25^{\circ}\text{C}$, $V_{DD}=15\text{V}$, $V_G=10\text{V}$, $L=0.5\text{mH}$
3. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 0.5\%$

Typical Characteristics: ($T_C=25^{\circ}\text{C}$ unless otherwise noted)




Figure1: Power Dissipation




Figure 2: Drain Current




Figure 3: Safe Operation Area




Figure 4: Thermal Transient Impedance




Figure 5 Power Dissipation




Figure 6: Drain Current




Figure 7: Safe Operation Area




Figure 8: Thermal Transient Impedance




Figure 9: Output Characteristics




Figure 10: Drain-Source On Resistance




Figure.11: Gate-Source On Resistance




Figure 12 Gate Threshold Voltage




Figure 13 Drain-Source On Resistance




Figure 14 Source-Drain Diode Forward




Figure 15 Capacitance




Figure 16 Gate Charge





Figure 17 Transfer Characteristics

TO-220 Package Information:



UNIT: mm

SYMBOLS	A	A1	A2	b	b1	c	D	D1	D2	E	E1	e
MIN	4.25	1.25	2.35	0.7	1.15	0.45	14.35	8.80	13.05	9.90	7.85	2.540
MAX	4.65	1.35	2.55	0.9	1.75	0.60	15.95	9.50	13.65	10.35	8.85	BSC
SYMBOLS	e1	H1	L	L1	Q	φP						
MIN	5.080	6.30	12.85	2.85	2.70	3.50						
MAX	BSC	6.65	13.50	3.25	2.90	3.70						

Marking Information:

①. Doingter LOGO


②. Date Code(YWWG / R)

Y : Year Code , last digit of the year

WW : Week Code(01-53)

G/R : G(Green) /R(Lead Free)

③. Part NO.



Previous Version

Version	Date	Subjects (major changes since last revision)
1.0	2024-09-26	Release of final version

Attention :

- Information furnished in this document is believed to be accurate and reliable. However, Shenzhen Doingter Semiconductor Co.,Ltd. assumes noresponsibility for the consequences of use without consideration for such information nor use beyond it.
- Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Shenzhen Doingter complies with the agreement. Products and information provided in this document have no infringement of patents.
- Shenzhen Doingter assumes noresponsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



Is

a registered trademark of Shenzhen Doingter Semiconductor Co., Ltd. Copyright © 2013

Shenzhen DoingterSemiconductor Co.,Ltd. Printed All rights reserved.