

## Features


Fast switching  
 Low turn-on voltage  
 PN junction guard ring for  
 transient and ESD protection  
 Available in lead free version.



SOT-23

## Mechanical Data

Case: SOT-23  
 Terminals: solderable per MIL-STD-202,  
 Method 208



## Ordering Information

Part Number	Package	Shipping
PMEG2005CT,215-JSM	SOT-23	3000pcs / Tape & Reel

## Maximum Ratings (@ $T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Limits	Unit
Peak Repetitive Peak reverse voltage	$V_{RRM}$		
Working Peak Reverse Voltage	$V_{RWM}$	30	V
DC Reverse Voltage	$V_R$		
Forward Continuous Current	$I_F$	200	mA
Repetitive Peak Forward Current	$I_{FRM}$	300	mA
Forward surge current@ $t_p < 1\text{s}$	$I_{FSM}$	600	mA

**Thermal Characteristics**





Parameter	Symbol	Limits	Unit
Power Dissipation *	$P_D$	250	mW
Thermal resistance junction to ambient air	$R_{\theta JA}$	500	°C/W
Thermal resistance junction to case	$R_{\theta JC}$	360	°C/W
Junction temperature	$T_J$	125	°C
Storage temperature range	$T_{STG}$	-55 to +150	°C

**Electrical Characteristics** (@ $T_A=25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse Breakdown Voltage	$V_{(BR)}$	$I_R=100\mu\text{A}$	30	-	-	V
Forward voltage * <sup>1</sup>	$V_F$	$I_F=0.1\text{mA}$	-	-	0.24	V
		$I_F=1\text{mA}$	-	-	0.32	V
		$I_F=10\text{mA}$	-	-	0.40	V
		$I_F=30\text{mA}$	-	-	0.50	V
		$I_F=100\text{mA}$	-	-	0.8	V
Reverse current * <sup>2</sup>	$I_R$	$V_R=25\text{V}$	-	-	2	$\mu\text{A}$
Capacitance Between Terminals	$C_T$	$V_R=1\text{V}, f=1\text{MHz}$	-	-	10	pF
Reverse Recovery Time	$t_{rr}$	$I_F=I_R=10\text{mA}$ $I_{rr}=0.1 \times I_R, R_L=100\Omega$	-	-	5	ns


 \*1: pulse test,  $t_p \leq 300\mu\text{s}$ 

 \*2: pulse test,  $t_p \leq 5\text{ms}$

**Ratings and Characteristic Curves** ( $T_A=25^\circ C$  unless otherwise noted)

**Fig.1- Typical Reverse Characteristic**

**Fig.2- Typical Forward Characteristics**

**Fig.3-Capacitance Characteristics**

**Fig.4-Derating Curve**

**Package Outline Dimensions** (unit: mm)


SOT-23



SOT-23		
Dim	Min	Max
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60

**Mounting Pad Layout** (unit: mm)

SOT-23



## Revision History

Rev.	Change	Date
V1.0	Initial version	2/23/2024

## Important Notice

JSMSEMI Semiconductor (JSMSEMI) PRODUCTS ARE NEITHER DESIGNED NOR INTENDED FOR USE IN MILITARY AND/OR AEROSPACE, AUTOMOTIVE OR MEDICAL DEVICES OR SYSTEMS UNLESS THE SPECIFIC JSMSEMI PRODUCTS ARE SPECIFICALLY DESIGNATED BY JSMSEMI FOR SUCH USE. BUYERS ACKNOWLEDGE AND AGREE THAT ANY SUCH USE OF JSMSEMI PRODUCTS WHICH JSMSEMI HAS NOT DESIGNATED FOR USE IN MILITARY AND/OR AEROSPACE, AUTOMOTIVE OR MEDICAL DEVICES OR SYSTEMS IS SOLELY AT THE BUYER'S RISK.

JSMSEMI assumes no liability for application assistance or customer product design. Customers are responsible for their products and applications using JSMSEMI products.

Resale of JSMSEMI products or services with statements different from or beyond the parameters stated by JSMSEMI for that product or service voids all express and any implied warranties for the associated JSMSEMI product or service. JSMSEMI is not responsible or liable for any such statements.

JSMSEMI All Rights Reserved. Information and data in this document are owned by JSMSEMI wholly and may not be edited, reproduced, or redistributed in any way without the express written consent from JSMSEMI.

Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the JSMSEMI product that you intend to use.

For additional information please contact [Kevin@jsmsemi.com](mailto:Kevin@jsmsemi.com) or visit [www.jsmsemi.com](http://www.jsmsemi.com)