

# Double Row Terminal Blocks

## 671 RZ Series

### 300 Volts AC/DC (Class B)



671 RZ 06

#### Specifications:

- Base, Thermoplastic, 125°C (UL RTI)
- Closed Back Design
- Screws, #6-32 Binder Head, Phil-Slot, Steel
- Terminals, Plated Brass
- 1-30 Poles
- 7/16" Centers
- Wire Range With Wire Binding Screw  
#12 - #22 AWG – 20 Amps
- Wire Range With Sems Pressure Screw #12 - #22 AWG  
Stranded Copper Wire Only, 20 Amps
- UL Recognized File No. XCFR2.E62806
- CSA Certified File No. LR19766
- **CE**
- RoHS Compliant

| MSP<br>Catalog # | # of poles | Dimensions |       |
|------------------|------------|------------|-------|
|                  |            | A          | B     |
| 671 RZ 01        | 1          | 1.19       | 0.88  |
| 671 RZ 02        | 2          | 1.62       | 1.31  |
| 671 RZ 03        | 3          | 2.06       | 1.75  |
| 671 RZ 04        | 4          | 2.50       | 2.19  |
| 671 RZ 05        | 5          | 2.94       | 2.63  |
| 671 RZ 06        | 6          | 3.37       | 3.06  |
| 671 RZ 07        | 7          | 3.81       | 3.50  |
| 671 RZ 08        | 8          | 4.25       | 3.94  |
| 671 RZ 09        | 9          | 4.69       | 4.38  |
| 671 RZ 10        | 10         | 5.12       | 4.81  |
| 671 RZ 11        | 11         | 5.56       | 5.25  |
| 671 RZ 12        | 12         | 6.00       | 5.69  |
| 671 RZ 13        | 13         | 6.44       | 6.13  |
| 671 RZ 14        | 14         | 6.87       | 6.56  |
| 671 RZ 15        | 15         | 7.31       | 7.00  |
| 671 RZ 16        | 16         | 7.75       | 7.44  |
| 671 RZ 17        | 17         | 8.19       | 7.88  |
| 671 RZ 18        | 18         | 8.62       | 8.31  |
| 671 RZ 19        | 19         | 9.06       | 8.75  |
| 671 RZ 20        | 20         | 9.50       | 9.19  |
| 671 RZ 21        | 21         | 9.94       | 9.63  |
| 671 RZ 22        | 22         | 10.37      | 10.06 |
| 671 RZ 23        | 23         | 10.81      | 10.50 |
| 671 RZ 24        | 24         | 11.25      | 10.94 |
| 671 RZ 25        | 25         | 11.69      | 11.38 |
| 671 RZ 26        | 26         | 12.12      | 11.81 |
| 671 RZ 27        | 27         | 12.56      | 12.25 |
| 671 RZ 28        | 28         | 13.00      | 12.69 |
| 671 RZ 29        | 29         | 13.44      | 13.13 |
| 671 RZ 30        | 30         | 13.87      | 13.56 |

mm=dim X 25.4

For electronic drawings or 2D/3D CAD data, submit request at [www.marathonsp.com/drawings.html](http://www.marathonsp.com/drawings.html)

#### Hardware Options:

(Hardware options may affect ratings - consult Customer Service)

| CATALOG # | PRODUCT               | PAGE                                                       |
|-----------|-----------------------|------------------------------------------------------------|
| MSP       | KULKA                 | REFERENCE                                                  |
|           | KT37                  | Full Quick Connect (0° Flat)                               |
|           | KT38                  | Full Quick Connect (45° Bend)                              |
|           | KT39                  | Full Quick Connect (90° Bend)                              |
|           | KT43                  | Half Quick Connect (0° Flat)                               |
|           | KT44                  | Half Quick Connect (45° Bend)                              |
|           | KT45                  | Half Quick Connect (90° Bend)                              |
|           | ST                    | Full Solder                                                |
|           | 3/4 ST                | Half Solder                                                |
|           | J 601                 | Line to Line Jumper                                        |
|           | 601RJ(S)              | Multiple Position Jumper                                   |
|           | 3765                  | SEMS Pressure Saddle Screw                                 |
|           | 3767                  | SEMS Pressure Saddle Screw with External Tooth Lock Washer |
| PSB       | Phil-Slot Brass Screw | Consult C/S                                                |

Quick Connects: .032" x .250"

See pages 104-115 for terminal block accessories

