

ECEC

NO:ECAB2601038

Acknowledgement Book

Customer Name	:
Customer P/N	:
Frequency	: 8.000000 MHz
ECEC Type	: OSC-3225
ECEC P/N	: TS08000028
Rev.	: 1
ISSUE DATE	: 2026/1/7

Approved By	MFG	QA	PE/RD
郭雄伟	郭雄伟	黄文俊	王晓东
总经理: 郭雄伟	副总: 郭雄伟	副总: 黄文俊	部长: 王晓东
APPROVED BY CUSTOMER			

公司名称: 东晶电子金华有限公司

Corporation: JinHua East Crystal Electronic Co.,Ltd.

地址: 浙江省金华市宾虹路二段555号

ADD: No 555,Sec 2,Binghong Road Jinhua Zhejiang , P.R.C

电话(TEL): 0086-0579-89186666 0086-579-89186777

FAX: 0086-579-89186677 <http://www.ecec.com.cn>



CEC 中国

CUST. P/N	:	
ECEC P/N	:	TS08000028
DESIGN	:	吕俏笑
INSPECTION	:	王晓东

ECEC

CUST. P/N	:			
ECEC P/N	:	TS08000028		
DESIGN	:	吕俏笑	SHEET :	2 of 9
INSPECTION	:	王晓东	REV. :	1

SMD CRYSTAL OSCILLATOR

1. ELECTRICAL CHARACTERISTICS

■ Standard atmospheric conditions

Unless otherwise specified, the standard range of atmospheric conditions for making measurement and tests are as follow :

Ambient temperature : $25 \pm 3^\circ\text{C}$

Relative humidity : 40%~70%

If there is any doubt about the results, measurement shall be made within the following limits :

Ambient temperature : $25 \pm 3^\circ\text{C}$

Relative humidity : 40%~70%

■ ECEC Model : OSC-3225


■ Cutting Model : AT CUT

Parameters	Symbol	Electrical Spec				Notes
		Min.	Typ.	Max.	Units.	
Nominal Frequency	F _{out}	8.000000			MHz	
Frequency Stability		± 10			ppm	at $25 \pm 2^\circ\text{C}$
Temperature drift (TC)		± 20			ppm	
Supply Voltage	V _{DD}	1.8	3.3	3.3	V	
Output Load	CL	15			pF	
Output Type (Logic Levels)		CMOS				
Aging	F _A	±3			ppm	1st Year at 25°C
Operating Temperature	T _{OPR}	-40	~	85	°C	Overall: ±35ppm
Storage Temperature Range	T _{STG}	-55	~	125	°C	
Current consumption	I _{DD}			15	mA	CL@15pF
Standby Current	I _{ST}			10	µA	
Output Voltage High	V _{OH}	2.97			V	
Output Voltage Low	V _{OL}			0.33	V	
Output Rise Time	T _r			8	ns	10%~90% VDD Level
Output Fall Time	T _f			8	ns	10%~90% VDD Level
Symmetry (Output Duty)	Duty	45	~	55	%	50% VDD level, CL@15pF
Start-up Time	T _{osc}			10	ms	
Tri-state Function	I _{NH}	yes				PIN1
Enable Voltage High	V _{IH}	2.31			V	
Disable Voltage Low	V _{IL}			0.99	V	


ECEC

CUST. P/N	:	
ECEC P/N	:	TS08000028
DESIGN	:	吕俏笑
INSPECTION	:	王晓东

2. C - MOS LOAD OUTPUT WAVEFORM



3. C - MOS LOAD TEST CIRCUIT




***Because SMB series has no by pass capacitor.

So, we recommend our customer to use capacitor 0.01 μ F in join Vcc and GND.

ECEC

CUST. P/N	:		
ECEC P/N	:	TS08000028	
DESIGN	:	吕俏笑	SHEET : 4 of 9
INSPECTION	:	王晓东	REV. : 1

4. MARKING :



Frequency: as shown in the table

EX)

Frequency	4.000MHz	16.9344MHz	40.000MHz	100.000MHz
Frequency Code	4000	16934	40000	100.000

Year/Month code: as shown in the table




EX) December of 2020 shall be marked as "z"

Four year 1 cycle


Year	Month											
	Jan.	Feb.	Mar.	Apr.	May.	Jun.	Jul.	Aug.	Sep.	Oct.	Nov.	Dec.
2001	2009	2017	2025	2033	2041	2049	2057	2065	2073	A	B	C
2002	2010	2018	2026	2034	2042	2050	2058	2066	2074	N	P	Q
2003	2011	2019	2027	2035	2043	2051	2059	2067	2075	a	b	c
2004	2012	2020	2028	2036	2044	2052	2060	2068	2076	n	p	q
2005	2013	2021	2029	2037	2045	2053	2061	2069	2077	A	B	C
2006	2014	2022	2030	2038	2046	2054	2062	2070	2078	N	P	Q
2007	2015	2023	2031	2039	2047	2055	2063	2071	2079	a	b	c
2008	2016	2024	2032	2040	2048	2056	2064	2072	2080	n	p	q
										r	s	t
										u	v	w
										x	y	z

5. DIMENSION :

(UNIT : mm)




Suggested Layout



ECEC

CUST. P/N	:	
ECEC P/N	:	TS08000028
DESIGN	:	吕俏笑
INSPECTION	:	王晓东

6. STRUCTURE ILLUSTRATION



PART NAME		MATERIAL	PART NAME		MATERIAL
A	BASE	PACKAGE	D	BLANK	QUARTZ
B	DICE	IC	E	ELECTRODE	SILVER
C	FIXED GLUE	SILVER GLUE	F	LEAD	KOVAR


ECEO 東興

CUST. P/N	:		
ECEC P/N	:	TS08000028	
DESIGN	:	吕俏笑	SHEET : 6 of 9
INSPECTION	:	王晓东	REV. : 1


7. PACKING :

7-1.Dimensions of the tape

(Unit : mm)



7-2.Dimensions of the reel



7-3.Packing and Label


QUARTZ CRYSTAL UNITS
P/O
P/N
HOLD
FRQ.
QTY



Box type(Reel quantity)	Box size(L×W×H) mm
Atype (Reel x 5pcs max)	200×200×140
Btype (Reel x 6~15pcs)	200×200×255
Ctype (Reel x 16~30pcs)	395×200×255
Dtype (Reel x 31~60pcs)	395×400×255

CUST. P/N :		
ECEC P/N :	TS08000028	
DESIGN :	吕俏笑	SHEET : 7 of 9
INSPECTION :	王晓东	REV. : 1

8. COVER TAPE ADHESION STRENGTH :




*** In the case, the cover tape is pulled off under the above conditions the cover tape adhesion strength should be as follows. ***

Plastic tape: 10.2g~71.4g

(Cover tape adhesion strength)

9. SOLDERING REFLOW PROFILE





CUST. P/N :			
ECEC P/N :	TS08000028		
DESIGN :	吕俏笑	SHEET :	8 of 9
INSPECTION :	王晓东	REV. :	1

10 . MECHANICAL PERFORMANCE

TEST ITEMS	TEST METHODS AND TEST CONDITION	PERFORMANCE
10-1. Drop Test	The specimen is measured for its frequency and resistance before the test. It is then dropped from a hight of 100 cm or more as a free fall object onto a hard wooden plate of 30mm or more in thickness. (in accordance with JIS-C0044)	
10-2. Vibration Test	The specimen is measured for its frequency and resistance before the test. Most them into X,Y and Z axes, respectively, for the vibration test. Vibration condition: Frequency range ; 20 ~ 2000HZ Peak to peak amplitude : 1.52 mm Peak acceleration : 20G Sweep time : 20 minute / axis Pendicular total test time : 4 hours (in accordance with MIL-STD-883F : 2007.3)	To satisfy the electrical performance .
10-3. Resistance to Soldering Test	The specimen is measured for its frequency and resistance before the test. Place the specimen on the belt of the converynace and let it pass through the reflow with the presetted temperature condition. After passing twice the reflow place, the specimen under the referee condition for ~2 hours and then measure its electrical performance. Temperature Condition of IR Simulation: The temperature range of the preheated section is setted at 150 ~ 180°C for 60~120 sec. For the next section the temperature range is setted at 217~260°C for 45~90 sec. and within this time range the specimen should be able to sustain at the peak temperature, 260+/-3°C , for 10 sec long. (in accordance with JESD22-B106-B)	
10-4. Fine Leak Test	Place the specimen in a pressurized container and pressurize it with the detection gas (mixed gas consisting of 95% or more helium) for at least 2 hours. Complete the measurement of the concentration of helium within 30 min after taking it out from the pressurized container. (in accordance with MIL-STD-883F : 1014.11)	Less than $1.0 * 10^{-8}$ atm .c.c. / sec, Helium


The referee condition: (In accordance with MIL-STD-883E : 1014. 9)

Temperature : 25 ± 2 °C Humidity : 44 ~ 55 % Pressure: 86 ~ 106 kPa

ECEC

CUST. P/N	:	
ECEC P/N	:	TS08000028
DESIGN	:	吕俏笑
INSPECTION	:	王晓东

11 . CLIMATIC RESISTANCE

TEST ITEMS	TEST METHODS AND TEST CONDITION	PERFORMANCE
11-1. Low Temp Exposure Test	<p>The specimen is measured for its frequency and resistance before the test .</p> <p>Place the specimen in the chamber and kept it at the temperature of $-40 \pm 3^{\circ}\text{C}$ for 168 ± 6 hours .</p> <p>Take the specimen out of the chamber and measure its electrical performance after leaving $1 \sim 2$ hours under the referee condition .</p> <p>(in accordance with JIS-C0020)</p>	
11-2. Aging Test	<p>The specimen is measured for its frequency and resistance before the test .</p> <p>Place the specimen in the testing chamber and keep it at the temperature of $+125 \pm 3^{\circ}\text{C}$ for 720 ± 48 hours .</p> <p>And then take the specimen out of the chamber and measure its electrical performance after leaving for $1 \sim 2$ hours under the referee condition .</p> <p>(in accordance with JIS-C0021)</p>	To satisfy the electrical performance .
11-3. High Temperature & High Humidity	<p>The specimen is measured for its frequency and resistance before the test .</p> <p>Place the specimen in the testing chamber and kept it at the temperature of $+85 \pm 5^{\circ}\text{C}$ and humidity of $85 \pm 5\%$ for 168 ± 6 hours . and then take the specimen out and measure its electrical performance after leaving for $1 \sim 2$ hours under the referee condition .</p> <p>(in accordance with MIL-STD-883F : 1004.7)</p>	
11-4. Temperature Cycle Test	<p>The specimen is measured for its frequency and resistance before the test .</p> <p>Subject the specimen to the 100 cycles of temperature ranges stated below .</p> <p>High temp . $+125 \pm 3^{\circ}\text{C}$ (15 ± 3 min).</p>  <p>Low temp. $-55 \pm 3^{\circ}\text{C}$ (15 ± 3 min).</p> <p>Measure its electrical performance after leaving it for $1 \sim 2$ hours under the referee condition .</p> <p>(in accordance with MIL-STD-883F : 1010.8)</p>	