

PRODUCT CHARACTERISTICS



V_{DSS}	750V
$R_{DS(ON)}$ Typ(@ $V_{GS}=15V$)	300m Ω
Q_g @typ	9nC
I_D	10A

APPLICATIONS

- *Switch Mode Power Supplies
- *High Voltage DC/DC Converters
- *Battery Chargers
- *Motor Drivers

FEATURE

- *Low On-Resistance With High Blocking Voltage
- *Low Capacitances With High -Speed Switching
- *Low Reverse Recovery(Qrr)
- *Easy to Parallel and Simple to Drive



ORDER INFORMATION

Order Codes		Package	Packing
Halogen-Free	Halogen		
N/A	MOT75CL300F	TO-220F	50 pieces/Tube

ABSOLUTE MAXIMUM RATINGS($T_c=25^{\circ}C$, unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DSS}	750	V
Gate-Source Voltage	V_{GSS}	-10/+22	V
Recommended Operation Voltage Of Gate to Source	V_{GSOP}	0/+18	V
Drain Current Continuous(@ $V_{GS}=15V$, $T_c=25^{\circ}C$)	I_D	10	A
Drain Current Continuous(@ $V_{GS}=15V$, $T_c=175^{\circ}C$)	I_D	7.5	A
Drain Current Pulsed(@ $V_{GS}=15V$, $T_c=25^{\circ}C$)	I_{DM}	18	A
Power Dissipation	P_D	36	W
Junction Temperature	T_J	+175	$^{\circ}C$
Storage Temperature	T_{STG}	-55~ +175	$^{\circ}C$

THERMAL CHARACTERISTICS

Parameter	Symbol	Typ	Unit
Junction to Case	R_{thJC}	4.1	$^{\circ}C/W$

■ ELECTRICAL CHARACTERISTICS ($T_C=25^{\circ}\text{C}$, unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Off characteristics						
Drain to Source Breakdown Voltage	V _{DSS}	V _{GS} =0V, I _D =500μA	750	-	-	V
Drain to Source Leakage Current	I _{DSS}	V _{DS} =750V, V _{GS} =0V	-	-	10	μA
Gate to Source Forward Leakage	I _{GSS}	V _{DS} =0V, V _{GS} =18V	-	-	250	nA
On characteristics						
Drain to Source On-Resistance	R _{DS(ON)}	V _{GS} =15V, I _D =4A	-	300	400	mΩ
		V _{GS} =15V, I _D =4A, T _J =175°C	-	280	-	mΩ
		V _{GS} =18V, I _D =4A	-	240	-	mΩ
		V _{GS} =18V, I _D =4A, T _J =175°C	-	250	-	mΩ
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250uA	2	2.5	4	V
Dynamic characteristics						
Gate capacitance	R _g	V _{AC} =25mV ,f=1.0MHz	-	24	-	Ω
Input Capacitance	C _{iss}	V _{DS} =40V, V _{GS} =0V f=1.0MHz	-	223	-	pF
Output Capacitance	C _{oss}		-	21	-	pF
Reverse Transfer Capacitance	C _{rss}		-	1	-	pF
Resistive Switching Characteristics						
Turn-on Delay Time	t _{d(ON)}	I _D =4A, V _{DS} =400V R _G =4.3Ω ,V _{GS} =0/15V	-	6.3	-	ns
Rise Time	t _r		-	17.4	-	ns
Turn-off Delay Time	t _{d(OFF)}		-	14.3	-	ns
Fall Time	t _f		-	14.8	-	ns
Total Gate Charge	Q _g	I _D =4 A, V _{DS} =400V V _{GS} =0/15V	-	9.0	-	nC
Gate to Source Charge	Q _{gs}		-	3.6	-	nC
Gate to Drain("Miller") Charge	Q _{gd}		-	1.2	-	nC
Source-Drain Diode Characteristics						
Continuous Source Current(Body Diode)	I _s		-	-	10	A
Diode Forward Voltage	V _{SD}	I _{SD} =1A, V _{GS} =0V	-	3.5	-	V
Reverse Recovery Time	t _{rr}	I _{SD} =4A, T _J =25 °C	-	25	-	ns
Reverse Recovery Charge	Q _{rr}		dI/dt=1200A/μs	-	9.2	-

■ TYPICAL CHARACTERISTICS




Figure 1: Output Characteristics($T_J=25^{\circ}\text{C}$)




Figure 2: Output Characteristics($T_J=175^{\circ}\text{C}$)




Figure 3: Typical Transfer Characteristics




Figure 4: Normalized On-Resistance vs Temperature




Figure 5: Normalized On-Resistance vs. Drain Current For Various Temperature




Figure 6: Normalized Threshold Voltage vs. Temperature

■ TYPICAL CHARACTERISTICS(Cont.)




Figure 7: Capacitance vs. Drain-Source Voltage




Figure 8: Body Diode Characteristics

■ TO-220F PACKAGE OUTLINE DIMENSIONS

