



Medical
electric
equipment



Power
Factor
Correction



World
wide



Safety
Approvals



EMI



Inrush
current
limiting



OCP



OVP



Remote
ON/OFF




Parallel
Operation



1U

G-series



■ Feature

Meets IEEE 802.3 and ANSIX3.263 standards .RoHS Compliant
 10/100/1000 Base-T, Surface Mount Type, Open Header
 Cable interface for isolation and low common mode emissions.
 Reflow soldering temperature: peak temperature $\leq 250^{\circ}\text{C}$ (10s)
 Reflow soldering frequency: It is recommended not to exceed 3 times
 Storage temperature range: -40°C to $+85^{\circ}\text{C}$
 Operating temperature range: 0°C to $+70^{\circ}\text{C}$

■ ROHS REACH marking


■ CE FCC marking



2 Specifications


Part No	OCL(uH min) @100KHz/0.1Vrms,8mA	Turns Ratio(3%)	Leakage primary@10KHz 0.1Vrms	DCR (Ω) Max	Cww(Pri:Sec) pF Typ	Isolation Voltage(AC Vrms 3S)	
G2406S	350UH	1:1	0.5uH max	0.9/1.2	35	1500V	
Part No	Insertion loss(dB max) 1-100MHz	Return Loss(dB Min)MHz			CMRR(dB min)MHz		Crosstalk(dB min)MHz
		1-30	40~60	60~100	1-60	60~100	1~100
G2406S	-1.2	-18	-16	-12	-40	-28	-40

3 Mechanical




※unit: mm

4 Schematic



5 packing



※unit: mm

※ Packaging quantity : 800pcs/roll 6400pcs/box

※ Outer box size: * L * * W * * H