



Features

- 650-Volt Schottky Rectifier
- Zero Reverse Recovery Current
- Zero Forward Recovery Voltage
- High-Frequency Operation
- Temperature-Independent Switching Behavior
- Extremely Fast Switching
- Positive Temperature Coefficient on V_F

Benefits


- Replace Bipolar with Unipolar Rectifiers
- Essentially No Switching Losses
- Higher Efficiency
- Reduction of Heat Sink Requirements
- Parallel Devices Without Thermal Runaway

Applications


- Switch Mode Power Supplies
- Power Factor Correction
- Motor Drives



Part Number	Package	Brand
HFFSP2065A	TO-220H-2L	HXY MOSFET



TO-220H-2L



Maximum Ratings ($T_c = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Value	Unit	Test Conditions
V_{RRM}	Repetitive Peak Reverse Voltage	650	V	
V_{RSM}	Surge Peak Reverse Voltage	650	V	
V_{DC}	DC Blocking Voltage	650	V	
I_F	Continuous Forward Current	20	A	$T_c = 125^\circ\text{C}$
I_{FRM}	Repetitive Peak Forward Surge Current	81	A	$T_c = 110^\circ\text{C}$, $t_p = 10$ ms, Half Sine Wave
I_{FSM}	Non-Repetitive Peak Forward Surge Current	123 104	A	$T_c = 25^\circ\text{C}$, $t_p = 10$ ms, Half Sine Wave $T_c = 150^\circ\text{C}$, $t_p = 10$ ms, Half Sine Wave
I_{FMax}	Non-Repetitive Peak Forward Surge Current	450	A	$T_c = 25^\circ\text{C}$, $t_p = 10$ μs , Pulse
P_{tot}	Power Dissipation	115	W	$T_c = 25^\circ\text{C}$
T_J, T_{stg}	Operating Junction and Storage Temperature	-55 to +175	$^\circ\text{C}$	



Electrical Characteristics

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions
V_F	Forward Voltage	1.35 1.5	1.5 -	V	$I_F = 20\text{ A}, T_J = 25^\circ\text{C}$ $I_F = 20\text{ A}, T_J = 175^\circ\text{C}$
I_R	Reverse Current	0.06 12	100 -	μA	$V_R = 650\text{ V}, T_J = 25^\circ\text{C}$ $V_R = 650\text{ V}, T_J = 175^\circ\text{C}$
Q_C	Total Capacitive Charge	24		nC	$V_R = 400\text{ V}, I_F = 10\text{ A}$ $dI/dt = 500\text{ A}/\mu\text{s}$ $T_J = 25^\circ\text{C}$
C	Total Capacitance	1000 91		pF	$V_R = 0\text{ V}, T_J = 25^\circ\text{C}, f = 1\text{ MHz}$ $V_R = 400\text{ V}, T_J = 25^\circ\text{C}, f = 1\text{ MHz}$
E_{ava}	Non-repetitive Avaranche Energy	220		mJ	$L=1\text{mH}$

Note: This is a majority carrier diode, so there is no reverse recovery charge.

Thermal Characteristics

Symbol	Parameter	Typ.	Unit
$R_{\theta\text{JC}}$	Thermal Resistance from Junction to Case	0.87	$^\circ\text{C}/\text{W}$

Typical Performance

Fig.1 $V_F - I_F$ Characteristics




Fig.2 $V_F - I_F$ Characteristics






Fig.3 $V_R - I_R$ Characteristics




Fig.4 $V_R - C_t$ Characteristics




Fig.5 Typical Transient Thermal Resistance vs. Pulse Width




Fig.6 Power Dissipation








Fig.7*3 Maximum peak forward current derating curve $I_P - T_c$



*3 Based on max V_f , max $R_{th(j-c)}$
Valid for switching of above 10kHz,
excluding D.C. curve.

Fig.8*4 Typical peak forward current derating curve $I_P - T_c$ (Not guaranteed)



*4 Based on typ V_f , typ $R_{th(j-c)}$
Typical value, not guaranteed
Valid for switching of above 10kHz,
excluding D.C. curve

Fig.9 Surge non-repetitive forward current vs. Pulse width (Sinusoidal waveform)




Fig.10 Typical capacitance store energy







Fig.11 Equivalent forward current curve



$$V_F = V_{th} + R_{diff} I_F$$


$$V_{th}(T_j) = a_0 + a_1 T_j$$
$$R_{diff}(T_j) = b_0 + b_1 T_j + b_2 T_j^2$$

Symbol	Typical Value	Unit
a_0	9.66E-01	V
a_1	-1.10E-03	V/°C
b_0	1.76E-02	Ω
b_1	3.73E-05	$\Omega/^\circ\text{C}$
b_2	3.84E-07	$\Omega/^\circ\text{C}^2$

T_j in °C; $-55^\circ\text{C} < T_j < 175^\circ\text{C}$; $I_F < 40\text{A}$




Package Information TO-220H-2L



Dimensions in millimeters

TO-220H-2L		
Dim	Min	Max
A	9.5	10.9
B	2.22	3.27
C	3.34	4.31
D	14.5	15.5
E	3.16	4.46
F	0.28	0.64
G	0.68	0.94
H	13.06	14.62
I	4.55	5.60
J	4.04	5.1
K	1.14	1.4
L	2.14	3.19

Recommended Solder Pad Layout



TO-220H-2L



Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.