



Photocoupler
Product Data Sheet
LTV-171G-TP-G

Spec No. :DS70-2019-0179
Effective Date: 03/31/2021
Revision: A

LITE-ON DCC

RELEASE

BNS-OD-FC001/A4

Photocoupler LTV-171G series

1. DESCRIPTION

The LTV-171G Photo Relay consists of a photo MOSFET optically coupled to an infrared light emitting diode. It is housed in a SOP4 package with 2.54-mm lead pitch. The LTV-171G is a bi-directional switch, which can replace mechanical relays in many applications. And its high on-state current maximum rating and low on-state resistance is suitable to control a power line.


1.1 Features

- Normally open (1-form-A)
- Operating temperature range: 85°C(max)
- Trigger LED current: 3 mA (max)
- Isolation voltage: 3750 Vrms (min)
- OFF-state output terminal voltage : 60 V (min)
- ON-state current : 1.6 A (max)
- ON-state resistance : 0.15 Ω (max)
- Safety standards
 - UL1577
 - CUL CA5A
 - VDE DIN EN60747-5-5 (VDE 0884-5)

1.3 Applications

- Battery Management System (BMS)
- Factory Automation (FA)
- Security Systems
- Measuring Instruments
- Smart Meters
- Mechanical relay replacements

1.2 Functional Diagram




- | | |
|------------|----------|
| 1. Anode | 3. Drain |
| 2. Cathode | 4. Drain |

Photocoupler LTV-171G series

2. PACKAGE DIMENSIONS

2.1 LTV-171G series




Notes:

- 1-digit year code, Example : 2010 = A
2-digit work week ranging from '01' to '53'
- Factory identification mark shall be marked (W: China -CZ, X: China -TJ)
- Output rating option (V_{OFF} / I_{ON}) :
"1G" : 60V / 1.6A
- "●" indicates halogen free option.
- "4" or "V" for VDE option.


Photocoupler LTV-171G series

3. TAPING DIMENSIONS

3.1 LTV-171G-TP



3.2 LTV-171G



Description	Symbol	Dimension in mm (inch)
Tape wide	W	12±0.3 (0.472)
Pitch of sprocket holes	P ₀	4±0.1 (0.157)
Distance of compartment	F	5.5±0.1 (0.217)
	P ₂	2±0.1 (0.079)
Distance of compartment to compartment	P ₁	8±0.1 (0.315)

3.3 Quantities Per Reel

Package Type	LTV-171G Series
Quantities (pcs)	3000

Photocoupler LTV-171G series

4. RATING AND CHARACTERISTICS

4.1 Absolute Maximum Ratings at Ta=25°C

Parameter		Symbol	Rating	Unit
Input	Forward Current	I_F	50	mA
	Peak Forward Current (100 μ s pulse, 100pps)	I_{FP}	1	A
	Reverse Voltage	V_R	5	V
	Input Power Dissipation	P_D	70	mW
	Junction Temperature	T_J	125	°C
Output	OFF-State Output Terminal Voltage	V_{OFF}	60	V
	ON-State Current	I_{ON}	1.6	A
	ON-State Current (pulsed) (t=100ms)	I_{ONP}	5	A
	Output Power dissipation	P_O	400	mW
	Junction Temperature	T_J	125	°C
Isolation Voltage (Note 1.)		V_{ISO}	3750	V
Operating Temperature		T_{opr}	-40 ~ +85	°C
Storage Temperature		T_{stg}	-55 ~ +125	°C
Soldering Temperature		T_{sol}	260 (For 10 seconds)	°C

4.2 RECOMMENDED OPERATING CONDITIONS (Note)

Characteristics	Symbol	Min.	Typ.	Max.	Unit
Supply Voltage	V_{DD}	-	-	48	V
Forward Current	I_F	5	10	25	mA
On-state Current	I_{ON}	-	-	1.3	A
Operating Temperature	T_{opr}	-20	-	65	°C

Note : The recommended operating conditions are given as a design guide necessary to obtain the intended performance of the device. Each parameter is an independent value. When creating a system design using this device, the electrical characteristics specified in this datasheet should also be considered.

Photocoupler LTV-171G series


4.3 ELECTRICAL OPTICAL CHARACTERISTICS at Ta=25°C

Parameter		Sym bol	Min.	Typ.	Max.	Unit	Test Condition
Input	Forward Voltage	V_F	-	1.18	1.5	V	$I_F=10\text{mA}$
	Reverse Current	I_R	-	-	10	μA	$V_R=5\text{V}$
Out -put	OFF-State Current	I_{OFF}	-	-	1	μA	$V_{OFF}=60\text{V}$
Coupled	Trigger LED Current	I_{FT}	-	0.8	3	mA	$I_{ON}=100\text{mA}$
	Return LED Current	I_{FC}	0.1	-	-	mA	$I_{OFF}=100\mu\text{A}$
	On Resistance	R_{on}	-	0.1	0.15	Ω	$I_F=5\text{mA}$, $I_{ON}=1.6\text{A}$, $t < 1\text{s}$
Transfer characteristics	Turn on time (Note 2.)	T_{ON}	-	1	3	ms	$I_F=5\text{mA}$, $V_{DD}=10\text{V}$, $I_L=100\text{mA}$
	Turn off time (Note 2.)	T_{OFF}	-	0.1	0.5	ms	
	Isolation Resistance	R_{ISO}	5×10^{10}	-	-	Ω	DC500V, R.H.40 ~ 60%

Note :

- AC For 1 Minute, R.H. = 40 ~ 60%. Isolation voltage shall be measured using the following method.
 - Short between anode and cathode on the primary side and between collector and emitter on the secondary side.
 - The isolation voltage tester with zero-cross circuit shall be used.
 - The waveform of applied voltage shall be a sine wave.

- Turn on / turn off time



Photocoupler LTV-171G series

5. CHARACTERISTICS CURVES




Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 On-State Current vs. On-State Voltage




Fig. 3 On-State Resistance vs. Ambient Temperature




Fig. 4 Trigger LED Current vs. Ambient Temperature




Fig. 5 Switching time vs. Forward Current

5




Fig. 7 Switching time vs. Ambient Temperature

Photocoupler
LTV-171G series




Fig. 8 Off-State Current vs. Ambient Temperature


Photocoupler LTV-171G series

6. TEMPERATURE PROFILE OF SOLDERING

6.1 IR Reflow soldering (JEDEC-STD-020E compliant)

One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than twice

Profile item	Conditions
Preheat	
- Temperature Min (T_{Smin})	150°C
- Temperature Max (T_{Smax})	200°C
- Time (min to max) (ts)	90±30 sec
Soldering zone	
- Temperature (T_L)	217°C
- Time (t_L)	60 sec
Peak Temperature (T_P)	260°C
Ramp-up rate	3°C / sec max.
Ramp-down rate	3~6°C / sec



Photocoupler LTV-171G series

6.2 Wave soldering (JEDEC22A111 compliant)


One time soldering is recommended within the condition of temperature.

Temperature: $260 \pm 0 / -5^\circ\text{C}$

Time: 10 sec.

Preheat temperature: 25 to 140°C

Preheat time: 30 to 80 sec.



6.3 Hand soldering by soldering iron

Allow single lead soldering in every single process. One time soldering is recommended.

Temperature: $380 \pm 0 / -5^\circ\text{C}$

Time: 3 sec max.

**Photocoupler
LTV-171G series**

7. NAMING RULE

LTV-171G-(1)-G

DEVICE PART NUMBER

(1) TAPING TYPE (TP, no suffix)
LTV-171G has tape and reel solution.
Please refer to orientation of taping on Page 3

(2) Halogen free option
Example : LTV-171G-TP-G

LTV171G(1)-V-G

DEVICE PART NUMBER

(1) TAPING TYPE (TP, no suffix)
LTV-171G has tape and reel solution.
Please refer to orientation of taping on Page 3

(2) VDE option

(3) Halogen free option
Example : LTV171GTP-V-G

8. NOTES

- LiteOn is continually improving the quality, reliability, function or design and LiteOn reserves the right to make changes without further notices.
- The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical application and instrumentation.
- For equipment/devices where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc, please contact our sales representatives.
- When requiring a device for any "specific" application, please contact our sales in advice.
- If there are any questions about the contents of this publication, please contact us at your convenience.
- The contents described herein are subject to change without prior notice.
- Immerge unit's body in solder paste is not recommended.