

■ **Features**

- Glass passivated chip
- Low reverse leakage current
- High surge current capability
- Fast reverse recovery time


<b>Reverse Voltage</b> 50-1000 V
<b>Forward Current</b> 4.0 A max

■ **Applications**

- General purpose use in AC/DC bridge full wave rectification

■ **Mechanical Data**

- Case: D3K
- Polarity symbols being marked on body
- Molding compound meets UL 94V-0 flammability rating
- RoHS-compliant, Solder plated, solderable per MIL-STD-750, Method 2026



■ **Marking**

- RD4UB(05~100)

■ **Maximum Ratings @ Ta = 25°C unless otherwise noted**

PARAMETER	SYMBOL	UNIT	RD4UB05	RD4UB10	RD4UB20	RD4UB40	RD4UB60	RD4UB80	RD4UB100	
Repetitive peak reverse voltage	$V_{RRM}$	V	50	100	200	400	600	800	1000	
Maximum RMS voltage	$V_{RMS}$	V	35	70	140	280	420	560	700	
Maximum DC blocking Voltage	$V_{DC}$	V	50	100	200	400	600	800	1000	
Maximum average output current@60Hz sine wave, resistance load	$I_{F(AV)}$	A	4.0							
Peak forward surge current 8.3 ms single half sine wave superimposed on rated load	$I_{FSM}$	A	120							
Peak forward surge current 1.0 ms single half sine wave superimposed on rated load		A	240							
Current squared time @1ms≤t<8.3ms Tj=25°C, Rating of per diode	$I^2t$	A <sup>2</sup> S	59.76							
Maximum reverse recovery time	$T_{rr}$	ns	150				250		500	
Storage temperature	$T_{stg}$	°C	-55~+150							
Junction temperature	$T_j$	°C	-55~+150							

■ **Electrical Characteristics @ Ta = 25°C unless otherwise noted**

PARAMETER	TEST CONDITIONS	SYMBOL	UNIT	RD4UB05	RD4UB10	RD4UB20	RD4UB40	RD4UB60	RD4UB80	RD4UB100
Maximum instantaneous forward voltage	$I_F=2.0A$	$V_F$	V	1.3						
Maximum DC reverse current at rated DC blocking voltage	$V_R=V_{DC}, T_j=25°C$	$I_R$	μA	5						
	$V_R=V_{DC}, T_j=100°C$	$I_R$		100						

■ **Characteristic Curve (Typical)**




FIG1. Derating Curve For Output Rectified Current




FIG2. Surge Forward Current Capability




FIG3. Typical Forward Characteristics





FIG4. Typical Reverse Characteristics


■ **Marking and packet information**



RD4UB\*\*\* : Marking Model      **TOS** : Brand Logo

Packaging information	
每盒	500PCS
每箱	5000PCS
脚长定制	支持

■ **D3K Package outline dimensions**



Dimensions in millimeters

■ **Notice**

XILONG reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product therein. xilong does not assume any liability arising out of the application or use of any product described herein.