

SD18X

1. Protection Solution To Meet

- IEC61000-4-2 (ESD) $\pm 30\text{kV}$ (air), $\pm 30\text{kV}$ (contact)
- IEC61000-4-4 (EFT) 40A (5/50ns)
- IEC61000-4-5 (Lightning) 9A (8/20 μs)

2. Features

- Low clamping voltage
- Working voltage: 18V
- Low leakage current
- RoHS compliant

3. Main Application

- Cell phone handsets and accessories
- Microprocessor based equipment
- Personal digital assistants (PDA' s)
- Notebooks, desktops, and servers
- Portable instrumentation

4. Mechanical Characteristics

- SOD-523 package
- Molding compound flammability rating: UL 94V-0
- Weight 0.5 milligrams (approximate)
- Lead finish: lead free

5. Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
ESD per IEC 61000-4-2 (Contact)	$V_{\text{ESD-Contact}}$	± 30	KV
ESD per IEC 61000-4-2 (Air)	$V_{\text{ESD-Air}}$	± 30	KV
Peak Pulse Power(8/20us)	P_{pp}	360	W
Operating Temperature	T_{OPT}	-55~+150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55~+150	$^\circ\text{C}$

6. Pinning information


Pin	Description	Simplified outline	Equivalent Circuit	Marking	Package
2	Uni			7U	SOD-523

7. Electrical Characteristics (Tamb=25°C)

Parameter	Symbols	Condition	Min	Typ	Max	Unit
Reverse Working Voltage	V_{RWM}				18	V
Breakdown Voltage	V_{BR}	$I_T = 1mA$	19.5			V
Reverse Leakage Current	I_R	$V_{RWM}=18V$			1	μA
Clamping Voltage	V_C	$I_{pp}=1A, t_p=8/20\mu s$			25	V
		$I_{pp}=9A, t_p=8/20\mu s$			40	V
Junction Capacitance	C_J	$V_R = 0V, f=1MHz$		60		pF

8. Electrical Parameters

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current@ V_{RWM}
I_T	Test Current
V_{BR}	Breakdown Voltage @ I_T
V_F	Forward Voltage
I_F	Forward Test Current



9. Typical Characteristics

Fig.1 8/20us Waveform Per IEC6100-4-5




Fig.2 Contact Discharge Current Waveform per IEC61000-4-2






Fig.3 Clamping Voltage Vs Peak Pulse Current




The curve above is for reference only.

10. Outline Drawing



11. Suggested Pad Layout



12. PACKAGE SPECIFICATIONS

Package	Reel Size	Reel DIA. (mm)	Q'TY/Reel (pcs)	Box Size (mm)	QTY/Box (pcs)	Carton Size (mm)	Q'TY/Carton (pcs)
SOD-523	7'	178	5000	190×190×190	75000	400×400×220	300,000

13.Important Notice and Disclaimer

Microdiode Electronics (Shenzhen) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design,purchase or use.

Microdiode Electronics (Shenzhen) makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does Microdiode Electronics (Shenzhen) assume any liability for application assistance or customer product design. Microdiode Electronics (Shenzhen) does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Microdiode Electronics (Shenzhen).

Microdiode Electronics (Shenzhen) products are not authorized for use as critical components in life support devices or systems without express written approval of Microdiode Electronics (Shenzhen).