



Technical Index:
 1. Temperature range: $-25^{\circ}\text{C}\sim 85^{\circ}\text{C}$.
 2. Rated voltage: 250V DC/AC(rms).
 3. Rated current: 3.0A.
 4. Contact resistance: $\leq 20\text{m}\Omega$.
 5. Withstanding voltage: 1000V AC/minute.
 6. Insulation resistance: $\geq 1000\text{M}\Omega$.

Part No	Pin	A	B
BX-HA2.54-2PWZ-GW	2	2.5	7.5
BX-HA2.54-3PWZ-GW	3	5.0	10.0
BX-HA2.54-4PWZ-GW	4	7.5	12.5
BX-HA2.54-5PWZ-GW	5	10.0	15.0
BX-HA2.54-6PWZ-GW	6	12.5	17.5
BX-HA2.54-7PWZ-GW	7	15.0	20.0
BX-HA2.54-8PWZ-GW	8	17.5	22.5
BX-HA2.54-9PWZ-GW	9	20.0	25.0
BX-HA2.54-10PWZ-GW	10	22.5	27.5
BX-HA2.54-11PWZ-GW	11	25.0	30.0
BX-HA2.54-12PWZ-GW	12	27.5	32.5
BX-HA2.54-13PWZ-GW	13	30.0	35.0
BX-HA2.54-14PWZ-GW	14	32.5	37.5
BX-HA2.54-15PWZ-GW	15	35.0	40.0
BX-HA2.54-16PWZ-GW	16	37.5	42.5
BX-HA2.54-17PWZ-GW	17	40.0	45.0

序号	品名	材质	制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	EMMA	料号 PART NO.	BX-HA2.54-NPWZ-GW	版本 REV.	A
						X.±0.50	X.±5°						
1	XH2.5 胶芯	PA66 UL94V-2 Beige				.X±0.20	.X°±3°	核准 APPROVAL	JADE	客户料号 CUTM.NO.			
2	XH2.5 弯针 端子	Copper Alloy/ Tin Plating				.XX±0.10	.XX°±1°	单位 UNITS	MM	比例 SCALE	1:1		