



技术要求Specification:

- 1、材质Material: PA66 UL94V-2;
- 2、塑件表面平整光洁, 无明显的毛刺、气泡、变形、浇口拉伤、缺料等不良现象。

Plastic surface smooth and clean, no obvious burrsbubbles, distortion, gate strain, lack of material and other undesirable phenomena.

Part No	Pin	A	B
BX-ZH1.5-2PJK	2	1.50	3.30
BX-ZH1.5-3PJK	3	3.00	4.80
BX-ZH1.5-4PJK	4	4.50	6.30
BX-ZH1.5-5PJK	5	6.00	7.80
BX-ZH1.5-6PJK	6	7.50	9.30
BX-ZH1.5-7PJK	7	9.00	10.80
BX-ZH1.5-8PJK	8	10.50	12.30
BX-ZH1.5-9PJK	9	12.00	13.80
BX-ZH1.5-10PJK	10	13.50	15.30
BX-ZH1.5-11PJK	11	15.00	16.80
BX-ZH1.5-12PJK	12	16.50	18.30
BX-ZH1.5-13PJK	13	18.00	19.80
BX-ZH1.5-14PJK	14	19.50	21.30
BX-ZH1.5-15PJK	15	21.00	22.80
BX-ZH1.5-16PJK	16	22.50	24.30
BX-ZH1.5-17PJK	17	24.00	25.80
BX-ZH1.5-18PJK	18	25.50	27.30
BX-ZH1.5-19PJK	19	27.00	28.80
BX-ZH1.5-20PJK	20	28.50	30.30

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	料号 PART NO.	版本 REV.	A
			X.±0.30	X.*±1*	EMMA	BX-ZH1.5-NPJK		
			.X±0.20		审核 CHECK	EVA	品名 TITLE	ZH1.5MM HOUSING
			.XX±0.10		核准 APPROVAL	JADE	客户料号 CUTM.NO.	
					单位 UNITS	MM	比例 SCALE	1:1
						JB Bossie (博锡)		