



VOLTAGE RANGE
50 to 1000 Volts
CURRENT
2.0 Ampere

FEATURES

- * Ideal for surface mount applications
- * Easy pick and place
- * Built-in strain relief
- * High surge current capability

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Terminals: Solder plated, solderable per MIL-STD-202F method 208 guranteed
- * Polarity: Color band denotes cathode end
- * Mounting position: Any
- * Weight: 0.063 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating 25°C ambient temperature unless otherwise specified.
Single phase half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

| TYPE NUMBER | S2A | S2B | S2D | S2G | S2J | S2K | S2M | UNITS |
|--|------------|-----|-----|-----|-----|-----|------|-------|
| Maximum Recurrent Peak Reverse Voltage | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Maximum RMS Voltage | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V |
| Maximum DC Blocking Voltage | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Maximum Average Forward Rectified Current | 2.0 | | | | | | | A |
| Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method) | 60 | | | | | | | A |
| Maximum Instantaneous Forward Voltage at 2.0A | 1.1 | | | | | | | V |
| Maximum DC Reverse Current Ta=25°C | 5.0 | | | | | | | μA |
| at Rated DC Blocking Voltage Ta=100°C | 100 | | | | | | | μA |
| Typical Junction Capacitance (Note 1) | 60 | | | | | | | pF |
| Typical Thermal Resistance R JA (Note 2) | 47 | | | | | | | °C/W |
| Operating and Storage Temperature Range Tj, Tstg | -55 — +150 | | | | | | | °C |

NOTES:

1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
2. Thermal Resistance from Junction to Ambient.

RATING AND CHARACTERISTIC CURVES

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3 - TYPICAL REVERSE CHARACTERISTICS




FIG.4-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT





FIG.5-TYPICAL JUNCTION CAPACITANCE




Soldering parameters

| Reflow Condition | | Pb-Free assembly (see as below) |
|---|-----------------------------------|------------------------------------|
| Pre Heat | -Temperature Min ($T_{s(min)}$) | +150°C |
| | -Temperature Max($T_{s(max)}$) | +200°C |
| | -Time (Min to Max) (ts) | 60-180 secs. |
| Average ramp up rate (Liquid us Temp (T_L) to peak) | | 3°C/sec. Max |
| $T_{s(max)}$ to T_L - Ramp-up Rate | | 3°C/sec. Max |
| Reflow | -Temperature(T_L)(Liquid us) | +217°C |
| | -Temperature(t_L) | 60-150 secs. |
| Peak Temp (T_P) | | +260(+0/-5)°C |
| Time within 5°C of actual Peak Temp (t_p) | | 30 secs. Max |
| Ramp-down Rate | | 6°C/sec. Max |
| Time 25°C to Peak Temp (T_P) | | 8 min. Max |
| Do not exceed | | +260°C |




Package Dimensions & Suggested Pad Layout

SMA



| SMA | | |
|----------------------|------|------|
| Dim | Min | Max |
| A | 2.40 | 2.79 |
| B | 3.99 | 4.50 |
| C | 1.32 | 1.47 |
| D | - | 0.20 |
| E | 4.93 | 5.28 |
| G | 0.15 | 0.31 |
| H | 0.76 | 1.52 |
| J | 1.98 | 2.29 |
| All Dimensions in mm | | |



| Dimensions | Value (in mm) |
|------------|---------------|
| C | 4.20 |
| G | 1.90 |
| X | 2.30 |
| X1 | 6.50 |
| Y | 2.00 |

Tape & reel specification

| Tape | | Symbol | Dimension (mm) |
|----------|--|-------------------|----------------|
| | | P0 | 4.00±0.20 |
| | | P1 | 4.00±0.20 |
| | | P2 | 2.00±0.20 |
| | | D0 | 1.60±0.20 |
| | | D1 | 1.60±0.20 |
| | | E | 1.75±0.20 |
| | | F | 5.50±0.15 |
| | | W | 12.00±0.25 |
| | | A0 | 2.75±0.20 |
| | | B0 | 5.25±0.20 |
| | | K0 | 2.45±0.25 |
| | | T | 0.20±0.10 |
| | | 7" Reel | |
| | | D3 | 55.0Min. |
| | | D4 | 14.0±2.5 |
| | | W1 | 14.0±2.5 |
| | | Quantity: 2000PCS | |
| 13" Reel | | D8 | 330.0±5.0 |
| | | D9 | 73.0Min. |
| | | D10 | 14.0±2.5 |
| | | W3 | 14.0±2.5 |
| | | Quantity: 5000PCS | |