

NCD3010RGB1



光电参数

Electro-Optical Characteristics

极限参数 (温度=25°C)



Absolute Maximum Ratings (Temperature=25°C)

参数名称 Parameter	符号 Symbol	数值 Rating	单位 Unit
正向电流 Forward Current	IF	20	mA
正向脉冲电流*Pulse Forward Current*	IFP	60	mA
反向电压 Reverse Voltage	VR	5	V
工作温度 Operating Temperature	TOPR	-30 ~ +85	°C
贮存温度 Storage Temperature	Tstg	-40 ~ +100	°C
功耗 Power Dissipation	R	52	mW
	UG/B	78	

* 注: 脉冲宽度 $\leq 0.1\text{ms}$, 占空比 $\leq 1/10$ * Note: Pulse Width $\leq 0.1\text{ms}$, Duty $\leq 1/10$

光电参数 (温度=25°C)



Electro-Optical Characteristics (Temperature=25°C)

参数名称 Parameter	符号 Symbol	条件 Condition	颜色 Color	最小值 Min.	典型值 Typ.	最大值 Max.	单位 Unit
反向电流 Reverse Current	IR	VR=5	R	-	-	10	μA
			UG/B			50	
正向电压 Forward Voltage	VF	IF=20mA	R	1.5	2.0	2.6	V
			UG	2.5	3.0	3.9	
			B	2.5	3.0	3.9	
主波长 Dominant Wavelength	λ_D		R	615	623	636	nm
			UG	515	528	536	
			B	460	470	478	
半波宽度 Spectrum Radiation Bandwidth	$\Delta\lambda$		R	-	15	-	nm
			UG		28		
			B	-	20	-	
光强 Luminous Intensity	IV	R	60	100	230	mcd	
		UG	100	260	330		
		B	40	90	120		
视角 View Angle	201/2	-		-	120	-	deg.

* 注 1: 光强偏差 $\pm 15\%$; 压降偏差 $\pm 0.1\text{V}$; (X,Y)坐标偏差 ± 0.01 ; 单色光波长偏差 $\pm 1\text{nm}$ 。

* Note1: Tolerance on each Luminous Intensity bin is $\pm 15\%$; Tolerance on each Forward Voltage bin is $\pm 0.1\text{V}$; Tolerance on each Hue(X,Y) bin is ± 0.01 ; Tolerance of Dominant Wavelength $\pm 1\text{nm}$.


* 注 2: 以上参数仅供参考, 请以实物标签为准。我司给出的参数均由国星测试系统测得。

* Note2: The parameters above are only for your reference. In case of any discrepancy, please adhere to the label of our actual products. All parameters are tested by the standard testing system of NationStar.

包装


Packaging

载带 Carrier Tape



单位: mm, 未注公差: ± 0.1 mm
All dimensions in mm, tolerances unless mentioned is ± 0.1 mm.

编带细节 Details Of Carrier Tape



A: 盖带, 100 mm; B: 引导, 空带, 300mm; C: 编载产品 3000 只; D: 尾部, 空带, 200mm
A: Top Cover Tape, 100mm; B: Leader, Empty, 300mm; C: 3000 Lamps Loaded; D: Trailer, Empty, 200mm.

外形尺寸

Outline Dimension

