



HE15R065H6DHL

High performance field stop IGBT power transistor

Product features/产品特点



- Top side cooling technology
顶部散热技术
- Advanced trench+FS IGBT technology
先进的沟槽栅+场截止技术
- Low gate charge
低栅极电荷
- Short-circuit withstand time, $t_{sc} \leq 5\mu s$ (@150°C)
短路承受时间 $t_{sc} \leq 5\mu s$ (@150°C)
- Maximum junction temperature: $T_{vj,MAX} = 175^\circ C$
最高结温 $T_{vj,MAX} = 175^\circ C$
- $V_{CE(sat)}$ with positive temperature coefficient (PTC)
具有正温度系数的 V_{CEsat}
- Halogen free, RoHS compliant
无卤, 符合RoHS

Applications/应用领域

- General purpose inverters
通用变频器
- Motor drives
电机驱动

Key performance parameters/关键性能参数

Parameter/参数	Value/值	Unit/单位
V_{CE}	650	V
I_C	15	A
$V_{CEsat,typ}$	1.5	V



Package parameters/封装信息

Type/型号	Package/封装	Marking/标识	Packaging method/包装方式
HE15R065H6DHL	TSC263-4L	HE15R065DHL	Tape and reel/卷带包装

HE15R065H6DHL

High performance field stop IGBT power transistor



1. Maximum ratings at $T_{vj}=25^{\circ}\text{C}$, unless otherwise specified.

最大额定值 默认 $T_{vj}=25^{\circ}\text{C}$ 除非另有说明

Table 1 Characteristic values/特征值

Parameter 参数	Symbol 符号	Test condition 测试条件	Value 值	Unit 单位
Collector-to-emitter voltage 集电极-发射极电压	V_{CE}	$T_{vj}\geq 25^{\circ}\text{C}$	650	V
DC Collector current 集电极连续直流电流	I_C^1	$T_C=25^{\circ}\text{C}$	30	A
		$T_C=100^{\circ}\text{C}$	15	
Pulsed Collector current 集电极脉冲电流	I_{Cpuls}^2		45	A
Turn off safe operating area 关断安全工作区	— ²	$V_{CE}\leq 650\text{V}, T_{vj}\leq 175^{\circ}\text{C}$	45	A
Diode continuous forward current 二极管连续直流电流	I_F^1	$T_C=25^{\circ}\text{C}$	30	A
		$T_C=100^{\circ}\text{C}$	15	
Diode pulsed current 二极管脉冲电流	I_{Fpuls}^2		45	A
Gate-emitter voltage 栅极-发射极峰值电压	V_{GE}		± 20	V
Transient gate-emitter voltage 瞬态栅极-发射极电压	V_{GE}	$t_p\leq 10\mu\text{s}, D<0.01$	± 30	V
Short circuit withstand time 短路耐量	t_{sc}	$V_{GE}=15\text{V}, V_{CC}\leq 400\text{V}, T_{vj}=150^{\circ}\text{C}$	5	μs
Power dissipation 总耗散功率	P_{tot}	$T_C=25^{\circ}\text{C}$	195	W
		$T_C=100^{\circ}\text{C}$	97	

1. Limited by $T_{vj,MAX}$ /受限于最高结温

2. Pulse width t_p limited by $T_{vj,MAX}$ /脉宽受限于最大结温



2. Package 封装

Table 2 Characteristic values/特征值

Parameter 参数	Symbol 符号	Test condition 测试条件	Value/值			Unit 单位
			Min.	Typ.	Max.	
Operating junction temperature 可工作结温	T_{vj}		-40		175	°C
Storage temperature range 储存温度	T_{stg}		-55		150	°C
Soldering temperature, reflow solderin 焊接温度, 回流焊	T_{sold}	Reflow MSL1			260	°C
IGBT thermal resistance, junction-to-case IGBT 芯片到壳热阻	$R_{th(j-C)}$				0.77	K/W
Diode thermal resistance, junction-to-case 二极管芯片到壳热阻	$R_{th(j-C)}$				1.54	K/W
Thermal resistance, junction-to-ambient 结到环境热阻	$R_{th(j-A)}$				61	K/W

HE15R065H6DHL

High performance field stop IGBT power transistor



3. Static electrical characteristic at $T_{vj}=25^{\circ}\text{C}$, unless otherwise specified.

静态电气特性 默认 $T_{vj}=25^{\circ}\text{C}$ 除非另有说明

Table 3 Characteristic values/特征值

Parameter 参数	Symbol 符号	Test condition 测试条件	Value/值			Units 单位
			Min.	Typ.	Max.	
Collector-Emitter breakdown voltage 集电极-发射极击穿电压	$V_{(BR)CES}$	$V_{GE}=0V, I_C=0.25mA, T_{vj}=25^{\circ}\text{C}$	650			V
Collector-Emitter Saturation voltage 集电极-发射极饱和压降	V_{CEsat}	$V_{GE}=15V, I_C=15A$		1.5	2.1	V
		$T_{vj}=175^{\circ}\text{C}$		1.9		
Gate threshold voltage 门极开启阈值电压	V_{GEth}	$V_{GE}=V_{CE}, I_C=1mA$	5.0	5.5	6.5	V
Diode forward voltage 二极管正向导通压降	V_F	$V_{GE}=0V, I_F=15A$		1.38	1.6	V
		$T_{vj}=175^{\circ}\text{C}$		1.18		
Gate to Emitter Leakage current 门极-发射极漏电流	I_{GES}	$V_{GE}=20V, V_{CE}=0V$			500	nA
		$V_{GE}=-20V, V_{CE}=0V$			-500	
Zero gate voltage collector current 集电极-发射极漏电	I_{CES}	$V_{CE}=650V, V_{GE}=0V$			10	μA

4. Dynamic electrical characteristic at $T_{vj}=25^{\circ}\text{C}$, unless otherwise specified.

动态电气特性 默认 $T_{vj}=25^{\circ}\text{C}$ 除非另有说明

Table 4 Characteristic values/特征值

Parameter 参数	Symbol 符号	Test condition 测试条件	Value/值			Units 单位
			Min.	Typ.	Max.	
Input capacitance 输入电容	C_{ies}	$V_{GE}=0V, V_{CE}=25V,$ $f=1MHz$		507		pF
Output capacitance 输出电容	C_{oes}			35		
Reverse transfer capacitance 反向传输电容	C_{res}			6		
Total gate charge 门极电荷	Q_g	$V_{GE}=15V,$ $I_C=15A, V_{CC}=480V,$		24		nC



5. Switching characteristic inductive load at $T_{vj}=25^{\circ}\text{C}$, unless otherwise specified.

开关特性感性负载 默认 $T_{vj}=25^{\circ}\text{C}$ 除非另有说明

Table 5 IGBT Characteristic values/IGBT特征值

Parameter 参数	Symbol 符号	Test condition 测试条件		Value/值			Units 单位
				Min.	Typ.	Max.	
Turn-on delay time 开启延迟时间	t _{d(on)}	V _{GE} =0/15V V _{CC} =400V I _C =15A R _{G(on)} =30Ω R _{G(off)} =30Ω	T _{vj} =25°C		31		ns
			T _{vj} =175°C		32		
Rise time 上升时间	t _r		T _{vj} =25°C		35		ns
			T _{vj} =175°C		36		
Turn-off delay time 关闭延迟时间	t _{d(off)}		T _{vj} =25°C		79		ns
			T _{vj} =175°C		100		
Fall time 下降时间	t _f		T _{vj} =25°C		66		ns
			T _{vj} =175°C		75		
Turn-on switch loss 单次开启损耗	E _{on}		T _{vj} =25°C		0.43		mJ
			T _{vj} =175°C		0.65		
Turn-off switch loss 单次关闭损耗	E _{off}		T _{vj} =25°C		0.34		mJ
			T _{vj} =175°C		0.37		
Total switching energy 总开关损耗	E _{ts}		T _{vj} =25°C		0.77		mJ
			T _{vj} =175°C		1.02		





Table 6 Diode Characteristic values/二极管特征值





Parameter 参数	Symbol 符号	Test condition 测试条件		Value/值			Units 单位
				Min.	Typ.	Max.	
Diode Reverse Recovery Time 二极管反向恢复时间	t _{rr}	I _F =15A V _R =400V di _F /dt=-200A/μs	T _{vj} =25°C		59		ns
			T _{vj} =175°C		144		
Diode Reverse Recovery Charge 二极管反向恢复电量	Q _{rr}		T _{vj} =25°C		200		nC
			T _{vj} =175°C		501		
Peak reverse recovery current 反向恢复峰值电流	I _{rrm}		T _{vj} =25°C		8		A
			T _{vj} =175°C		11		







6. Characteristics diagrams

特性曲线










7. Package outline

封装外形

Figure 1. Outline TSC263-4L, dimensions in mm/ TSC263-4L外形尺寸 (毫米)



DIM SYMBOL	MIN.	TYP.	MAX.	DIM SYMBOL	MIN.	TYP.	MAX.
*A	4.40	4.50	4.60	*E	9.45	9.60	9.75
A1	1.75	1.80	1.85	E1	6.15	6.35	6.55
A2	2.65	2.70	2.75	e	5.08 BSC		
*b	1.22	1.27	1.32	*H	16.02	16.22	16.42
*b1	1.22	1.27	1.32	*L	1.70	1.90	2.10
*c	0.45	0.50	0.55	*L2	0.05	0.10	0.15
*D	10.95	11.10	11.25	*L3	1.10	1.30	1.50
D1	9.50	9.60	9.70	L4	2.27 REF		
*D2	9.00	9.20	9.40	L5	4.15	4.35	4.55
				Θ	0°	-	8°

NOTES:

- ALL DIMENSIONS ARE IN MILLIMETER. ANGLES ARE IN DEGREE.
- DIMENSION "D" DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSIONS. INTERLEAD FLASH SHALL NOT EXCEED 0.150 MM PER SIDE. DIMENSION "E" DOES NOT INCLUDE MOLD FLASH, GATE BURRS, THE GATE BURRS SHALL NOT EXCEED 0.15MM.
- DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF THE PLASTIC BODY.

注:

- 所有尺寸均以毫米为单位。角度以度为单位。
- 尺寸 D 不包括引脚间飞边或突出物。引脚间飞边在每侧不得超过0.15mm。尺寸 E 不包括模具飞边、浇口残余物，浇口残余物不得超过0.15mm。
- 尺寸 D、E 是在塑胶本体的最外极限确定的，不包括模具飞边、连接条残余、浇口残余和引脚间飞边，但包括塑胶本体顶部和底部之间可能存在的任何不匹配或错位。



8. Revision history
修订历史

Table 7 Date and version number/日期与版本号

Date日期	Revision版本	Changes更改内容
2025-12-15	Rev.G1.0	Target Datasheet (目标规格书)

9. Matters needing attention
注意事项

Important Technical Guidance, Application Policy, and Copyright Notice
重要技术指南、应用规范与版权声明

[Data and Design Guidance]

The information provided herein, including typical values and application examples, serves as technical guidance only and should not be construed as a formal guarantee of product characteristics. This documentation is intended for qualified engineering personnel, who bear the ultimate responsibility for evaluating the product's suitability for their specific application and compliance with all industry standards.

[Copyright and Revision Management]

We reserve all rights to the intellectual property contained within this document, and unauthorized reproduction is prohibited. For the sake of continuous improvement, the content is subject to change without prior notice. Designers are obligated to consult and use the latest revision of this datasheet to ensure optimal performance and accuracy in their final product.

[Application Safety and Intellectual Property]

Our product supply does not confer any license or right under any third-party intellectual property. Customers are fully responsible for the patent clearance and functional safety of their end application. Furthermore, this product is not intended for use in life-critical or high-risk systems (such as Class III medical devices or aerospace control) unless explicitly approved by us through a dedicated high-reliability agreement.

【数据与设计指引】

本文件中提供的所有信息，包括任何典型值和应用示例，仅作为技术指引，不应被视为对产品特性的正式保证。本资料专供具备资质的工程技术人员使用，客户的技术部门应对产品在特定应用中的适用性和对所有行业标准的符合性负最终评估责任。

【版权与版本管理】

本文件的所有知识产权和版权均归我方所有，严禁未经授权的复制与传播。为持续优化产品性能，本文件内容可能随时变更，恕不另行通知。设计人员有义务查阅并使用最新的版本数据手册，以确保设计准确性并实现最佳系统性能。

【应用安全与知识产权】

我方提供本产品，不应被视为授予任何第三方知识产权的许可或权利。客户应对其终端应用中的功能安全性、系统鲁棒性以及不侵犯任何第三方专利负全部责任。此外，本产品未被设计或认证用于生命维持或极高风险的关键系统。在将本产品用于此类高可靠性应用之前，客户必须设计充分的冗余和安全机制，并事先与我方签署专门的高可靠性供货协议。

<http://www.hmwsemi.com/>