

CMP15N65A/CMB15N65A/CMI15N65A/CMF15N65A

650V, 0.6Ω typ., 15A N-Channel MOSFET

General Description

These Power MOSFETs are produced using Cmos's proprietary, planar stripe, DMOS technology. These devices are well suited for active power factor correction and switching mode power supplies.

Features

- 100% avalanche tested
- Improved dv/dt capability
- RoHS Compliant


Product Summary

BVDSS	R _{DS(on)} max.	ID
650V	680mΩ	15A

Applications

- PFC
- Power Supply

TO-220/263/262/220F Pin Configuration



Absolute Maximum Ratings

Symbol	Parameter	220/263/262	220F	Units
V _{DS}	Drain-Source Voltage	650		V
V _{GS}	Gate-Source Voltage	±30		V
I _D @T _C =25°C	Continuous Drain Current	15	15*	A
I _D @T _C =100°C	Continuous Drain Current	10	10*	A
I _{DM}	Pulsed Drain Current	60	60*	A
EAS	Single Pulse Avalanche Energy (Note 1)	1210		mJ
P _D @T _C =25°C	Total Power Dissipation	250	60	W
T _{STG}	Storage Temperature Range	-55 to 150		°C
T _J	Operating Junction Temperature Range	-55 to 150		°C

* Drain current limited by maximum junction temperature.

Thermal Data

Symbol	Parameter	220/263/262	220F	Unit
R _{θJA}	Thermal Resistance Junction-ambient Max.	62.5	65	°C/W
R _{θJC}	Thermal Resistance Junction-case Max.	0.5	2.08	°C/W

Electrical Characteristics ($T_J=25^{\circ}\text{C}$, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	650	---	---	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=10V, I_D=7A$	---	0.6	0.68	Ω
$V_{GS(th)}$	Gate Threshold Voltage	$V_{GS}=V_{DS}, I_D=250\mu A$	2.0	---	4.0	V
I_{DSS}	Drain-Source Leakage Current	$V_{DS}=650V, V_{GS}=0V$	---	---	1	μA
I_{GSS}	Gate-Source Leakage Current	$V_{GS}=\pm 30V, V_{DS}=0V$	---	---	± 100	nA
gfs	Forward Transconductance	$V_{DS}=15V, I_D=7A$	---	15	---	S
R_g	Gate Resistance	$V_{DS}=0V, V_{GS}=0V, f=1\text{MHz}$	---	2.9	---	Ω
Q_g	Total Gate Charge	$I_D=14A$	---	51	---	nC
Q_{gs}	Gate-Source Charge	$V_{DD}=400V$	---	11	---	
Q_{gd}	Gate-Drain Charge	$V_{GS}=10V$	---	19	---	
$T_{d(on)}$	Turn-On Delay Time	$V_{DD}=300V$ $V_{GS}=10V$ $R_G=25\Omega, I_D=14A$	---	40	---	ns
T_r	Rise Time		---	58	---	
$T_{d(off)}$	Turn-Off Delay Time		---	150	---	
T_f	Fall Time		---	40	---	
C_{iss}	Input Capacitance	$V_{DS}=25V, V_{GS}=0V, f=1\text{MHz}$	---	1940	---	pF
C_{oss}	Output Capacitance		---	170	---	
C_{riss}	Reverse Transfer Capacitance		---	14	---	

Diode Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_S	Continuous Source Current	$V_G=V_D=0V$, Force Current	---	---	15	A
I_{SM}	Pulsed Source Current		---	---	60	A
V_{SD}	Diode Forward Voltage	$V_{GS}=0V, I_S=14A, T_J=25^{\circ}\text{C}$	---	0.84	1.4	V

Note :







1.The EAS data shows Max. rating . The test condition is $V_{DD}=100V, V_{GS}=10V, L=20\text{mH}, I_{AS}=11A$.

This product has been designed and qualified for the consumer market.

Cmos assumes no liability for customers' product design or applications.

Cmos reserves the right to improve product design ,functions and reliability without notice.Please refer to the latest version of specification.


Typical Characteristics



Package Dimension

TO-220

Unit :mm




DIM	MILLIMETERS
A	10.0±0.3
A1	8.64±0.2
A2	1.15±0.1
A3	5.0±0.2
B	15.8±0.4
B1	13.2±0.3
C	4.56±0.1
C1	1.3±0.2
D	0.8±0.2
E	3.6±0.2
F	2.95±0.3
G	6.5±0.3
H	0.5±0.1
K	3.1±0.2
L	13.2±0.4
M	1.25±0.1
N	2.54±0.1
P	2.4±0.3
Q	9.0±0.3
T	W:0.35
DIA	⊙1.5(deep 0.2)

Package Dimension

TO-263

Unit :mm




DIM	MILLIMETERS
A	9.8±0.2
a	7.4±0.4
B	4.5±0.2
b1	1.3±0.05
b2	2.4±0.2
H	15.5±0.3
h	1.54±0.2
h1	10.5±0.2
h2	9.2±0.1
h3	1.54±0.2
h4	2.7±0.2
L	2.4±0.2
1	1.3±0.1
11	0.8±0.1
12	1.3±0.1
13	0.5±0.1
N	2.54±0.1
R	0.5R±0.05

Package Dimension

TO-262

Unit :mm




DIM	MILLIMETERS
A	9.98±0.2
a	7.4±0.4
B	4.5±0.2
b1	1.3±0.05
b2	2.4±0.2
H	23.9±0.3
h	3.1±0.2
h1	9.16±0.2
h2	13.2±0.2
L	0.5±0.1
l1	1.3±0.1
l2	0.8±0.1
N	2.45±0.1

Package Dimension

TO-220F

Unit :mm



DIM	MILLIMETERS
A	10.16±0.3
A1	7.00±0.1
A2	3.3±0.2
A3	9.5±0.2
B1	15.87±0.3
B2	4.7±0.2
B3	6.68±0.4
C	3.3±0.2
C1	12.57±0.3
C2	10.02±0.5
D	2.54±0.05
D1	1.28±0.2
D2	0.8±0.1
K	3.1±0.3
E1	2.54±0.1
E3	0.5±0.1
E4	2.76±0.2
DIA	⊙1.5 (deep 0.2)