

Multilayer Chip Varistor (MLV) Datasheet



Features

- Leadless , Size 1206
- Inherent Bi-directional Clamping
- High surge suppress capability, Low Leakage Current
- Low Inductance, Fast Response
- Excellent Temperature Coefficient
- Operating temperature: -40°C to +125°C
- RoHS compliant & Lead-Free & Halogen Free


Applications

- Suppression of Inductive Switching or Other Transient Events
- Provides On-Board Transient Voltage Protection for ICs, CMOS and MOSFET
- Used to Help Achieve Electromagnetic Compliance of End Products
- Portable equipment protection, such as mobile phone, TV, etc.

Part Number Code



Recommended Soldering Conditions



Profile Feature		Pb-Free Assembly
Pre-heat	Temperature Min (Ts(min))	+150°C
	Temperature Max(Ts(max))	+200°C
	Time (Min to Max) (ts)	60-180 secs.
Average ramp up rate (Liquid us Temp (T _L) to peak)		3°C /sec. Max
T _{S(max)} to T _L - Ramp-up Rate		3°C /sec. Max
Reflow	Temperature(T _p)(Liquid us)	+217°C
	Temperature(t _L)	60-150 secs.
Peak Temp (T _p)		+240°C to +260°C
Time within 5°C of actual Peak Temp (t _p)		15-30secs
Ramp-down Rate		6°C /sec. Max
Time 25°C to Peak Temp (T _p)		8 min. Max
Do not exceed		+260°C



Note 1: All temperature refer to topside of the package, measured on the package body surface.
Note 2: If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.

● **Electrical Characteristics** (Ta=25°C Unless otherwise specified)

Part Number	Varistor Voltage	Max. Allowable Voltage		Leakage Current @ V _{DC}	Max. Clamping Voltage @8/20μs		Peak Single Pulse Transient Current @8/20μs	Max. Energy @10/1000μs	Typical Capacitance (Reference) @1KHZ	Response Time
	V _{1mA} (V)	V _{AC} (V)	V _{DC} (V)	(μA)	I _P (A)	V _C (V)	I(A)	(J)	(pF)	(ns)
HMLV1206-240G	21.6~26.4	14	18	50	5	38	120	0.8	1450	5

Note 1: Typical capacitance value tolerance 40%

● **Ratings And Characteristics Curves** (Ta=25°C Unless otherwise specified)



● **Reliability Test**

Characteristic	Test method and description		
High Temperature Storage	The specimen shall be subjected to 125 °C for 1000 hours in a thermostatic bath without load and then stored at room temperature and humidity for 1 to 2 hours. The change of varistor voltage shall be within 10%.		
Temperature Cycle	The temperature cycle of specified temperature shall be repeated five times and then stored at room temperature and humidity for one two hours. The change of varistor voltage shall be within 10%and mechanical damage shall be examined.		
High Temperature Load	After being continuously applied the maximum allowable voltage at 125 °C for 1000hours, the specimen shall be stored at room temperature and humidity for one or hours, the change of varistor voltage		
Damp Heat Load/Humidity Load	The specimen should be subjected to 40°C,90 to 95%RH environment, and the maximum allowable voltage applied for 1000 hours, then stored at room temperature and humidity for one or two hours. The change of varistor voltage shall be within 10%		
Low Temperature Storage	The specimen should be subjected to -40 °C , without load for 1000 hours and then stored at room temperature for one two hours. The change of varistor voltage shall be within 10%.		

● Environmental Specification

Storage temperature:	-25°C to +45°C
Storage Conditions:	Light-proof, Hermetically Sealed, Moisture-proof; The components should be left in their original packing to avoid soldering problems due to oxidized contacts.
Relative humidity:	< 75 % annual average, < 95 % on max. 30 days in a year.
Storage period	The components should be employed within 24 months after delivery

● Physical Dimensions

The diagram shows three views of the multilayer chip varistor: a top view, a side view, and a perspective view. The top view is a rectangle with length L and width W. The side view is a rectangle with height H and length L1. The perspective view shows the 3D shape with dimensions L, W, H, and L1. The L1 dimension is the distance from the edge of the component to the center of the terminal pads.

Part Number	L	W	H	L1
	(mm)	(mm)	(mm)	(mm)
HMLV1206-240G	3.20±0.30	1.60±0.30	1.60(max)	0.35±0.25

● Ordering Information

PACKAGE	Part Number	DELIVERY MODE	MPQ(PCS)
1206	HMLV1206-240G	7" REEL	3,000

● Packaging Information

The diagram shows the dimensions of the component in its packaging. The top view shows a row of components with dimensions P0, P2, D, B, W, F, P, A, A, B. The side view shows dimensions B0, K0, T. The bottom view shows dimensions A0. The section A-A and B-B are indicated.

Symbol	Dimensions
	(mm)
W	8±0.1
A0	1.88±0.1
B0	3.5±0.1
K0	1.27±0.1
P	4.0±0.1
F	3.5±0.1
E	1.75±0.1
D	1.5±0.1
P0	4.0±0.1
P2	2.0±0.1
T	0.2±0.05