

## Product Summary



- $V_{DS}$  150V
- $I_D$  35A
- $R_{DS(ON)}$  (at  $V_{GS}=10V$ )  $<40m\Omega$
- 100% EAS Tested
- 100%  $\nabla V_{DS}$  Tested

## General Description

- Vertical Double-diffused MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low  $R_{DS(ON)}$
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

## Applications

- Power switching application
- Uninterruptible power supply
- DC-DC convertor
- Motor drivers



| Absolute Maximum Ratings $T_C = 25^\circ\text{C}$ , unless otherwise noted |                |               |                  |
|----------------------------------------------------------------------------|----------------|---------------|------------------|
| Parameter                                                                  | Symbol         | Value         | Unit             |
| Drain-Source Voltage                                                       | $V_{DSS}$      | 150           | V                |
| Continuous Drain Current                                                   | $I_D$          | 35            | A                |
| Pulsed Drain Current (note1)                                               | $I_{DM}$       | 140           | A                |
| Gate-Source Voltage                                                        | $V_{GSS}$      | $\pm 20$      | V                |
| Single Pulse Avalanche Energy (note1)                                      | $E_{AS}$       | 191           | mJ               |
| Avalanche Current (note1)                                                  | $I_{AS}$       | 31            | A                |
| Repetitive Avalanche Energy (note1)                                        | $E_{AR}$       | 124           | mJ               |
| Power Dissipation ( $T_C = 25^\circ\text{C}$ )                             | $P_D$          | 160           | W                |
| Operating Junction and Storage Temperature Range                           | $T_J, T_{stg}$ | $-55\sim+150$ | $^\circ\text{C}$ |

| Thermal Resistance                      |            |       |                    |
|-----------------------------------------|------------|-------|--------------------|
| Parameter                               | Symbol     | Value | Unit               |
| Thermal Resistance, Junction-to-Case    | $R_{thJC}$ | 1.2   | $^\circ\text{C/W}$ |
| Thermal Resistance, Junction-to-Ambient | $R_{thJA}$ | 60    |                    |

**Specifications**  $T_J = 25^\circ\text{C}$ , unless otherwise noted

| Parameter                               | Symbol        | Test Conditions                                               | Value |      |           | Unit       |
|-----------------------------------------|---------------|---------------------------------------------------------------|-------|------|-----------|------------|
|                                         |               |                                                               | Min.  | Typ. | Max.      |            |
| Static                                  |               |                                                               |       |      |           |            |
| Drain-Source Breakdown Voltage          | $V_{(BR)DSS}$ | $V_{GS} = 0V, I_D = 250\mu A$                                 | 220   | --   | --        | V          |
| Zero Gate Voltage Drain Current         | $I_{DSS}$     | $V_{DS} = 220V, V_{GS} = 0V, T_J = 25^{\circ}C$               | --    | --   | 1         | $\mu A$    |
|                                         |               | $V_{DS} = 220V, V_{GS} = 0V, T_J = 125^{\circ}C$              | --    | --   | 100       |            |
| Gate-Source Leakage                     | $I_{GSS}$     | $V_{GS} = \pm 20V, V_{DS} = 0V$                               | --    | --   | $\pm 100$ | nA         |
| Gate-Source Threshold Voltage           | $V_{GS(th)}$  | $V_{DS} = V_{GS}, I_D = 250\mu A$                             | 2.0   | --   | 4.0       | V          |
| Drain-Source On-Resistance (Note4)      | $R_{DS(on)}$  | $V_{GS} = 10V, I_D = 20A$                                     | --    | 30   | 40        | m $\Omega$ |
| Forward Transconductance (Note4)        | $g_{fs}$      | $V_{DS} = 25V, I_D = 20A$                                     | --    | 16   | --        | S          |
| Dynamic                                 |               |                                                               |       |      |           |            |
| Input Capacitance                       | $C_{iss}$     | $V_{GS} = 0V,$<br>$V_{DS} = 25V,$<br>$f = 1.0MHz$             | --    | 2800 | --        | pF         |
| Output Capacitance                      | $C_{oss}$     |                                                               | --    | 355  | --        |            |
| Reverse Transfer Capacitance            | $C_{rss}$     |                                                               | --    | 101  | --        |            |
| Total Gate Charge                       | $Q_g$         | $V_{DD} = 160V, I_D = 40A,$                                   | --    | 154  |           | nC         |
| Gate-Source Charge                      | $Q_{gs}$      |                                                               | --    | 13   | --        |            |
| Gate-Drain Charge                       | $Q_{gd}$      |                                                               | --    | 58   | --        |            |
| Turn-on Delay Time                      | $t_{d(on)}$   | $V_{DD} = 160V, I_D = 40A,$<br>$V_{GS} = 15V, R_G = 25\Omega$ | --    | 46   | --        | ns         |
| Turn-on Rise Time                       | $t_r$         |                                                               | --    | 54   | --        |            |
| Turn-off Delay Time                     | $t_{d(off)}$  |                                                               | --    | 360  | --        |            |
| Turn-off Fall Time                      | $t_f$         |                                                               | --    | 96   | --        |            |
| Drain-Source Body Diode Characteristics |               |                                                               |       |      |           |            |
| Continuous Source Current               | $I_{SD}$      | Integral PN-diode in MOSFET                                   | --    | --   | 35        | A          |
| Pulsed Source Current                   | $I_{SM}$      |                                                               | --    | --   | 140       |            |
| Body Forward Voltage                    | $V_{SD}$      | $I_S = 20A, V_{GS} = 0V$                                      | --    | --   | 1.4       | V          |
| Reverse Recovery Time                   | $t_{rr}$      | $V_{GS} = 0V, I_F = 10A,$<br>$di_F/dt = 100A/\mu s$           | --    | 152  | --        | ns         |
| Reverse Recovery Charge                 | $Q_{rr}$      |                                                               | --    | 1    | --        | $\mu C$    |

**Notes:**


1. Repetitive Rating: Pulse width limited by maximum junction temperature
2.  $L = 1mH, V_{DD} = 30V, R_G = 25\Omega$ , Starting  $T_J = 25^\circ\text{C}$
3. Pulse Test: Pulse width  $\leq 300\mu s$ , Duty Cycle  $\leq 1\%$

**Ordering Information**


| Ordernumber        | Package | Marking | Operation Temperature Range | MSL Grade | Ship, Quantity | Green |
|--------------------|---------|---------|-----------------------------|-----------|----------------|-------|
| IRFS4615TRLPBF-JSM | TO-263  | FS4615  | -55 to $150^\circ\text{C}$  | 1         | T&R, 800       | RoHS  |

**Typical Characteristics**  $T_J = 25^\circ\text{C}$ , unless otherwise noted


**Figure 1. Output Characteristics ( $T_J = 25^\circ\text{C}$ )**




**Figure 2. Transfer Characteristics**




**Figure 3. Drain to Source Resistance vs. Drain Current**




**Figure 4.  $BV_{DSS}$  Variation vs. Temperature**



**Figure 5. Drain to Source Voltage vs. Gate to Source Voltage**



**Figure 6. Body Diode Forward Characteristics**



Typical Characteristics  $T_J = 25^\circ\text{C}$ , unless otherwise noted

Figure 7. Capacitance




Figure 8. Gate Charge




Figure 9. Transient Thermal Impedance




Figure A: Gate Charge Test Circuit and Waveform




Figure B: Resistive Switching Test Circuit and Waveform






Figure C: Unclamped Inductive Switching Test Circuit and Waveform



Package Outline: TO-263



| SYMBOL | MIN     | NOM  | MAX   |
|--------|---------|------|-------|
| A      | 4.30    | 4.57 | 4.72  |
| A1     | 0       | 0.10 | 0.25  |
| b      | 0.71    | 0.81 | 0.91  |
| c      | 0.30    | ---  | 0.60  |
| c2     | 1.17    | 1.27 | 1.37  |
| D      | 8.50    | ---  | 9.35  |
| E      | 9.80    | ---  | 10.45 |
| e      | 2.54BSC |      |       |
| H      | 14.70   | ---  | 15.75 |
| L      | 2.00    | 2.30 | 2.74  |
| L1     | 1.12    | 1.27 | 1.42  |
| L2     | ---     | ---  | 1.75  |



## Revision History

| Rev. | Change          | Date      |
|------|-----------------|-----------|
| V1.0 | Initial version | 6/27/2021 |
|      |                 |           |

## Important Notice

JSMSEMI Semiconductor (JSMSEMI) PRODUCTS ARE NEITHER DESIGNED NOR INTENDED FOR USE IN MILITARY AND/OR AEROSPACE, AUTOMOTIVE OR MEDICAL DEVICES OR SYSTEMS UNLESS THE SPECIFIC JSMSEMI PRODUCTS ARE SPECIFICALLY DESIGNATED BY JSMSEMI FOR SUCH USE. BUYERS ACKNOWLEDGE AND AGREE THAT ANY SUCH USE OF JSMSEMI PRODUCTS WHICH JSMSEMI HAS NOT DESIGNATED FOR USE IN MILITARY AND/OR AEROSPACE, AUTOMOTIVE OR MEDICAL DEVICES OR SYSTEMS IS SOLELY AT THE BUYER' S RISK.

JSMSEMI assumes no liability for application assistance or customer product design. Customers are responsible for their products and applications using JSMSEMI products.

Resale of JSMSEMI products or services with statements diferent from or beyond the parameters stated by JSMSEMI for that product or service voids all express and any implied warranties for the associated JSMSEMI product or s ervice. JSMSEMI is not responsible or liable for any such statements.

JSMSEMI All Rights Reserved. Information and data in this document are owned by JSMSEMI wholly and may not be edited, reproduced, or redistributed in any way without the express written consent from JSMSEMI.

Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the JSMSEMI product that you intend to use.

For additional information please contact Kevin@jsemsemi.com or visit www.jsemsemi.com